

Errai

Errai Reference Guide

Preface	ix
1. Document Conventions	ix
2. Feedback	ix
1. Introduction	1
1.1. What is it?	1
1.2. Required software	1
2. Messaging	3
2.1. Messaging Overview	3
2.2. Messaging API Basics	3
2.2.1. Sending Messages with the Client Bus	3
2.2.2. Receiving Messages on the Server Bus / Server Services	5
2.2.3. Sending Messages with the Server Bus	5
2.2.4. Receiving Messages on the Client Bus/ Client Services	6
2.2.5. Local Services	7
2.3. Single-Response Conversations & Pseudo-Synchronous Messaging	8
2.4. Sender Inferred Subjects	8
2.5. Broadcasting	9
2.6. Client-to-Client Communication	9
2.6.1. Relay Services	9
2.7. Message Routing Information	10
2.8. Handling Errors	11
2.8.1. Handling global message transport errors	12
2.9. Asynchronous Message Tasks	12
2.10. Repeating Tasks	13
2.11. Queue Sessions	14
2.11.1. Lifecycle	14
2.11.2. Scopes	14
2.12. Client Logging and Error Handling	15
2.13. Wire Protocol (J.REP)	15
2.13.1. Payload Structure	15
2.13.2. Message Routing	18
2.13.3. Bus Management and Handshaking Protocols	18
2.14. Conversations	20
2.15. WebSockets	20
2.15.1. Configuring the sideband server	21
2.15.2. Deploying with JBoss AS 7	21
2.16. Bus Lifecycle	22
2.16.1. Turning Server Communication On and Off	22
2.16.2. Observing Bus Lifecycle State and Communication Status	23
2.17. Shadow Services	24
2.18. Debugging Messaging Problems	24
3. Dependency Injection	27
3.1. Container Wiring	28
3.2. Wiring server side components	30

3.3. Scopes	30
3.3.1. Dependent Scope	30
3.4. Built-in Extensions	31
3.4.1. Bus Services	31
3.4.2. Client Components	32
3.4.3. Lifecycle Tools	35
3.4.4. Timed Methods	36
3.5. Client-Side Bean Manager	36
3.5.1. Looking up beans	37
3.5.2. Availability of beans	38
3.6. Alternatives and Mocks	38
3.6.1. Alternatives	38
3.6.2. Test Mocks	40
3.7. Bean Lifecycle	41
3.7.1. Destruction of Beans	41
4. Errai CDI	45
4.1. Features and Limitations	45
4.1.1. Other features	46
4.2. Events	46
4.2.1. Conversational events	47
4.2.2. Client-Server Event Example	48
4.3. Producers	51
4.4. safe dynamic lookup	52
4.5. Deploying Errai CDI	52
4.5.1. Deployment in Development Mode	53
4.5.2. Deployment to a Servlet Engine	54
4.5.3. Deployment to an Application Server	54
5. Marshalling	55
5.1. Mapping Your Domain	55
5.1.1. @Portable and @NonPortable	55
5.1.2. Manual Mapping	59
5.1.3. Manual Class Mapping	61
5.1.4. Custom Marshallers	63
6. Remote Procedure Calls (RPC)	67
6.1. Making calls	68
6.1.1. Proxy Injection	69
6.2. Handling exceptions	69
6.2.1. Global RPC exception handler	70
6.3. Client-side Interceptors	70
6.4. Session and request objects in RPC endpoints	71
6.5. Batching remote calls	72
7. Errai JAX-RS	73
7.1. Getting Started	73
7.1.1. Dependencies	73

7.1.2. GWT Module	74
7.1.3. Server-Side JAX-RS Implementation	74
7.1.4. Shared JAX-RS Interface	75
7.2. Creating Requests	76
7.2.1. Proxy Injection	77
7.3. Handling Responses	78
7.4. Client-side Interceptors	79
7.5. Wire Format	80
7.6. Configuration	80
7.6.1. Configuring the default root path of JAX-RS endpoints	80
7.6.2. Enabling Jackson marshalling	81
8. Errai JPA	83
8.1. Getting Started	84
8.1.1. Compile-time dependency	84
8.1.2. GWT Module Descriptor	84
8.1.3. INF/persistence.xml	84
8.1.4. Declaring an Entity Class	85
8.1.5. Entity Lifecycle States	88
8.1.6. Obtaining an instance of EntityManager	89
8.1.7. Named Queries	91
8.1.8. Entity Lifecycle Events	92
8.1.9. JPA Metamodel	94
8.1.10. JPA Features Not Implemented in Errai 2.1	94
8.1.11. Other Caveats for Errai 2.1 JPA	95
8.2. Errai JPA Data Sync	95
8.2.1. How To Use It	96
9. Data Binding	103
9.1. Getting Started	103
9.1.1. Compile-time dependency	103
9.1.2. GWT module descriptor	103
9.1.3. Bindable Objects	103
9.1.4. Initializing a DataBinder	104
9.2. Creating Bindings	105
9.3. Specifying Converters	106
9.3.1. Registering a global default converter	106
9.3.2. Providing a binding-specific converter	107
9.4. Property Change Handlers	107
9.5. Declarative Binding	108
9.5.1. Default, Simple, and Chained Property Bindings	109
9.5.2. Data Converters	110
9.5.3. Replacing a model object	110
9.6. Bean validation	111
9.6.1. Excluding Classes from Validation	112
10. Errai UI	115

10.1. Get started	115
10.1.1. App.gwt.xml	115
10.1.2. pom.xml	115
10.1.3. Working Demo	116
10.2. Use Errai UI Composite components	116
10.2.1. Inject a single instance	116
10.2.2. Inject multiple instances (for iteration)	116
10.3. Create a @Templated Composite component	117
10.3.1. Basic component	117
10.3.2. Custom template names	117
10.4. Create an HTML template	118
10.4.1. Select a template from a larger HTML file	118
10.5. Use other Widgets in a composite component	120
10.5.1. Annotate Widgets in the template with @DataField	120
10.5.2. Add corresponding attributes to the HTML template	121
10.6. How HTML templates are merged with Components	122
10.6.1. Example	122
10.6.2. Element attributes (template wins)	123
10.6.3. DOM Elements (component field wins)	123
10.6.4. Inner text and inner HTML (preserved when component implements HasText or HasHTML)	124
10.7. Event handlers	124
10.7.1. Concepts	124
10.7.2. GWT events on Widgets	124
10.7.3. GWT events on DOM Elements	125
10.7.4. Native DOM events on Elements	125
10.8. Data Binding	127
10.8.1. Default, Simple, and Chained Property Bindings	128
10.8.2. Binding of Lists	129
10.8.3. Data Converters	131
10.9. Nest Composite components	131
10.10. Extend Composite components	131
10.10.1. Template	132
10.10.2. Parent component	132
10.10.3. Child component	133
10.11. Stylesheet binding	133
10.12. Internationalization (i18n)	134
10.13. Extended styling with LESS	137
11. Errai UI Navigation	139
11.1. Getting Started	139
11.1.1. Compile-time dependency	139
11.1.2. GWT Module Descriptor	140
11.2. How it Works	140
11.2.1. Declaring a Page	140

11.2.2. Declaring a Link with TransitionAnchor	143
11.2.3. Declaring a Manual Link	144
11.2.4. Following a Manual Link	144
11.2.5. Installing the Navigation Panel into the User Interface	145
11.2.6. Overriding the default Navigating Panel type	146
11.2.7. Viewing the Generated Navigation Graph	147
12. Errai Cordova (Mobile Support)	149
12.1. Get started	149
12.1.1. App.gwt.xml	149
12.2. Integrate with native hardware	149
12.3. Maven build	151
12.4. AeroGear Wrappers	152
12.4.1. Pipes	152
12.4.2. Stores	153
12.4.3. Authentication	153
13. Logging	155
13.1. What is slf4j?	155
13.2. Client-Side Setup	155
13.3. Server-Side Setup	155
13.4. Example Usage	155
13.5. Logger Names	156
14. Configuration	157
14.1. ErraiApp.properties	157
14.1.1. As a Marker File	157
14.1.2. As a Configuration File	157
14.1.3.	158
14.2. Messaging (Errai Bus) Configuration	158
14.2.1. Disabling remote communication	158
14.2.2. Configuring an alternative remote bus endpoint	159
14.2.3. ErraiService.properties	159
14.2.4. Servlet Configuration	162
15. Troubleshooting & FAQ	167
15.1. Why does it seem that Errai can't see my class at compile time?	167
15.2. Why am I getting "java.lang.ClassFormatError: Illegal method name "<init> \$" in class org/xyz/package/MyClass"?	167
15.3. I'm getting "java.lang.RuntimeException: There are no proxy providers registered yet." in my @PostConstruct method!	168
16. Upgrade Guide	169
16.1. Upgrading from 1.* to 2.0	169
16.2. Upgrading from 2.0.Beta to 2.0.*.Final	170
16.3. Upgrading from Errai 2.2.x to 2.4 or 3.0	170
17. Downloads	173
18. Sources	175
19. Reporting problems	177

20. Errai License	179
A. Revision History	181

Preface

1. Document Conventions

2. Feedback

Introduction

1.1. What is it?

Errai is a GWT-based framework for building rich web applications using next-generation web technologies. Built on-top of ErraiBus, the framework provides a unified federation and RPC infrastructure with true, uniform, asynchronous messaging across the client and server.

1.2. Required software

Errai requires a JDK version 6 or higher and depends on Apache Maven to build and run the examples, and for leveraging the quickstart utilities.

- JDK 6.0: <http://java.sun.com/javase/downloads/index.jsp>
- Apache Maven: <http://maven.apache.org/download.html>



Launching maven the first time

Please note, that when launching maven the first time on your machine, it will fetch all dependencies from a central repository. This may take a while, because it includes downloading large binaries like GWT SDK. However, subsequent builds are not required to go through this step and will be much faster.

Messaging

This section covers the core messaging concepts of the ErraiBus messaging framework.

ErraiBus provides a straight-forward approach to a complex problem space. Providing common APIs across the client and server, developers will have no trouble working with complex messaging scenarios from building instant messaging clients, stock tickers, to monitoring instruments. There's no more messing with RPC APIs, or unweildy AJAX or COMET frameworks. We've built it all in to one, concise messaging framework. It's single-paradigm, and it's fun to work with.

2.1. Messaging Overview

It's important to understand the concept of how messaging works in ErraiBus. Service endpoints are given string-based names that are referenced by message senders. There is no difference between sending a message to a client-based service, or sending a message to a server-based service. In fact, a service of the same name may co-exist on both the client and the server and both will receive all messages bound for that service name, whether they are sent from the client or from the server.

Services are lightweight in ErraiBus, and can be declared liberally and extensively within your application to provide a message-based infrastructure for your web application. It can be tempting to think of ErraiBus simply as a client-server communication platform, but there is a plethora of possibilities for using ErraiBus purely with the GWT client context, such as a way to advertise and expose components dynamically, to get around the lack of reflection in GWT.

In fact, ErraiBus was originally designed to run completely within the client but quickly evolved into having the capabilities it now has today. So keep that in mind when you run up against problems in the client space that could benefit from runtime federation.

2.2. Messaging API Basics

The `MessageBuilder` is the heart of the messaging API in ErraiBus. It provides a fluent / builder API, that is used for constructing messages. All three major message patterns can be constructed from the `MessageBuilder`.

Components that want to receive messages need to implement the `MessageCallback` interface.

But before we dive into the details, let's look at some use cases first.

2.2.1. Sending Messages with the Client Bus

In order to send a message from a client you need to create a `Message` and send it through an instance of `MessageBus`. In this simple example we send it to the subject 'HelloWorldService'.

```
public class HelloWorld implements EntryPoint {
```

```
// Get an instance of the RequestDispatcher
private RequestDispatcher dispatcher = ErraiBus.getDispatcher();

public void onModuleLoad() {
    Button button = new Button("Send message");

    button.addClickHandler(new ClickHandler() {
        public void onClick(ClickEvent event) {
            // Send a message to the 'HelloWorldService'.
            MessageBuilder.createMessage()
                .toSubject("HelloWorldService") // (1)
                .signalling() // (2)
                .noErrorHandling() // (3)
                .sendNowWith(dispatcher); // (4)
        }
    });

    [...]
}
}
```

In the above example we build and send a message every time the button is clicked. Here's an explanation of what's going on as annotated above:

1. We specify the subject we wish to send a message to. In this case, "HelloWorldService".
2. We indicate that we wish to only signal the service, meaning, that we're not sending a qualifying command to the service. For information on this, read the section on *Protocols*.
3. We indicate that we do not want to provide an `ErrorCallback` to deal with errors for this message.
4. We transmit the message by providing an instance to the `RequestDispatcher`



Important

An astute observer will note that access to the `RequestDispatcher` differs within client code and server code. Because the client code does not run within a container, access to the `RequestDispatcher` and `MessageBus` is statically accessed using the `ErraiBus.get()` and `ErraiBus.getDispatcher()` methods. The server-side code, conversely, runs inside a dependency container for managing components. See the section on Errai IOC and Errai CDI for using `ErraiBus` from a client-side container.

When using Errai IOC or CDI, you can also use the `Sender<T>` interface to send messages.

2.2.2. Receiving Messages on the Server Bus / Server Services

Every message has a sender and at least one receiver. A receiver is as it sounds--it receives the message and does something with it. Implementing a receiver (also referred to as a service) is as simple as implementing our standard `MessageCallback` interface, which is used pervasively across, both client and server code. Let's begin with server side component that receives messages:

```
@Service
public class HelloWorldService implements MessageCallback {
    public void callback(Message message) {
        System.out.println("Hello, World!");
    }
}
```

Here we declare an extremely simple service. The `@Service` annotation provides a convenient, meta-data based way of having the bus auto-discover and deploy the service.

2.2.3. Sending Messages with the Server Bus

In the following example we extend our server side component to reply with a message when the callback method is invoked. It will create a message and address it to the subject 'HelloWorldClient':

```
@Service
public class HelloWorldService implements MessageCallback {

    private RequestDispatcher dispatcher;

    @Inject
    public HelloWorldService(RequestDispatcher dispatcher) {
        dispatcher = dispatcher;
    }

    public void callback(CommandMessage message) {
        // Send a message to the 'HelloWorldClient'.
        MessageBuilder.createMessage()
            .toSubject("HelloWorldClient") // (1)
            .signalling() // (2)
            .with("text", "Hi There") // (3)
            .noErrorHandling() // (4)
            .sendNowWith(dispatcher); // (5)
    }
}
```

```
}
```

The above example shows a service which sends a message in response to receiving a message. Here's what's going on:

1. We specify the subject we wish to send a message to. In this case, "HelloWorldClient". We are sending this message to all clients which are listening in on this subject. For information on how to communicate with a single client, see Section 2.6.
2. We indicate that we wish to only signal the service, meaning that we're not sending a qualifying command to the service. For information on this, read the section on Protocols.
3. We add a message part called "text" which contains the value "Hi there".
4. We indicate that we do not want to provide an `errorCallback` to deal with errors for this message.
5. We transmit the message by providing an instance of the `RequestDispatcher` .

2.2.4. Receiving Messages on the Client Bus/ Client Services

Messages can be received asynchronously and arbitrarily by declaring callback services within the client bus. As ErraiBus maintains an open COMET channel at all times, these messages are delivered in real time to the client as they are sent. This provides built-in push messaging for all client services.

```
public class HelloWorld implements EntryPoint {

    private MessageBus bus = ErraiBus.get();

    public void onModuleLoad() {
        [...]

        /*
         * Declare a service to receive messages on the subject
         * "BroadcastReceiver".
         */
        bus.subscribe("BroadcastReceiver", new MessageCallback() {
            public void callback(CommandMessage message) {
                /*
                 * When a message arrives, extract the "text" field and
                 * do something with it
                 */
                String messageText = message.get(String.class, "text");
            }
        });
    }
}
```

```

    });

    [...]
}
}

```

In the above example, we declare a new client service called "BroadcastReceiver" which can now accept both local messages and remote messages from the server bus. The service will be available in the client to receive messages as long the client bus is and the service is not explicitly de-registered.

2.2.5. Local Services

On the client or the server, you can create a local receiver which only receives messages that originated on the local bus. A local server-side service only receives messages that originate on that server, and a local client-side service only receives messages that originated on that client.

To create a local receiver using the declarative API, use the `@Local` annotation in conjunction with `@Service` :

```

@Local
@Service
public class HelloIntrovertService implements MessageCallback {
    public void callback(Message message) {
        System.out.println("Hello, me!");
    }
}

```

To create a local receiver using through programmatic service registration, use the `subscribeLocal()` method in place of `subscribe()` :

```

public void registerLocalService(MessageBus bus) {
    bus.subscribeLocal("LocalBroadcastReceiver", new MessageCallback() {
        public void callback(Message message) {
            String messageText = message.get(String.class, "text");
        }
    });
}

```

Both examples above work in client- and server-side code.

2.3. Single-Response Conversations & Pseudo-Synchronous Messaging

It is possible to construct a message and a default response handler as part of the `MessageBuilder` API. It should be noted, that multiple replies will not be possible and will result an exception if attempted. Using this aspect of the API is very useful for doing simple pseudo-synchronous conversive things.

You can do this by specifying a `MessageCallback` using the `repliesTo()` method in the `MessageBuilder` API after specifying the error handling of the message.

```
MessageBuilder.createMessage()  
    .toSubject("ConversationalService").signalling()  
    .with("SomeField", someValue)  
    .noErrorHandling()  
    .repliesTo(new MessageCallback() {  
        public void callback(Message message) {  
            System.out.println("I received a response");  
        }  
    })
```

See the next section on how to build conversational services that can respond to such messages.

2.4. Sender Inferred Subjects

It is possible for the sender to infer, to whatever conversational service it is calling, what subject it would like the reply to go to. This is accomplished by utilizing the standard `MessageParts.ReplyTo` message part. Using this methodology for building conversations is generally encouraged.

Consider the following client side code:

```
MessageBuilder.createMessage()  
    .toSubject("ObjectService").signalling()  
    .with(MessageParts.ReplyTo, "ClientEndpoint")  
    .noErrorHandling().sendNowWith(dispatcher);
```

And the conversational code on the server (for service `ObjectService`):

```
MessageBuilder.createConversation(message)  
    .subjectProvided().signalling()
```

```
.with("Records", records)
.noErrorHandling().reply();
```

In the above examples, assuming that the latter example is inside a service called "ObjectService" and is referencing the incoming message that was sent in the former example, the message created will automatically reference the `ReplyTo` subject that was provided by the sender, and send the message back to the subject desired by the client on the client that sent the message.

2.5. Broadcasting

Broadcasting messages to all clients listening on a specific subject is quite simple and involves nothing more than forgoing use of the reply API. For instance:

```
MessageBuilder.createMessage().
    .toSubject("MessageListener")
    .with("Text", "Hello, from your overlords in the cloud")
    .noErrorHandling().sendGlobalWith(dispatcher);
```

If sent from the server, all clients currently connected, who are listening to the subject "MessageListener" will receive the message. It's as simple as that.

2.6. Client-to-Client Communication

Communication from one client to another client is not directly possible within the bus federation, by design. This isn't to say that it's not possible. But one client cannot see a service within the federation of another client. We institute this limitation as a matter of basic security. But many software engineers will likely find the prospects of such communication appealing, so this section will provide some basic pointers on how to go about accomplishing it.

2.6.1. Relay Services

The essential architectural thing you'll need to do is create a relay service that runs on the server. Since a service advertised on the server is visible to all clients and all clients are visible to the server, you might already see where we're going with this.

By creating a service on the server which accepts messages from clients, you can create a simple protocol on-top of the bus to enable quasi peer-to-peer communication. (We say quasi, because it still needs to be routed through the server)

While you can probably imagine simply creating a broadcast-like service which accepts a message from one client and broadcasts it to the rest of the world, it may be less clear how to go about routing from one particular client to another particular client, so we'll focus on that problem. This is covered in [Section 2.7, "Message Routing Information"](#)

2.7. Message Routing Information

Every message that is sent between a local and remote (or server and client) buses contain session routing information. This information is used by the bus to determine what outbound queues to use to deliver the message to, so they will reach their intended recipients. It is possible to manually specify this information to indicate to the bus, where you want a specific message to go.

You can obtain the `SessionID` directly from a `Message` by getting the `QueueSession` resource:

```
QueueSession sess = message.getResource(QueueSession.class, Resources.Session.name());
String sessionId = sess.getSessionId();
```

You can extract the `SessionID` from a message so that you may use it for routing by obtaining the `QueueSession` resource from the `Message`. For example:

```
...
public void callback(Message message) {
    QueueSession sess = message.getResource(QueueSession.class, Resources.Session.name());
    String sessionId = sess.getSessionId();

    // Record this sessionId somewhere.
    ...
}
```

The `SessionID` can then be stored in a medium, say a `Map`, to cross-reference specific users or whatever identifier you wish to allow one client to obtain a reference to the specific `SessionID` of another client. In which case, you can then provide the `SessionID` as a `MessagePart` to indicate to the bus where you want the message to go.

```
MessageBuilder.createMessage()
    .toSubject("ClientMessageListener")
    .signalling()
    .with(MessageParts.SessionID, sessionId)
    .with("Message", "We're relaying a message!")
    .noErrorHandling().sendNowWith(dispatcher);
```

By providing the `SessionID` part in the message, the bus will see this and use it for routing the message to the relevant queue.

It may be tempting however, to try and include destination `SessionIDs` at the client level, assuming that this will make the infrastructure simpler. But this will not achieve the desired results, as the bus treats `SessionIDs` as transient. Meaning, the `SessionID` information is not ever transmitted from bus-to-bus, and therefore is only directly relevant to the proximate bus.

2.8. Handling Errors

Asynchronous messaging necessitates the need for asynchronous error handling. Luckily, support for handling errors is built directly into the `MessageBuilder` API, utilizing the `ErrorCallback` interface. In the examples shown in previous exceptions, error handling has been glossed over with ubiquitous usage of the `noErrorHandling()` method while building messaging. We chose to require the explicit use of such a method to remind developers of the fact that they are responsible for their own error handling, requiring you to explicitly make the decision to forego handling potential errors.

As a general rule, you should *always handle your errors*. It will lead to faster and quicker identification of problems with your applications if you have error handlers, and generally help you build more robust code.

```
MessageBuilder.createMessage()
    .toSubject("HelloWorldService")
    .signalling()
    .with("msg", "Hi there!")
    .errorsHandledBy(new ErrorCallback() {
        public boolean error(Message message, Throwable throwable) {
            throwable.printStackTrace();
            return true;
        }
    })
    .sendNowWith(dispatcher);
```

The addition of error handling at first may put off developers as it makes code more verbose and less-readable. This is nothing that some good practice can't fix. In fact, you may find cases where the same error handler can appropriately be shared between multiple different calls.

```
ErrorCallback error = new ErrorCallback() {
    public boolean error(Message message, Throwable throwable) {
        throwable.printStackTrace();
        return true;
    }
}

MessageBuilder.createMessage()
```

```
.toSubject("HelloWorldService")
.signalling()
.with("msg", "Hi there!")
.errorsHandledBy(error)
.sendNowWith(dispatcher);
```

The error handler is required to return a `boolean` value. This is to indicate whether or not Errai should perform the default error handling actions it would normally take during a failure. You will almost always want to return `true` here, unless you are trying to explicitly suppress some undesirably activity by Errai, such as automatic subject-termination in conversations. But this is almost never the case.

2.8.1. Handling global message transport errors

You may need to detect problems which occur on the bus at runtime. The client bus API provides a facility for doing this in the `org.jboss.errai.bus.client.framework.ClientMessageBus` using the `addTransportErrorHandler()` method.

A `TransportErrorHandler` is an interface which you can use to define error handling behavior in the event of a transport problem.

For example:

```
messageBus.addTransportErrorHandler(new TransportErrorHandler() {
    public void onError(TransportError error) {
        // error handling code.
    }
});
```

The `TransportError` interface represents the details of an error from the bus. It contains a set of methods which can be used for determining information on the initial request which triggered the error, if the error occurred over HTTP or WebSockets, status code information, etc. See the JavaDoc for more information.

2.9. Asynchronous Message Tasks

In some applications, it may be necessary or desirable to delay transmission of, or continually stream data to a remote client or group of clients (or from a client to the server). In cases like this, you can utilize the `replyRepeating()`, `replyDelayed()`, `sendRepeating()` and `sendDelayed()` methods in the `MessageBuilder`.

Delayed Tasks Sending a task with a delay is straight forward. Simply utilize the appropriate method (either `replyDelayed()` or `sendDelayed()`).

```

MessageBuilder.createConversation(msg)
    .toSubject("FunSubject")
    .signalling()
    .noErrorHandling()
    .replyDelayed(TimeUnit.SECONDS, 5); // sends the message after 5 seconds.

```

or

```

MessageBuilder.createMessage()
    .toSubject("FunSubject")
    .signalling()
    .noErrorHandling()
    .sendDelayed(requestDispatcher, TimeUnit.SECONDS, 5); // sends the message
after 5 seconds.

```

2.10. Repeating Tasks

A repeating task is sent using one of the `MessageBuilder`'s `repeatXXX()` methods. The task will repeat indefinitely until cancelled (see next section).

```

MessageBuilder.createMessage()
    .toSubject("FunSubject")
    .signalling()
    .withProvided("time", new ResourceProvider<String>() {
        SimpleDateFormat fmt = new SimpleDateFormat("hh:mm:ss");

        public String get() {
            return fmt.format(new Date(System.currentTimeMillis()));
        }
    })
    .noErrorHandling()
    .sendRepeatingWith(requestDispatcher, TimeUnit.SECONDS, 1); //sends a message
every 1 second

```

The above example sends a message every 1 second with a message part called "time" , containing a formatted time string. Note the use of the `withProvided()` method; a provided message part is calculated at the time of transmission as opposed to when the message is constructed.

Cancelling an Asynchronous TaskA delayed or repeating task can be cancelled by calling the `cancel()` method of the `AsyncTask` instance which is returned when creating a task. Reference to the `AsyncTask` object can be retained and cancelled by any other thread.

```
AsyncTask task = MessageBuilder.createConversation(message)
    .toSubject("TimeChannel").signalling()
    .withProvided(TimeServerParts.TimeString, new ResourceProvider<String>() {
        public String get() {
            return String.valueOf(System.currentTimeMillis());
        }
    }).defaultErrorHandler().replyRepeating(TimeUnit.MILLISECONDS, 100);

...

// cancel the task and interrupt it's thread if necessary.
task.cancel(true);
```

2.11. Queue Sessions

The ErraiBus maintains it's own separate session management on-top of the regular HTTP session management. While the queue sessions are tied to, and dependant on HTTP sessions for the most part (meaning they die when HTTP sessions die), they provide extra layers of session tracking to make dealing with complex applications built on Errai easier.

2.11.1. Lifecycle

The lifecycle of a session is bound by the underlying HTTP session. It is also bound by activity thresholds. Clients are required to send heartbeat messages every once in a while to maintain their sessions with the server. If a heartbeat message is not received after a certain period of time, the session is terminated and any resources are deallocated.

2.11.2. Scopes

One of the things Errai offers is the concept of session and local scopes.

2.11.2.1. Session Scope

A session scope is scoped across all instances of the same session. When a session scope is used, any parameters stored will be accessible and visible by all browser instances and tabs.

The `SessionContext` helper class is used for accessing the session scope.

```
public class TestService implements MessageCallback {
    public void callback(final Message message) {
```

```

    // obtain a reference to the session context by referencing the incoming
    message.
    SessionContext injectionContext = SessionContext.get(message);

    // set an attribute.
    injectionContext.setAttribute("MyAttribute", "Foo");
}
}

```

2.11.2.2. Local Scope

A local scope is scoped to a single browser instance. But not to a single session.

In a browser a local scope would be confined to a tab or a window within a browser. You can store parameters inside a local scope just like with a session by using the `LocalContext` helper class.

```

public class TestService implements MessageCallback {
    public void callback(final Message message) {
        // obtain a reference to the local context by referencing the incoming message.
        LocalContext injectionContext = LocalContext.get(message);

        // set an attribute.
        injectionContext.setAttribute("MyAttribute", "Foo");
    }
}

```

2.12. Client Logging and Error Handling

2.13. Wire Protocol (J.REP)

ErraiBus implements a JSON-based wire protocol which is used for the federated communication between different buses. The protocol specification encompasses a standard JSON payload structure, a set of verbs, and an object marshalling protocol. The protocol is named J.REP. Which stands for JSON Rich Event Protocol.

2.13.1. Payload Structure

All wire messages sent across are assumed to be JSON arrays at the outermost element, contained in which, there are $0..n$ messages. An empty array is considered a no-operation, but should be counted as activity against any idle timeout limit between federated buses.

Example 2.1. Figure 1 - Example J.REP Payload

```
[
```

```
{ "ToSubject" : "SomeEndpoint", "Value" : "SomeValue" },  
  { "ToSubject" : "SomeOtherEndpoint", "Value" : "SomeOtherValue" }  
]
```

In **Figure 1**, we see an example of a J.REP payload containing two messages. One bound for an endpoint named "SomeEndpoint" and the other bound for the endpoint "SomeOtherEndpoint". They both include a payload element "Value" which contain strings. Let's take a look at the anatomy of an individual message.

Example 2.2. Figure 2 - An J.REP Message

```
{  
  "ToSubject" : "TopicSubscriber",  
  "CommandType" : "Subscribe",  
  "Value" : "happyTopic",  
  "ReplyTo" : "MyTopicSubscriberReplyTo"  
}
```

The message shown in **Figure 2** shows a very vanilla J.REP message. The keys of the JSON Object represent individual *message parts*, with the values representing their corresponding values. The standard J.REP protocol encompasses a set of standard message parts and values, which for the purposes of this specification we'll collectively refer to as the protocol verbs.

The following table describes all of the message parts that a J.REP capable client is expected to understand:

Part	Required	JSON Type	Description
ToSubject	Yes	String	Specifies the subject within the bus, and its federation, which the message should be routed to.
CommandType	No	String	Specifies a command verb to be transmitted to the receiving subject. This is an optional part of a message contract, but is required for using management services
ReplyTo	No	String	Specifies to the receiver what subject it should reply to

Part	Required	JSON Type	Description
			in response to this message.
Value	No	Any	A recommended but not required standard payload part for sending data to services
PriorityProcessing	No	Number	A processing order salience attribute. Messages which specify priority processing will be processed first if they are competing for resources with other messages in flight. Note: the current version of ErraiBus only supports two salience levels (0 and >1). Any non-zero salience in ErraiBus will be given the same priority relative to 0 salience messages
ErrorMessage	No	String	An accompanying error message with any serialized exception
Throwable	No	Object	If applicable, an encoded object representing any remote exception that was thrown while dispatching the specified service

2.13.1.1. Built-in Subjects

The table contains a list of reserved subject names used for facilitating things like bus management and error handling. A bus should never allow clients to subscribe to these subjects directly.

Subject	Description
ClientBus	The self-hosted message bus endpoint on the client
ServerBus	The self-hosted message bus endpoint on the server
ClientBusErrors	The standard error receiving service for clients

As this table indicates, the bus management protocols in J.REP are accomplished using self-hosted services. See the section on **Bus Management and Handshaking Protocols** for details.

2.13.2. Message Routing

There is no real distinction in the J.REP protocol between communication with the server, versus communication with the client. In fact, it assumed from an architectural standpoint that there is no real distinction between a client and a server. Each bus participates in a flat-namespaced federation. Therefore, it is possible that a subject may be observed on both the server and the client.

One in-built assumption of a J.REP-compliant bus however, is that messages are routed within the auspices of session isolation. Consider the following diagram:

Figure 2.1. Figure 3 - Topology of a J.REP Messaging Federation

In **Figure 3**, it is possible for *Client A* to send messages to the subjects *ServiceA* and *ServiceB*. But it is not possible to address messages to *ServiceC*. Conversely, *Client B* can address messages to *ServiceC* and *ServiceB*, but not *ServiceA*.

2.13.3. Bus Management and Handshaking Protocols

Federation between buses requires management traffic to negotiate connections and manage visibility of services between buses. This is accomplished through services named `ClientBus` and `ServerBus` which both implement the same protocol contracts which are defined in this section.

2.13.3.1. ServerBus and ClientBus commands

Both bus services share the same management protocols, by implementing verbs (or commands) that perform different actions. These are specified in the protocol with the `CommandType` message part. The following table describes these commands:

Table 2.1. Message Parts for Bus Commands:

Command / Verb	Message Parts	Description
ConnectToQueue	N/A	The first message sent by a connecting client to begin the handshaking process.

Command / Verb	Message Parts	Description
CapabilitiesNotice	CapabilitiesFlags	A message sent by one bus to another to notify it of its capabilities during handshake (for instance long polling or websockets)
FinishStateSync	N/A	A message sent from one bus to another to indicate that it has now provided all necessary information to the counter-party bus to establish the federation. When both buses have sent this message to each other, the federation is considered active.
RemoteSubscribe	Subject <i>OR</i> SubjectsList	A message sent to the remote bus to notify it of a service or set of services which it is capable of routing to.
RemoteUnsubscribe	Subject	A message sent to the remote bus to notify it that a service is no longer available.
Disconnect	Reason	A message sent to a server bus from a client bus to indicate that it wishes to disconnect and defederate. Or, when sent from the client to server, indicates that the session has been terminated.
SessionExpired	N/A	A message sent to a client bus to indicate that its messages are no longer being routed because it no longer has an active session
Heartbeat	N/A	A message sent from one bus to another periodically to indicate it is still active.

Part	Required	JSON Type	Description
CapabilitiesFlags	Yes	String	A comma delimited string of capabilities

Part	Required	JSON Type	Description
			the bus is capable of us
Subject	Yes	String	The subject to subscribe or unsubscribe from
SubjectsList	Yes	Array	An array of strings representing a list of subjects to subscribe to

2.14. Conversations

Conversations are message exchanges which are between a single client and a service. They are a fundamentally important concept in ErraiBus, since by default, a message will be broadcast to all client services listening on a particular channel.

When you create a reply with an incoming message, you ensure that the message you are sending back is received by the same client which sent the incoming message. A simple example:

```
@Service
public class HelloWorldService implements MessageCallback {
    public void callback(CommandMessage message) {
        // Send a message to the 'HelloWorldClient' on the client that sent us the
        // the message.
        MessageBuilder.createConversation(message)
            .toSubject("HelloWorldClient")
            .signalling()
            .with("text", "Hi There! We're having a reply!")
            .noErrorHandling().reply();
    }
}
```

Note that the only difference between the example in the previous section and this is the use of the `createConversation()` method with `MessageBuilder`.

2.15. WebSockets

ErraiBus has support for WebSocket-based communication. When WebSockets are enabled, capable web browsers will attempt to upgrade their COMET-based communication with the server-side bus to use a WebSocket channel.

There are two different ways the bus can enable WebSockets. The first uses a sideband server, which is a small, lightweight server which runs on a different port from the application server. The second is native JBoss AS 7-based integration.

2.15.1. Configuring the sideband server

Activating the sideband server is as simple as adding the following to the `ErraiService.properties` file:

```
errai.bus.enable_web_socket_server=true
```

The default port for the sideband server is 8085 . You can change this by specifying a port with the `errai.bus.web_socket_port` property in the `ErraiService.properties` file.

2.15.2. Deploying with JBoss AS 7

It is currently necessary use the native connector in JBoss AS for WebSockets to work. So the first step is to configure your JBoss AS instance to use the native connector by changing the `domain/configuration/domain.xml` file, and change the line:

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-host" native="false">
```

to:

```
<subsystem xmlns="urn:jboss:domain:web:1.1" default-virtual-server="default-host" native="true">
```

You will then need to configure the servlet in your application's `web.xml` which will provide WebSocket upgrade support within AS7.

Add the following to the `web.xml` :

```
<context-param>
  <param-name>websockets-enabled</param-name>
  <param-value>true</param-value>
</context-param>

<context-param>
```

```
<param-name>websocket-path-element</param-name>
<param-value>in.erraiBusWS</param-value>
</context-param>
```

This will tell the bus to enable web sockets support. The `websocket-path-element` specified the path element within a URL which the client bus should request in order to negotiate a websocket connection. For instance, specifying `in.erraiBusWS` as we have in the snippet above, will result in attempted negotiation at `http://<your_server>:<your_port>/<context_path>/in.erraiBusWS`. For this to have any meaningful result, we must add a servlet mapping that will match this pattern:

```
<servlet>
  <servlet-name>ErraiWSServlet</servlet-name>
  <servlet-class>org.jboss.errai.bus.server.servlet.JBossAS7WebSocketServlet</servlet-class>
  <init-param>
    <param-name>service-locator</param-name>
    <param-value>org.jboss.errai.cdi.server.CDIServiceLocator</param-value>
  </init-param>
  <load-on-startup>1</load-on-startup>
</servlet>

<servlet-mapping>
  <servlet-name>ErraiWSServlet</servlet-name>
  <url-pattern>*.erraiBusWS</url-pattern>
</servlet-mapping>
```



Do not remove the regular ErraiBus servlet mappings!

When configuring ErraiBus to use WebSockets on JBoss AS, you **do not** remove the existing servlet mappings for the bus. The WebSocket servlet is in *addition to* your current bus servlet. This is because ErraiBus *always* negotiates WebSocket sessions over the COMET channel.

2.16. Bus Lifecycle

2.16.1. Turning Server Communication On and Off

By default, Errai's client-side message bus attempts to connect to the server as soon as the ErraiBus module has been loaded. The bus will stay connected until a lengthy (about 45 seconds) communication failure occurs, or the web page is unloaded.

The application can affect bus communication through two mechanisms:

1. By setting a global JavaScript variable `erraiBusRemoteCommunicationEnabled = false` before the GWT scripts load, bus communication with the server is permanently disabled
2. By calling `((ClientMessageBus) ErraiBus.get()).stop()`, the bus disconnects from the server

To resume server communication after a call to `ClientMessageBus.stop()` or after communication with the server has exceeded the bus' retry timeout, call `((ClientMessageBus) ErraiBus.get()).init()`. You can use a `BusLifecycleListener` to monitor the success or failure of this attempt. See the next section for details.

2.16.2. Observing Bus Lifecycle State and Communication Status

In a perfect world, the client message bus would always be able to communicate with the server message bus. But in the real world, there's a whole array of reasons why the communication link between the server and the client might be interrupted.

On its own, the client message bus will attempt to reconnect with the server whenever communication has been disrupted. Errai applications can monitor the status of the bus' communication link (whether it is disconnected, attempting to connect, or fully connected) through the `BusLifecycleListener` interface:

```
class BusStatusLogger implements BusLifecycleListener {

    @Override
    public void busAssociating(BusLifecycleEvent e) {
        GWT.log("Errai Bus trying to connect...");
    }

    @Override
    public void busOnline(BusLifecycleEvent e) {
        GWT.log("Errai Bus connected!");
    }

    @Override
    public void busOffline(BusLifecycleEvent e) {
        GWT.log("Errai Bus trying to connect...");
    }

    @Override
    public void busDisassociating(BusLifecycleEvent e) {
        GWT.log("Errai Bus going into local-only mode.");
    }
}
```

To attach such a listener to the bus, make the following call in client-side code:

```
ClientMessageBus bus = (ClientMessageBus) ErraiBus.get();
bus.addLifecycleListener(new BusStatusLogger());
```

2.17. Shadow Services

Shadow Services is a Service that will get invoked when there is no longer a connection with the server. This is particular helpful when developing an application for mobile. To create a Shadow Service for a specific Services all you have to do is annotate a new client side implementation with the `@ShadowService`:

```
@ShadowService
public class SignupShadowService implements MessageCallback {
    @Override
    public void callback(Message message) {
    }
}
```

Also when you have a RPC based Service you can just add `@ShadowService` on a client side implementation to configure it to be the service to get called when there is no network:

```
@ShadowService
public class SignupServiceShadow implements SignupService {
    @Override
    public User register(User newUserObject, String password) throws RegistrationException {
    }
}
```

In this shadow service we can create logic that will deal with the temporary connection loss. For instance you could save the data that needs to get send to the server with JPA on the client and then when the bus get online again sent the data to the server.

2.18. Debugging Messaging Problems

Errai includes a bus monitoring application, which allows you to monitor all of the message exchange activity on the bus in order to help track down any potential problems It allows you to inspect individual messages to examine their state and structure.

To utilize the bus monitor, you'll need to include the `_errai-tools_` package as part of your application's dependencies. When you run your application in development mode, you will simply need to add the following JVM options to your run configuration in order to launch the monitor: -

```
Derrai.tools.bus_monitor_attach=true
```

Figure 2.2. TODO InformalFigure image title empty

The monitor provides you a real-time perspective on what's going on inside the bus. The left side of the main screen lists the services that are currently available, and the right side is the service-explorer, which will show details about the service.

To see what's going on with a specific service, simply double-click on the service or highlight the service, then click "Monitor Service...". This will bring up the service activity monitor.

Figure 2.3. TODO InformalFigure image title empty

The service activity monitor will display a list of all the messages that were transmitted on the bus since the monitor became active. You do not need to actually have each specific monitor window open in order to actively monitor the bus activity. All activity on the bus is recorded.

The monitor allows you select individual messages, and view their individual parts. Clicking on a message part will bring up the object inspector, which will allow you to explore the state of any objects contained within the message, not unlike the object inspectors provided by debuggers in your favorite IDE. This can be a powerful tool for looking under the covers of your application.

Dependency Injection

The core Errai IOC module implements the [JSR-330 Dependency Injection](http://download.oracle.com/otndocs/jcp/dependency_injection-1.0-final-oth-JSpec/) [http://download.oracle.com/otndocs/jcp/dependency_injection-1.0-final-oth-JSpec/] specification for in-client component wiring.

Dependency injection (DI) allows for cleaner and more modular code, by permitting the implementation of decoupled and type-safe components. By using DI, components do not need to be aware of the implementation of provided services. Instead, they merely declare a contract with the container, which in turn provides instances of the services that component depends on.



Classpath Scanning and ErraiApp.properties

Errai only scans the contents of classpath locations (JARs and directories) that have *a file called ErraiApp.properties* at their root. If dependency injection is not working for you, double-check that you have an `ErraiApp.properties` in every JAR and directory that contains classes Errai should know about.

A simple example:

```
public class MyLittleClass {
    private final TimeService timeService;

    @Inject
    public MyLittleClass(TimeService timeService) {
        this.timeService = timeService;
    }

    public void printTime() {
        System.out.println(this.timeService.getTime());
    }
}
```

In this example, we create a simple class which declares a dependency using `@Inject` [http://download.oracle.com/javaee/6/api/javax/inject/Inject.html] for the interface `TimeService`. In this particular case, we use constructor injection to establish the contract between the container and the component. We can similarly use field injection to the same effect:

```
public class MyLittleClass {
    @Inject
```

```
private TimeService timeService;

public void printTime() {
    System.out.println(this.timeService.getTime());
}
}
```

In order to inject `TimeService`, you must annotate it with `@ApplicationScoped` or the Errai DI container will not acknowledge the type as a bean.

```
@ApplicationScoped
public class TimeService {
}
```



Best Practices

Although field injection results in less code, a major disadvantage is that you cannot create immutable classes using the pattern, since the container must first call the default, no argument constructor, and then iterate through its injection tasks, which leaves the potential – albeit remote – that the object could be left in a partially or improperly initialized state. The advantage of constructor injection is that fields can be immutable (final), and invariance rules applied at construction time, leading to earlier failures, and the guarantee of consistent state.

3.1. Container Wiring

In contrast to [Gin](http://code.google.com/p/google-gin/), the Errai IOC container does not provide a programmatic way of creating and configuring injectors. Instead, container-level binding rules are defined by implementing a [Provider](http://download.oracle.com/javaee/6/api/javax/inject/Provider.html), which is scanned for and auto-discovered by the container.

A `Provider` is essentially a factory which produces type instances within in the container, and defers instantiation responsibility for the provided type to the provider implementation. Top-level providers use the standard `javax.inject.Provider<T>` interface.

Types made available as *top-level* providers will be available for injection in any managed component within the container.

Out of the box, Errai IOC implements these default top-level providers, all defined in the `org.jboss.errai.ioc.client.api.builtin` package:

- `CallerProvider` : Makes RPC `Caller<T>` objects available for injection.

- `DisposableProvider` : Makes Errai IoC `Disposable<T>` objects available for injection.
- `InitBallotProvider` : Makes instances of `InitBallot` available for injection.
- `IOCBeanManagerProvider` : Makes Errai's client-side bean manager, `ClientBeanManager` , available for injection.
- `MessageBusProvider` : Makes Errai's client-side `MessageBus` singleton available for injection.
- `RequestDispatcherProvider` : Makes an instance of the `RequestDispatcher` available for injection.
- `RootPanelProvider` : Makes GWT's `RootPanel` singleton injectable.
- `SenderProvider` : Makes `MessageBus` `Sender<T>` objects available for injection.

Implementing a `Provider` is relatively straight-forward. Consider the following two classes:

TimeService.java

```
public interface TimeService {
    public String getTime();
}
```

TimeServiceProvider.java

```
@IOCPProvider
@Singleton
public class TimeServiceProvider implements Provider<TimeService> {
    @Override
    public TimeService get() {
        return new TimeService() {
            public String getTime() {
                return "It's midnight somewhere!";
            }
        };
    }
}
```

If you are familiar with Guice, this is semantically identical to configuring an injector like so:

```
Guice.createInjector(new AbstractModule() {
    public void configure() {
```

```
bind(TimeService.class).toProvider(TimeServiceProvider.class);
}
}).getInstance(MyApp.class);
```

As shown in the above example code, the annotation `@IOCPProvider` is used to denote top-level providers.

The classpath will be searched for all annotated providers at compile time.



Important

Top-level providers are regular beans, so they can inject dependencies—particularly from other top-level providers—as necessary.

3.2. Wiring server side components

By default, Errai uses Google Guice to wire server-side components. When deploying services on the server-side, it is currently possible to obtain references to the `MessageBus`, `RequestDispatcher`, the `ErraiServiceConfigurator`, and `ErraiService` by declaring them as injection dependencies in Service classes, extension components, and session providers.

Alternatively, supports CDI based wiring of server-side components. See the chapter on Errai CDI for more information.

3.3. Scopes

Out of the box, the IOC container supports three bean scopes, `@Dependent`, `@Singleton` and `@EntryPoint`. The singleton and entry-point scopes are roughly the same semantics.

3.3.1. Dependent Scope

In Errai IOC, all client types are valid bean types if they are default constructable or can have construction dependencies satisfied. These unqualified beans belong to the dependent pseudo-scope. See: [Dependent Pseudo-Scope from CDI Documentation](http://docs.jboss.org/weld/reference/latest/en-US/html/scopescontexts.html#d0e1997) [http://docs.jboss.org/weld/reference/latest/en-US/html/scopescontexts.html#d0e1997]

Additionally, beans may be qualified as `@ApplicationScoped`, `@Singleton` or `@EntryPoint`. Although `@ApplicationScoped` and `@Singleton` are supported for completeness and conformance, within the client they effectively result in behavior that is identical.

Example 3.1. Example dependent scoped bean

```
public void MyDependentScopedBean {
    private final Date createDate;
```

```

public MyDependentScopedBean {
    createDate = new Date();
}
}

```

Example 3.2. Example ApplicationScoped bean

```

@ApplicationScoped
public void MyClientBean {
    @Inject MyDependentScopedBean bean;

    // ... //
}

```



Availability of dependent beans in the client-side BeanManager

As is mentioned in the [bean manager documentation](#) [38], only beans that are *explicitly* scoped will be made available to the bean manager for lookup. So while it is not necessary for regular injection, you must annotate your dependent scoped beans with `@Dependent` if you wish to dynamically lookup these beans at runtime.

3.4. Built-in Extensions

3.4.1. Bus Services

As Errai IOC provides a container-based approach to client development, support for Errai services are exposed to the container so they may be injected and used throughout your application where appropriate. This section covers those services.

3.4.1.1. @Service

The `org.jboss.errai.bus.server.annotations.Service` annotation is used for binding service endpoints to the bus. Within the Errai IOC container you can annotate services and have them published to the bus on the client (or on the server) in a very straight-forward manner:

Example 3.3. A simple message receiving service

```
@Service
```

```
public class MyService implements MessageCallback {
    public void callback(Message message) {
        // ... //
    }
}
```

As with server-side use of the annotation, if a service name is not explicitly specified, the underlying class name or field name being annotated will be used as the service name.

3.4.1.2. @Local

The `org.jboss.errai.bus.server.api.Local` annotation is used in conjunction with the `@Service` annotation to advertise a service only for visibility on the local bus and thus, cannot receive messages across the wire for the service.

Example 3.4. A local only service

```
@Service @Local
public class MyLocalService implements MessageCallback {
    public void callback(Message message) {
        // ... //
    }
}
```

3.4.1.3. Lifecycle Impact of Services

Services which are registered with ErraiBus via the bean manager through use of the `@Service` annotation, have de-registration hooks tied implicitly to the destruction of the bean. Thus, *destruction of the bean* implies that these associated services are to be dereferenced.

3.4.2. Client Components

The IOC container, by default, provides a set of default injectable bean types. They range from basic services, to injectable proxies for RPC. This section covers the facilities available out-of-the-box.

3.4.2.1. MessageBus

The type `org.jboss.errai.bus.client.framework.MessageBus` is globally injectable into any bean. Injecting this type will provide the instance of the active message bus running in the client.

Example 3.5. Injecting a MessageBus

```
@Inject MessageBus bus;
```

3.4.2.2. RequestDispatcher

The type `org.jboss.errai.bus.client.framework.RequestDispatcher` is globally injectable into any bean. Injecting this type will provide a `RequestDispatcher` instance capable of delivering any messages provided to it, to the `MessageBus`.

Example 3.6. Injecting a RequestDispatcher

```
@Inject RequestDispatcher dispatcher;
```

3.4.2.3. Caller<?>

The type `org.jboss.errai.common.client.api.Caller<?>` is a globally injectable RPC proxy. RPC proxies may be provided by various components. For example, JAX-RS or Errai RPC. The proxy itself is agnostic to the underlying RPC mechanism and is qualified by its type parameterization.

For example:

Example 3.7. An example Caller<?> proxy

```
public void MyClientBean {
    @Inject
    private Caller<MyRpcInterface> rpcCaller;

    // ... ///

    @EventHandler("button")
    public void onButtonClick(ClickHandler handler) {
        rpcCaller.call(new RemoteCallback<Void>() {
            public void callback(Void void) {
                // put code here that should execute after RPC response arrives
            }
        }).callSomeMethod();
    }
}
```

The above code shows the injection of a proxy for the RPC remote interface, `MyRpcInterface`. For more information on defining RPC proxies see [Chapter 6, Remote Procedure Calls \(RPC\)](#) and [Creating Requests in Errai JAX-RS](#).

3.4.2.4. Sender<?>

The `org.jboss.errai.ioc.support.bus.client.Sender<?>` interface is the lower-level counterpart to the `Caller<?>` interface described above. You can inject a `Sender` to send low-level ErraiBus messages directly to subscribers on any subject.

For example:

```
@Inject
@ToSubject("ListCapitalizationService")
Sender<List<String>> listSender;

// ... ///

@EventHandler("button")
public void onClick(ClickHandler handler) {
    List<String> myListOfStrings = getSelectedCitiesFromForm();
    listSender.send(myListOfStrings, new MessageCallback() {
        public void callback(Message reply) {
            // do stuff with reply
        }
    });
}
```

The `Sender.send()` method is overloaded. The variant demonstrated above takes a value and a `MessageCallback` to reply receive a reply (assuming the subscriber sends a conversational reply). The following variants are available:

- `send(T)`
- `send(T, ErrorCallback)`
- `send(T, MessageCallback)`
- `send(T, MessageCallback, ErrorCallback)`

The reply-to service can also be specified declaratively using the `@ReplyTo` annotation. This allows the app to receive conversational replies even when using the `send()` variants that do not take a `MessageCallback`:

```
@Inject
@ToSubject("ListCapitalizationService")
@ReplyTo("ClientListService")
Sender<List<String>> listSender;
```

```

// ... ///

@EventHandler("button")
public void onClick(ClickHandler handler) {
    List<String> myListOfStrings = getSelectedCitiesFromForm();
    listSender.send(myListOfStrings);
}

@Singleton
@Service
public static class ClientListService implements MessageCallback {
    @Override
    public void callback(Message message) {
        // do stuff with message
    }
}

```

These `Sender<?>` features are just convenient wrappers around the full-featured programmatic ErraiBus API. See [Section 2.2, “Messaging API Basics”](#) and [Section 2.14, “Conversations”](#) for full information about low-level ErraiBus communication.

3.4.3. Lifecycle Tools

A problem commonly associated with building large applications in the browser is ensuring that things happen in the proper order when code starts executing. Errai IOC provides you tools which permit you to ensure things happen before initialization, and forcing things to happen after initialization of all of the Errai services.

3.4.3.1. Controlling Startup

In order to prevent initialization of the the bus and it's services so that you can do necessary configuration, especially if you are writing extensions to the Errai framework itself, you can create an implicit startup dependency on your bean by injecting an `org.jboss.errai.ioc.client.api.InitBallot<?>`.

Example 3.8. Using an InitBallot to Control Startup

```

@Singleton
public class MyClientBean {
    @Inject InitBallot<MyClientBean> ballot;

    @PostConstruct
    public void doStuff() {
        // ... do some work ...
    }
}

```

```
        ballot.voteForInit();
    }
}
```

3.4.3.2. Performing Tasks After Initialization

Sending RPC calls to the server from inside constructors and `@PostConstruct` methods in Errai is not always reliable due to the fact that the bus and RPC proxies initialize asynchronously with the rest of the application. Therefore it is often desirable to have such things happen in a post-initialization task, which is exposed in the `ClientMessageBus` API. However, it is much cleaner to use the `@AfterInitialization` annotation on one of your bean methods.

Example 3.9. Using `@AfterInitialization` to do something after startup

```
@Singleton
public class MyClientBean {
    @AfterInitialization
    public void doStuffAfterInit() {
        // ... do some work ...
    }
}
```

3.4.4. Timed Methods

The `@Timed` annotation allows scheduling method executions on managed client-side beans. Timers are automatically scoped to the scope of the corresponding managed bean and participate in the same lifecycle (see [Section 3.7, “Bean Lifecycle”](#) for details).

In the following example the `updateTime` method is invoked repeatedly every second.

```
@Timed(type = TimerType.REPEATING, interval = 1, timeUnit = TimeUnit.SECONDS)
private void updateTime() {
    timeWidget.setTime(System.currentTimeMillis);
}
```

For delayed one-time execution of methods `type = TimerType.DELAYED` can be used instead.

3.5. Client-Side Bean Manager

It may be necessary at times to manually obtain instances of beans managed by Errai IOC from outside the container managed scope or creating a hard dependency from your

bean. Errai IOC provides a simple client-side bean manager for handling these scenarios:
`org.jboss.errai.ioc.client.container.ClientBeanManager` .

As you might expect, you can inject a bean manager instance into any of your managed beans. If you use Errai IOC in its default mode you will need to inject the synchronous bean manager (`org.jboss.errai.ioc.client.container.SyncBeanManager`).

If you have asynchronous IOC mode enabled simply inject the asynchronous bean manager (`org.jboss.errai.ioc.client.container.async.AsyncBeanManager`) instead. Asynchronous IOC brings support for *code splitting* [<http://www.gwtproject.org/doc/latest/DevGuideCodeSplitting.html>] . That means that any bean annotated with `@LoadAsync` can be compiled into a separate JavaScript file that's downloaded when the bean is first needed on the client.

Example 3.10. Injecting the client-side bean manager

```
public MyManagedBean {
    @Inject SyncBeanManager manager;

    // class body
}
```

If you need to access the bean manager outside a managed bean, such as in a unit test, you can access it by calling `org.jboss.errai.ioc.client.container.IOC.getBeanManager()`

3.5.1. Looking up beans

Looking up beans can be done through the use of the `lookupBeans()` method. Here's a basic example:

Example 3.11. Example lookup of a bean

```
public MyManagedBean {
    @Inject SyncBeanManager manager;

    public void lookupBean() {
        IOCBeanDef<SimpleBean> bean = manager.lookupBean(SimpleBean.class);

        if (bean != null) {
            // get the instance of the bean
            SimpleBean inst = bean.getInstance();
        }
    }
}
```

```
}
```

In this example we lookup a bean class named `SimpleBean`. This example will succeed assuming that `SimpleBean` is unambiguous. If the bean is ambiguous and requires qualification, you can do a qualified lookup like so:

Example 3.12. Looking up beans with qualifiers

```
MyQualifier qual = new MyQualifier() {
    public annotationType() {
        return MyQualifier.class;
    }
}

MyOtherQualifier qual2 = new MyOtherQualifier() {
    public annotationType() {
        return MyOtherQualifier.class;
    }
}

// pass qualifiers to ClientBeanManager.lookupBeans
IOCBanDef<SimpleBean> bean = beanManager.lookupBean(SimpleBean.class, qual, qual2);
```

In this example we manually construct instances of qualifier annotations in order to pass it to the bean manager for lookup. This is a necessary step since there's currently no support for annotation literals in Errai client code.

3.5.2. Availability of beans

Not all beans that are available for injection are available for lookup from the bean manager by default. Only beans which are *explicitly* scoped are available for dynamic lookup. This is an intentional feature to keep the size of the generated code down in the browser.

3.6. Alternatives and Mocks

3.6.1. Alternatives

It may be desirable to have multiple matching dependencies for a given injection point with the ability to specify which implementation to use at runtime. For instance, you may have different versions of your application which target different browsers or capabilities of the browser. Using alternatives allows you to share common interfaces among your beans, while still using dependency injection, by exporting consideration of what implementation to use to the container's configuration.

Consider the following example:

```
@Singleton @Alternative
public class MobileView implements View {
    // ... //
}
```

and

```
@Singleton @Alternative
public class DesktopView implements View {
    // ... //
}
```

In our controller logic we in turn inject the `View` interface:

```
@EntryPoint
public class MyApp {
    @Inject
    View view;

    // ... //
}
```

This code is unaware of the implementation of `View`, which maintains good separation of concerns. However, this of course creates an ambiguous dependency on the `View` interface as it has two matching subtypes in this case. Thus, we must configure the container to specify which alternative to use. Also note, that the beans in both cases have been annotated with `javax.enterprise.inject.Alternative`.

In your `ErraiApp.properties` for the module, you can simply specify which active alternative should be used:

```
errai.ioc.enabled.alternatives=org.foo.MobileView
```

You can specify multiple alternative classes by white space separating them:

```
errai.ioc.enabled.alternatives=org.foo.MobileView \
                                org.foo.HTML5Orientation \
                                org.foo.MobileStorage
```

You can only have one enabled alternative for a matching set of alternatives, otherwise you will get ambiguous resolution errors from the container.

3.6.2. Test Mocks

Similar to alternatives, but specifically designed for testing scenarios, you can replace beans with mocks at runtime for the purposes of running unit tests. This is accomplished simply by annotating a bean with the `org.jboss.errai.ioc.client.api.TestMock` annotation. Doing so will prioritize consideration of the bean over any other matching beans while running unit tests.

Consider the following:

```
@ApplicationScoped
public class UserManagementImpl implements UserManagement {
    public List<User> listUsers() {
        // do user listy things!
    }
}
```

You can specify a mock implementation of this class by implementing its common parent type (`UserManagement`) and annotating that class with the `@TestMock` annotation inside your test package like so:

```
@TestMock @ApplicationScoped
public class MockUserManagementImpl implements UserManagement {
    public List<User> listUsers() {
        // return only a test user.
        return Collections.singletonList(TestUser.INSTANCE);
    }
}
```

In this case, the container will replace the `UserManagementImpl` with the `MockUserManagementImpl` automatically when running the unit tests.

The `@TestMock` annotation can also be used to specify alternative providers during test execution. For example, it can be used to mock a `Caller<T>`. `Callers` are used to invoke RPC or JAX-RS endpoints. During tests you might want to replace these callers with mock implementations. For details on providers see [Section 3.1, “Container Wiring”](#).

```

@TestMock @IOCProvider
public class MockedHappyServiceCallerProvider implements ContextualTypeProvider<Caller<HappyService>> {

    @Override
    public Caller<HappyService> provide(Class<?>[] typeargs, Annotation[] qualifiers) {
        return new Caller<HappyService>() {
            ...
        }
    }
}

```

3.7. Bean Lifecycle

All beans managed by the Errai IOC container support the `@PostConstruct` and `@PreDestroy` annotations.

Beans which have methods annotated with `@PostConstruct` are guaranteed to have those methods called before the bean is put into service, and only after all dependencies within its graph has been satisfied.

Beans are also guaranteed to have their `@PreDestroy` annotated methods called before they are destroyed by the bean manager.



Important

This cannot be guaranteed when the browser DOM is destroyed prematurely due to: closing the browser window; closing a tab; refreshing the page, etc.

3.7.1. Destruction of Beans

Beans under management of Errai IOC, of any scope, can be explicitly destroyed through the client bean manager. Destruction of a managed bean is accomplished by passing a reference to the `destroyBean()` method of the bean manager.

Example 3.13. Destruction of bean

```

public MyManagedBean {
    @Inject SyncBeanManager manager;

    public void createABeanThenDestroyIt() {
        // get a new bean.
        SimpleBean bean = manager.lookupBean(SimpleBean.class).getInstance();
    }
}

```

```
bean.sendMessage("Sorry, I need to dispose of you now");

// destroy the bean!
manager.destroyBean(bean);
}
}
```

When the bean manager "destroys" the bean, any pre-destroy methods the bean declares are called, it is taken out of service and no longer tracked by the bean manager. If there are references on the bean by other objects, the bean will continue to be accessible to those objects.



Important

Container managed resources that are dependent on the bean such as bus service endpoints or CDI event observers will also be automatically destroyed when the bean is destroyed.

Another important consideration is the rule, "all beans created together are destroyed together." Consider the following example:

Example 3.14. SimpleBean.class

```
@Dependent
public class SimpleBean {
    @Inject @New AnotherBean anotherBean;

    public AnotherBean getAnotherBean() {
        return anotherBean;
    }

    @PreDestroy
    private void cleanUp() {
        // do some cleanup tasks
    }
}
```

Example 3.15. Destroying bean from subgraph

```
public MyManagedBean {
    @Inject SyncBeanManager manager;
```

```
public void createABeanThenDestroyIt() {
    // get a new bean.
    SimpleBean bean = manager.lookupBean(SimpleBean.class).getInstance();

    // destroy the AnotherBean reference from inside the bean
    manager.destroyBean(bean.getAnotherBean());
}
}
```

In this example we pass the instance of `AnotherBean`, created as a dependency of `SimpleBean`, to the bean manager for destruction. Because this bean was created at the same time as its parent, its destruction will also result in the destruction of `SimpleBean`; thus, this action will result in the `@PreDestroy` `cleanUp()` method of `SimpleBean` being invoked.

3.7.1.1. Disposers

Another way which beans can be destroyed is through the use of the injectable `org.jboss.errai.ioc.client.api.Disposer<T>` class. The class provides a straight forward way of disposing of bean type.

For instance:

Example 3.16. Destroying bean with disposer

```
public MyManagedBean {
    @Inject @New SimpleBean myNewSimpleBean;
    @Inject Disposer<SimpleBean> simpleBeanDisposer;

    public void destroyMyBean() {
        simpleBeanDisposer.dispose(myNewSimpleBean);
    }
}
```


Errai CDI

CDI (Contexts and Dependency Injection) is the Java EE standard (JSR-299) for handling dependency injection. In addition to dependency injection, the standard encompasses component lifecycle, application configuration, call-interception and a decoupled, type-safe eventing specification.

The Errai CDI extension implements a subset of the specification for use inside of client-side applications within Errai, as well as additional capabilities such as distributed eventing.

Errai CDI does not currently implement all life cycles specified in JSR-299 or interceptors. These deficiencies may be addressed in future versions.



Important

Errai CDI is implemented as an extension on top of the Errai IOC Framework (see [Chapter 3, Dependency Injection](#)), which itself implements JSR-330. Inclusion of the CDI module your GWT project will result in the extensions automatically being loaded and made available to your application.



Classpath Scanning and ErraiApp.properties

Errai CDI only scans the contents of classpath locations (JARs and directories) that have *a file called `ErraiApp.properties`* at their root. If CDI features such as dependency injection, event observation, and `@PostConstruct` are not working for your classes, double-check that you have an `ErraiApp.properties` at the root of every JAR and directory tree that contains classes Errai should know about.

4.1. Features and Limitations

Beans that are deployed to a CDI container will automatically be registered with Errai and exposed to your GWT client application. So, you can use Errai to communicate between your GWT client components and your CDI backend beans.

Errai CDI based applications use the same annotation-driven programming model as server-side CDI components, with some notable limitations. Many of these limitations will be addressed in future releases.

1. There is no support for CDI interceptors in the client. Although this is planned in a future release.
2. Passivating scopes are not supported.

3. The JSR-299 SPI is not supported for client side code. Although writing extensions for the client side container is possible via the Errai IOC Extensions API.
4. The `@Typed` annotation is unsupported.
5. The `@Interceptor` annotation is unsupported.
6. The `@Decorator` annotation is unsupported.

4.1.1. Other features

The CDI container in Errai is built around the *Errai IOC module*, and thus is a superset of the existing functionality in Errai IOC. Thus, all features and APIs documented in Errai IOC are accessible and usable with this Errai CDI programming model.

4.2. Events

Any CDI managed component may produce and consume *events* [<http://docs.jboss.org/weld/reference/latest/en-US/html/events.html>]. This allows beans to interact in a completely decoupled fashion. Beans consume events by registering for a particular event type and optional qualifiers. The Errai CDI extension simply extends this concept into the client tier. A GWT client application can simply register an `Observer` for a particular event type and thus receive events that are produced on the server-side. Likewise and using the same API, GWT clients can produce events that are consumed by a server-side observer.

Let's take a look at an example.

Example 4.1. FraudClient.java

```
public class FraudClient extendsLayoutPanel {

    @Inject
    private Event<AccountActivity> event; (1)

    private HTML responsePanel;

    public FraudClient() {
        super(new BoxLayout(BoxLayout.Orientation.VERTICAL));
    }

    @PostConstruct
    public void buildUI() {
        Button button = new Button("Create activity", new ClickHandler() {
            public void onClick(ClickEvent clickEvent) {
                event.fire(new AccountActivity());
            }
        });
    }
}
```

```

responsePanel = new HTML();
add(button);
add(responsePanel);
}

public void processFraud(@Observes @Detected Fraud fraudEvent) { (2)
    responsePanel.setText("Fraud detected: " + fraudEvent.getTimestamp());
}
}

```

Two things are noteworthy in this example:

1. Injection of an `Event` dispatcher proxy
2. Creation of an `Observer` method for a particular event type

The event dispatcher is responsible for sending events created on the client-side to the server-side event subsystem (CDI container). This means any event that is fired through a dispatcher will eventually be consumed by a CDI managed bean, if there is an corresponding `Observer` registered for it on the server side.

In order to consume events that are created on the server-side you need to declare an client-side observer method for a particular event type. In case an event is fired on the server this method will be invoked with an event instance of type you declared.

To complete the example, let's look at the corresponding server-side CDI bean:

Example 4.2. AccountService.java

```

@ApplicationScoped
public class AccountService {

    @Inject @Detected
    private Event<Fraud> event;

    public void watchActivity(@Observes AccountActivity activity) {
        Fraud fraud = new Fraud(System.currentTimeMillis());
        event.fire(fraud);
    }
}

```

4.2.1. Conversational events

A server can address a single client in response to an event annotating event types as `@Conversational`. Consider a service that responds to a subscription event.

Example 4.3. SubscriptionService.java

```
@ApplicationScoped
public class SubscriptionService {

    @Inject
    private Event<Documents> welcomeEvent;

    public void onSubscription(@Observes Subscription subscription) {
        Document docs = createWelcomePackage(subscription);
        welcomeEvent.fire(docs);
    }
}
```

And the `Document` class would be annotated like so:

Example 4.4. Document.java

```
@Conversational @Portable
public class Document {
    // code here
}
```

As such, when `Document` events are fired, they will be limited in scope to the initiating conversational contents – which are implicitly inferred by the caller. So only the client which fired the `Subscription` event will receive the fired `Document` event.

4.2.2. Client-Server Event Example

A key feature of the Errai CDI framework is the ability to federate the CDI eventing bus between the client and the server. This permits the observation of server produced events on the client, and vice-versa.

Example server code:

Example 4.5. MyServerBean.java

```
@ApplicationScoped
public class MyServerBean {
    @Inject
    Event<MyResponseEvent> myResponseEvent;
}
```

```
public void myClientObserver(@Observes MyRequestEvent event) {
    MyResponseEvent response;

    if (event.isThankYou()) {
        // aww, that's nice!
        response = new MyResponseEvent("Well, you're welcome!");
    }
    else {
        // how rude!
        response = new MyResponseEvent("What? Nobody says 'thank you' anymore?");
    }

    myResponseEvent.fire(response);
}
}
```

Domain-model:

Example 4.6. MyRequestEvent.java

```
@Portable
public class MyRequestEvent {
    private boolean thankYou;

    public MyRequestEvent(boolean thankYou) {
        setThankYou(thankYou);
    }

    public void setThankYou(boolean thankYou) {
        this.thankYou = thankYou;
    }

    public boolean isThankYou() {
        return thankYou;
    }
}
```

Example 4.7. MyResponseEvent.java

```
@Portable
public class MyResponseEvent {
    private String message;
```

```
public MyRequestEvent(String message) {
    setMessage(message);
}

public void setMessage(String message) {
    this.message = message;
}

public String getMessage() {
    return message;
}
}
```

Client application logic:

Example 4.8. MyClientBean.java

```
@EntryPoint
public class MyClientBean {
    @Inject
    Event<MyRequestEvent> requestEvent;

    public void myResponseObserver(@Observes MyResponseEvent event) {
        Window.alert("Server replied: " + event.getMessage());
    }

    @PostConstruct
    public void init() {
        Button thankYou = new Button("Say Thank You!");
        thankYou.addClickHandler(new ClickHandler() {
            public void onClick(ClickEvent event) {
                requestEvent.fire(new MyRequestEvent(true));
            }
        });

        Button nothing = new Button("Say nothing!");
        nothing.addClickHandler(new ClickHandler() {
            public void onClick(ClickEvent event) {
                requestEvent.fire(new MyRequestEvent(false));
            }
        });

        VerticalPanel vPanel = new VerticalPanel();
        vPanel.add(thankYou);
        vPanel.add(nothing);
    }
}
```

```
RootPanel.get().add(vPanel);
    }
}
```

4.3. Producers

Producer methods and fields act as sources of objects to be injected. They are useful when additional control over object creation is needed before injections can take place e.g. when you need to make a decision at runtime before an object can be created and injected.

Example 4.9. App.java

```
@EntryPoint
public class App {
    ...

    @Produces @Supported
    private MyBaseWidget createWidget() {
        return (Canvas.isSupported()) ? new MyHtml5Widget() : new MyDefaultWidget();
    }
}
```

Example 4.10. MyComposite.java

```
@ApplicationScoped
public class MyComposite extends Composite {

    @Inject @Supported
    private MyBaseWidget widget;

    ...
}
```

Producers can also be scoped themselves. By default, producer methods are dependent-scoped, meaning they get called every time an injection for their provided type is requested. If a producer method is scoped `@Singleton` for instance, the method will only be called once, and the bean manager will inject the instance from the first invocation of the producer into every matching injection point.

Example 4.11. Singleton producer

```
public class App {  
    ...  
  
    @Produces @Singleton  
    private MyBean produceMyBean() {  
        return new MyBean();  
    }  
}
```

For more information on CDI producers, see the [CDI specification](http://docs.jboss.org/cdi/spec/1.0/html/) [http://docs.jboss.org/cdi/spec/1.0/html/] and the [WELD reference documentation](http://seamframework.org/Weld/WeldDocumentation) [http://seamframework.org/Weld/WeldDocumentation].

4.4. safe dynamic lookup

As an alternative to using the bean manager to dynamically create beans, this can be accomplished in a type-safe way by injecting a `javax.enterprise.inject.Instance<T>`.

For instance, assume you have a dependent-scoped bean `Bar` and consider the following:

```
public class Foo {  
    @Inject Instance<Bar> barInstance;  
  
    public void pingNewBar() {  
        Bar bar = barInstance.get();  
        bar.ping();  
    }  
}
```

In this example, calling `barInstance.get()` returns a new instance of the dependent-scoped bean `Bar`.

4.5. Deploying Errai CDI

If you do not care about the deployment details for now and just want to get started take a look at the [ERRAI:Quickstart Guide](#).

The CDI integration is a plugin to the Errai core framework and represents a CDI portable extension. Which means it is discovered automatically by both Errai and the CDI container. In order to use it, you first need to understand the different runtime models involved when working GWT, Errai and CDI.

Typically a GWT application lifecycle begins in *Development Mode* [<http://code.google.com/webtoolkit/doc/latest/DevGuideCompilingAndDebugging.html>] and finally a web application containing the GWT client code will be deployed to a target container (Servlet Engine, Application Server). This is no way different when working with CDI components to back your application.

What's different however is availability of the CDI container across the different runtimes. In GWT development mode and in a pure servlet environment you need to provide and bootstrap the CDI environment on your own. While any Java EE 6 Application Server already provides a preconfigured CDI container. To accomodate these differences, we need to do a little trickery when executing the GWT Development Mode and packaging our application for deployment.

4.5.1. Deployment in Development Mode

In development mode we need to bootstrap the CDI environment on our own and make both Errai and CDI available through JNDI (common denominator across all runtimes). Since GWT uses Jetty, that only supports read only JNDI, we need to replace the default Jetty launcher with a custom one that will setup the JNDI bindings:

```
<plugin>
  <groupId>org.codehaus.mojo</groupId>
  <artifactId>gwt-maven plugin</artifactId>
  <version>${gwt.maven}</version>

  <configuration>
    ...
    <server>org.jboss.errai.cdi.server.gwt.JettyLauncher</server>
  </configuration>
  <executions>
    ...
  </executions>
</plugin>
```



Starting Development Mode from within your IDE

Consequently, when starting Development Mode from within your IDE the following program argument has to be provided: `-server org.jboss.errai.cdi.server.gwt.JettyLauncher`

4.5.1.1. Special-case Classloading

JettyLauncher uses different class loaders to load classes that belongs to the web application, the Jetty server, and the Java standard library itself. In the majority of cases, you can simply put all dependencies into your web application's `WEB-INF/lib` folder. However, there are cases where

putting a dependency in `WEB-INF/lib` will cause troubles such as `ClassCastException` when same class is also loaded by a different classloader. To mitigate this problem, `JettyLauncher` can be instructed that certain classes (or packages) shall be loaded only by the system class loader. To do so, set the Java system property `jetty.custom.sys.classes` when launching Dev Mode.

For example, when using `gwt-maven-plugin`:

```
<extraJvmArgs>-Djetty.custom.sys.classes=bitronix;javax.transaction</extraJvmArgs>
```

Once this is set up correctly, we can bootstrap the CDI container through a servlet listener:

```
<web-app>
  ...
  <listener>
    <listener-class>org.jboss.errai.container.CDIServletStateListener</listener-class>
  </listener>

  <resource-env-ref>
    <description>Object factory for the CDI Bean Manager</description>
    <resource-env-ref-name>BeanManager</resource-env-ref-name>
    <resource-env-ref-type>javax.enterprise.inject.spi.BeanManager</resource-env-ref-type>
  </resource-env-ref>
  ...
</web-app>
```

4.5.2. Deployment to a Servlet Engine

Deployment to servlet engine has basically the same requirements as running in development mode. You need to include the servlet listener that bootstraps the CDI container and make sure both Errai and CDI are accessible through JNDI. For Jetty you can re-use the artefacts we ship with the archetype. In case you want to run on tomcat, please consult the [Apache Tomcat Documentation](http://tomcat.apache.org/tomcat-5.5-doc/jndi-resources-howto.html) [http://tomcat.apache.org/tomcat-5.5-doc/jndi-resources-howto.html] .

4.5.3. Deployment to an Application Server

We provide integration with the [JBoss Application Server](http://jboss.org/jbossas) [http://jboss.org/jbossas] , but the requirements are basically the same for other vendors. When running a GWT client app that leverages CDI beans on a Java EE 6 application server, CDI is already part of the container and accessible through JNDI (`java: /BeanManager`).

Marshalling

Errai includes a comprehensive marshalling framework which permits the serialization of domain objects between the browser and the server. From the perspective of GWT, this is a complete replacement for the provided GWT serialization facilities and offers a great deal more flexibility. You are able to map both application-specific domain model, as well as preexisting model, including model from third-party libraries using the custom definitions API.

5.1. Mapping Your Domain

All classes that you intend to be marshalled between the client and the server must be exposed to the marshalling framework. There are several ways you can do it and this section will take you through the different approaches you can take to fit your needs.

5.1.1. @Portable and @NonPortable

To make a Java class eligible for serialization with Errai Marshalling, mark it with the `org.jboss.errai.common.client.api.annotations.Portable` annotation. This tells the marshalling system to generate marshalling and demarshalling code for the annotated class and all of its nested classes.

The mapping strategy that will be used depends on how much information you provide about your model up-front. If you simply annotate a domain type with `@Portable` and do nothing else, the marshalling system will use an exhaustive strategy to determine how to construct and deconstruct instances of that type and its nested types.

The Errai marshalling system works by enumerating all of the Portable types it can find (by any of the three methods discussed in this section of the reference guide), eliminating all the non-portable types it can find (via `@NonPortable` annotations and entries in `ErraiApp.properties`), then enumerating the marshallable properties that make up each remaining portable entity type. The rules that Errai uses for enumerating the properties of a portable entity type are as follows:

- If an entity type has a field called `foo`, then that entity has a property called `foo` unless the field is marked `static` or `transient`.

Note that the existence of methods called `getFoo()`, `setFoo()`, or both, *does not* mean that the entity has a property called `foo`. Errai Marshalling always works from fields when discovering properties.

When reading a field `foo`, Errai Marshalling will call the method `getFoo()` in preference to direct field access if the `getFoo()` method exists.

Similarly, when writing a field `foo`, Errai Marshalling will call the method `setFoo()` in preference to direct field access if the `setFoo()` method exists.

The above rules are sufficient for marshalling an existing entity to a JSON representation, but for de-marshalling, Errai must also know how to obtain an instance of a type. The rules that Errai uses for deciding how to create an instance of a `@Portable` type are as follows:

- If the entity has a public constructor where every argument is annotated with `@MapsTo`, and those parameters cover all properties of the entity type, then Errai uses this constructor to create the object, passing in all of the property values.
- Otherwise, if the entity has a public static method where every argument is annotated with `@MapsTo`, and those parameters cover all properties of the entity type, then Errai uses this method to create the object. Note that when using this mechanism you are free to create and return a subtype of the marshalled type, or resolve one from a cache.
- If the entity has a public no-arguments constructor (or no explicit constructors at all), it will be created via that constructor, and the properties will be written to the new object one at a time. Each property will be written by its setter method, or by direct field access if a setter method is not available.

Now let's take a look at some common examples of how this works.

5.1.1.1. Example: A Simple Entity

```
@Portable
public class Person {
    private String name;
    private int age;

    public Person() {
    }

    public Person(String name, int age) {
        this.name = name;
        this.age = age;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

This is a pretty vanilla domain object. Note the default, public, no-argument constructor. In this case, it will be necessary to have one explicitly declared. But notice we have no setters. In

this case, the marshaler will rely on private field access to write the values on each side of the marshalling transaction. For simple domain objects, this is both nice and convenient. But you may want to make the class immutable and have a constructor enforce invariance. See the next section for that.

5.1.1.2. Example: An Immutable Entity with a Public Constructor

Immutability is almost always a good practice, and the marshalling system provides you a straight forward way to tell it how to marshal and de-marshal objects which enforce an immutable contract. Let's modify our example from the previous section.

```
@Portable
public class Person {
    private final String name;
    private final int age;

    public Person(@MapsTo("name") String name, @MapsTo("age") int age) {
        this.name = name;
        this.age = age;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Here we have set both of the class fields final. By doing so, we had to remove our default constructor. But that's okay, because we have annotated the remaining constructor's parameters using the `org.jboss.errai.marshalling.client.api.annotations.MapsTo` annotation.

By doing this, we have told the marshaling system, for instance, that the first parameter of the constructor maps to the property `name`. Which in this case, defaults to the name of the corresponding field. This may not always be the case – as will be explored in the section on custom definitions. But for now that's a safe assumption.

5.1.1.3. Example: An Immutable Entity with a Factory Method

Another good practice is to use a factory pattern to enforce invariance. Once again, let's modify our example.

```
@Portable
public class Person {
    private final String name;
    private final int age;

    private Person(String name, int age) {
        this.name = name;
        this.age = age;
    }

    public static Person createPerson(@MapsTo("name") String name, @MapsTo("age") int age) {
        return new Person(name, age);
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Here we have made our only declared constructor private, and created a static factory method. Notice that we've simply used the same `@MapsTo` annotation in the same way we did on the constructor from our previous example. The marshaller will see this method and know that it should use it to construct the object.

5.1.1.4. Example: An Immutable Entity with a Builder

For types with a large number of optional attributes, a builder is often the best approach.

```
@Portable
public class Person {
    private final String name;
    private final int age;

    private Person(@MapsTo("name") String name, @MapsTo("age") int age) {
        this.name = name;
        this.age = age;
    }

    public String getName() {
        return name;
    }
}
```

```
public int getAge() {
    return age;
}

@NonPortable
public static class Builder {
    private String name;
    private int age;

    public Builder name(String name) {
        this.name = name;
        return this;
    }

    public Builder age(int age) {
        this.age = age;
        return this;
    }

    public Person build() {
        return new Person(name, age);
    }
}
}
```

In this example, we have a nested `Builder` class that implements the Builder Pattern and calls the private `Person` constructor. Hand-written code will always use the builder to create `Person` instances, but the `@MapsTo` annotations on the private `Person` constructor tell Errai Marshalling to bypass the builder and construct instances of `Person` directly.

One final note: as a nested type of `Person` (which is marked `@Portable`), the builder itself would normally be portable. However, we do not intend to move instances of `Person.Builder` across the network, so we mark `Person.Builder` as `@NonPortable`.

5.1.2. Manual Mapping

Some classes may be out of your control, making it impossible to annotate them for auto-discovery by the marshalling framework. For cases such as this, there are two approaches which can be undertaken to include these classes in your application.

The first approach is the easiest, but is contingent on whether or not the class is directly exposed to the GWT compiler. That means, the classes must be part of a GWT module and within the GWT client packages. See the GWT documentation on [Client-Side Code](http://code.google.com/webtoolkit/doc/latest/DevGuideCodingBasicsClient.html) [http://code.google.com/webtoolkit/doc/latest/DevGuideCodingBasicsClient.html] for information on this.

5.1.2.1. Mapping Existing Client Classes

If you have client-exposed classes that cannot be annotated with the `@Portable` annotation, you may manually map these classes so that the marshaller framework will comprehend and producemarshallers for them and their nested types.

To do this, specify them in `ErraiApp.properties`, using the `errai.marshalling.serializableTypes` attribute with a whitespace separated list of classes to make portable.

Example 5.1. Example `ErraiApp.properties` defining portable classes.

```
errai.marshalling.serializableTypes=org.foo.client.UserEntity \  
                                     org.foo.client.GroupEntity \  
                                     org.abcinc.model.client.Profile
```

If any of the serializable types have nested classes that you wish to make non-portable, you can specify them like this:

Example 5.2. Example `ErraiApp.properties` defining nonportable classes.

```
errai.marshalling.nonserializableTypes=org.foo.client.UserEntity$Builder \  
                                         org.foo.client.GroupEntity$Builder
```

5.1.2.2. Aliased Mappings of Existing Interface Contracts

The marshalling framework supports and promotes the concept of marshalling by interface contract, where possible. For instance, the framework ships with a marshaller which can marshall data to and from the `java.util.List` interface. Instead of having custommarshallers for classes such as `ArrayList` and `LinkedList`, by default, these implementations are merely aliased to the `java.util.List` marshaller.

There are two distinct ways to go about doing this. The most straightforward is to specify which marshaller to alias when declaring your class is `@Portable`.

```
package org.foo.client;  
  
@Portable(aliasOf = java.util.List.class)  
public MyListImpl extends ArrayList {  
    // ..  
}
```

```
}

```

In the case of this example, the marshaller will not attempt to comprehend your class. Instead, it will merely rely on the `java.util.List` marshaller to dematerialize and serialize instances of this type onto the wire.

If for some reason it is not feasible to annotate the class, directly, you may specify the mapping in the **ErraiApp.properties** file using the `errai.marshalling.mappingAliases` attribute.

```
errai.marshalling.mappingAliases=org.foo.client.MyListImpl->java.util.List \
                                org.foo.client.MyMapImpl->java.util.Map

```

The list of classes is whitespace-separated so that it may be split across lines.

The example above shows the equivalent mapping for the `MyListImpl` class from the previous example, as well as a mapping of a class to the `java.util.Map` marshaller.

The syntax of the mapping is as follows: `<class_to_map> -> <contract_to_map_to> .`



Aliases do not inherit functionality!

When you alias a class to another marshalling contract, extended functionality of the aliased class will not be available upon deserialization. For this you must provide custommarshallers for those classes.

5.1.3. Manual Class Mapping

Although the default marshalling strategies in Errai Marshalling will suit the vast majority of use cases, there may be situations where it is necessary to manually map your classes into the marshalling framework to teach it how to construct and deconstruct your objects.

This is accomplished by specifying `MappingDefinition` classes which inform the framework exactly how to read and write state in the process of constructing and deconstructing objects.

5.1.3.1. MappingDefinition

All manual mappings should extend the `org.jboss.errai.marshalling.rebind.api.model.MappingDefinition` class. This is base metadata class which contains data on exactly how the marshaller can deconstruct and construct objects.

Consider the following class:

```
public class MySuperCustomEntity {
    private final String mySuperName;
    private String mySuperNickname;

    public MySuperCustomEntity(String mySuperName) {
        this.mySuperName = mySuperName;;
    }

    public String getMySuperName() {
        return this.mySuperName;
    }

    public void setMySuperNickname(String mySuperNickname) {
        this.mySuperNickname = mySuperNickname;
    }

    public String getMySuperNickname() {
        return this.mySuperNickname;
    }
}
```

Let us construct this object like so:

```
MySuperCustomEntity entity = new MySuperCustomEntity("Coolio");
entity.setSuperNickname("coo");
```

It is clear that we may rely on this object's two getter methods to extract the totality of its state. But due to the fact that the `mySuperName` field is final, the only way to properly construct this object is to call its only public constructor and pass in the desired value of `mySuperName`.

Let us consider how we could go about telling the marshalling framework to pull this off:

```
@CustomMapping
public MySuperCustomEntityMapping extends MappingDefinition {
    public MySuperCustomEntityMapping() {
        super(MySuperCustomEntity.class); //
    }
    (1)

    SimpleConstructorMapping cnsMapping = new SimpleConstructorMapping();
    cnsMapping.mapParamToIndex("mySuperName", 0, String.class); //
    (2)
```

```

        setInstantiationMapping(cnsMapping);
addMemberMapping(new WriteMapping("mySuperNickname",String.class,setMySuperNickname));//
    (3)

    addMemberMapping(new ReadMapping("mySuperName",String.class,"getMySuperName")); //
    (4)
addMemberMapping(new ReadMapping("mySuperNickname",String.class,"getMySuperNickname")); //
    (5)
    }
}

```

And that's it. This describes to the marshalling framework how it should go about constructing and deconstructing `MySuperCustomEntity`.

Paying attention to our annotating comments, let's describe what we've done here.

1. Call the constructor in `MappingDefinition` passing our reference to the class we are mapping.
2. Using the `SimpleConstructorMapping` class, we have indicated that a custom constructor will be needed to instantiate this class. We have called the `mapParamToIndex` method with three parameters. The first, `"mySupername"` describes the class field that we are targeting. The second parameter, the integer `0` indicates the parameter index of the constructor arguments that we'll be providing the value for the aforementioned field – in this case the first and only, and the final parameter `String.class` tells the marshalling framework which marshalling contract to use in order to de-marshall the value.
3. Using the `WriteMapping` class, we have indicated to the marshaller framework how to write the `"mySuperNickname"` field, using the `String.class` marshaller, and using the setter method `setMySuperNickname`.
4. Using the `ReadMapping` class, we have indicated to the marshaller framework how to read the `"mySuperName"` field, using the `String.class` marshaller, and using the getter method `getMySuperName`.
5. Using the `ReadMapping` class, we have indicated to the marshaller framework how to read the `"mySuperNickname"` field, using the `String.class` marshaller, and using the getter method `getMySuperNickname`.

5.1.4. Custom Marshallers

There is another approach to extending the marshalling functionality that doesn't involve mapping rules, and that is to implement your own `Marshaller` class. This gives you complete control over the parsing and emission of the JSON structure.

The implementation of marshallers is made relatively straight forward by the fact that both the server and the client share the same JSON parsing API.

Consider the included `java.util.Date` marshaller that comes built-in to the marshalling framework:

Example 5.3. DataMarshaller.java from the built-inmarshallers

```
@ClientMarshaller(Date.class)
@ServerMarshaller(Date.class)
public class DateMarshaller extends AbstractNullableMarshaller<Date> {
    @Override
    public Date[] getEmptyArray() {
        return new Date[0];
    }

    @Override
    public Date doNotNullDemarshall(final EJValue o, final MarshallingSession ctx) {
        if (o.isObject() != null) {
            EJValue qualifiedValue = o.isObject().get(SerializationParts.QUALIFIED_VALUE);
            if (!qualifiedValue.isNull() && qualifiedValue.isString() != null) {
                return new Date(Long.parseLong(qualifiedValue.isString().stringValue()));
            }
            EJValue numericValue = o.isObject().get(SerializationParts.NUMERIC_VALUE);
            if (!numericValue.isNull() && numericValue.isNumber() != null) {
                return new Date(new Double(numericValue.isNumber().doubleValue()).longValue());
            }
            if (!numericValue.isNull() && numericValue.isString() != null) {
                return new Date(Long.parseLong(numericValue.isString().stringValue()));
            }
        }

        return null;
    }

    @Override
    public String doNotNullMarshall(final Date o, final MarshallingSession ctx) {
        return "{\\" + SerializationParts.ENCODED_TYPE + "\\":
            \\" + Date.class.getName() + "\", " +
                "\\" + SerializationParts.OBJECT_ID + "\\:" + o.hashCode() + "\", " +
                    "\\" + SerializationParts.QUALIFIED_VALUE + "\\":
            \\" + o.getTime() + "\"}";
    }
}
```

The class is annotated with both `@ClientMarshaller` and `@ServerMarshaller` indicating that this class should be used for both marshalling on the client and on the server.

The `doNotNullDemarshall()` method is responsible for converting the given JSON object (which has already been parsed and verified non-null) into a Java object.

The `doNotNullMarshall()` method does roughly the inverse: it converts the given Java object into a String (which must be parseable as a JSON object) for transmission on the wire.

Remote Procedure Calls (RPC)

ErraiBus supports a high-level RPC layer to make typical client-server RPC communication easy on top of the bus. While it is possible to use ErraiBus without ever using this API, you may find it to be a more useful and concise approach for exposing services to the clients.

Please note that this API has changed since version 1.0. RPC services provide a way of creating type-safe mechanisms to make client-to-server calls. Currently, this mechanism only support client-to-server calls, and not vice-versa.

Creating a service is straight forward. It requires the definition of a remote interface, and a service class which implements it. See the following:

```
@Remote
public interface MyRemoteService {
    public boolean isEveryoneHappy();
}
```

The `@Remote` annotation tells Errai that we'd like to use this interface as a remote interface. The remote interface must be part of the GWT client code. It cannot be part of the server-side code, since the interface will need to be referenced from both the client and server side code. That said, the implementation of a service is relatively simple to the point:

```
@Service
public class MyRemoteServiceImpl implements MyRemoteService {

    public boolean isEveryoneHappy() {
        // blatantly lie and say everyone's happy.
        return true;
    }
}
```

That's all there is to it. You use the same `@Service` annotation as described in Section 2.4. The presence of the remote interface tips Errai off as to what you want to do with the class.



Warning

Beginning with Errai 2.0.CR1, the default for automatic service discovery has changed in favour of CDI based applications, meaning RPC service discovery must be explicitly turned on in case Errai CDI is not used (the `weld-integration.jar`

is not on the classpath). This can be done using an `init-param` in the servlet config of your `web.xml`:

```
<servlet>
  <servlet-name>ErraiServlet</servlet-name>
  <servlet-class>org.jboss.errai.bus.server.servlet.DefaultBlockingServlet</
servlet-class>
  <init-param>
    <param-name>auto-discover-services</param-name>
    <param-value>true</param-value>
  </init-param>
  <load-on-startup>1</load-on-startup>
</servlet>
```

6.1. Making calls

Calling a remote service involves use of the `MessageBuilder` API. Since all messages are asynchronous, the actual code for calling the remote service involves the use of a callback, which we use to receive the response from the remote method. Let's see how it works:

```
MessageBuilder.createCall(new RemoteCallback<Boolean>() {
  public void callback(Boolean isHappy) {
    if (isHappy) Window.alert("Everyone is happy!");
  }
}, MyRemoteService.class).isEveryoneHappy();
```

In the above example, we declare a remote callback that receives a `Boolean`, to correspond to the return value of the method on the server. We also reference the remote interface we are calling, and directly call the method. However, *don't be tempted to write code like this* :

```
boolean bool = MessageBuilder.createCall(..., MyRemoteService.class).isEveryoneHappy();
```

The above code will never return a valid result. In fact, it will always return `null`, `false`, or `0` depending on the type. This is due to the fact that the method is dispatched asynchronously, as in, it does not wait for a server response before returning control. The reason we chose to do this, as opposed to emulate the native GWT-approach, which requires the implementation of remote and `async` interfaces, was purely a function of a tradeoff for simplicity.

6.1.1. Proxy Injection

An alternative to using the `MessageBuilder` API is to have a proxy of the service injected.

```
@Inject
private Caller<MyRemoteService> remoteService;
```

For calling the remote service, the callback objects need to be provided to the `call` method before the corresponding interface method is invoked.

```
remoteService.call(callback).isEveryoneHappy();
```

The Errai IOC GWT module needs to be inherited to make use of caller injection. To do this, the following line needs to be added to the application's `*.gwt.xml` file. It is important that this line comes *after* the Errai Bus module:

```
<inherits name="org.jboss.errai.ioc.Container"/>
```

6.2. Handling exceptions

Handling remote exceptions can be done by providing an `ErrorCallback` on the client:

```
MessageBuilder.createCall(
    new RemoteCallback<Boolean>() {
        public void callback(Boolean isHappy) {
            if (isHappy) Window.alert("Everyone is happy!");
        }
    },
    new ErrorCallback() {
        public boolean error(Message message, Throwable caught) {
            try {
                throw caught;
            }
            catch (NobodyIsHappyException e) {
                Window.alert("OK, that's sad!");
            }
            catch (Throwable t) {
                GWT.log("An unexpected error has occurred", t);
            }
        }
    }
);
```

```
    }  
    return false;  
  }  
},  
MyRemoteService.class).isEveryoneHappy();
```

As remote exceptions need to be serialized to be sent to the client, the `@Portable` annotation needs to be present on the corresponding exception class (see [Chapter 5, *Marshalling*](#)). Further the exception class needs to be part of the client-side code. For more details on `ErrorCallbacks` see [Section 2.8, *Handling Errors*](#).

6.2.1. Global RPC exception handler

In a scenario where many different remote calls potentially throw the same exception types (e.g. exceptions related to authentication or authorization) it can be easier to register a global exception handler instead of providing error callbacks at each RPC invocation. This global exception handler is called in case an exception occurs in the process of a remote call that has no error callback associated with it. So, it will handle an otherwise uncaught exception.

```
@UncaughtException  
private void onUncaughtException(Throwable t) {  
  try {  
    throw caught;  
  }  
  catch (UserNotLoggedInException e) {  
    // navigate to login dialog  
  }  
  catch (Throwable t) {  
    GWT.log("An unexpected error has occurred", t);  
  }  
}
```

6.3. Client-side Interceptors

Client-side remote call interceptors provide the ability to manipulate or bypass the remote call before it's being sent. This is useful for implementing crosscutting concerns like caching, for example when the remote call should be avoided if the data is already cached locally.

To have a remote call intercepted, either an interface method or the remote interface type has to be annotated with `@InterceptedCall`. If the type is annotated, all interface methods will be intercepted.

```
@Remote
```

```
public interface CustomerService {

    @InterceptedCall(MyCacheInterceptor.class)
    public Customer retrieveCustomerById(long id);

}
```

Note that an ordered list of interceptors can be used for specifying an interceptor chain e.g.

```
@InterceptedCall({MyCacheInterceptor.class, MySecurityInterceptor.class})
public Customer retrieveCustomerById(long id);
```

Implementing an interceptor is easy:

```
public class MyCacheInterceptor implements RpcInterceptor {

    @Override
    public void aroundInvoke(final RemoteCallContext context) {
        // e.g check if the result is cached and carry out the actual call only
        // in case it's not.
        context.proceed() // executes the next interceptor in the chain or the
        // actual remote call.
        // context.setResult() // sets the result directly without carrying out
        // the remote call.
    }
}
```

The `RemoteCallContext` passed to the `aroundInvoke` method provides access to the intercepted method's name and read/write access to the parameter values provided at the call site.

Calling `proceed` executes the next interceptor in the chain or the actual remote call if all interceptors have already been executed. If access to the result of the (asynchronous) remote call is needed in the interceptor, one of the overloaded versions of `proceed` accepting a `RemoteCallback` has to be used instead.

The result of the remote call can be manipulated by calling `RemoteCallContext.setResult()`.

Not calling `proceed` in the interceptor bypasses the actual remote call, passing `RestCallContext.getResult()` to the `RemoteCallback` provided at the call site.

6.4. Session and request objects in RPC endpoints

Before invoking an endpoint method Errai sets up an `RpcContext` that provides access to message resources that are otherwise not visible to RPC endpoints.

```
@Service
public class MyRemoteServiceImpl implements MyRemoteService {

    public boolean isEveryoneHappy() {
        HttpSession session = RpcContext.getHttpSession();
        ServletRequest request = RpcContext.getServletRequest();
        ...
        return true;
    }
}
```

6.5. Batching remote calls

Some use cases require multiple interactions with the server to complete. Errai's RPC mechanism allows for batched invocations of remote methods that will be executed using a single server round-trip. This is useful for reducing the number of simultaneous HTTP connections and at the same time allows for reusing and combining fine-grained remote services.

Injecting a `BatchCaller` instead of a `Caller<T>` is all it takes to make use of batched remote procedure calls.

```
@EntryPoint
public class MyBean {

    @Inject
    private BatchCaller batchCaller;

    private void someMethod() {
        // ...
        batchCaller.call(remoteCallback1, RemoteService1.class).method1();
        batchCaller.call(remoteCallback2, RemoteService2.class).method2();

        // Invokes the accumulated remote requests using a single server round-trip.
        batchCaller.sendBatch();
    }
}
```

The remote methods will get executed only after `sendBatch()` was called. The method `sendBatch` accepts an additional `RemoteCallback` instance as a parameter which will be invoked when all remote calls have completed in success. Consequently, an `ErrorCallback` can also be provided which will get executed for all remote calls that have completed in failure.

Errai JAX-RS

JAX-RS (Java API for RESTful Web Services) is a Java EE standard (JSR-311) for implementing REST-based Web services in Java. Errai JAX-RS brings this standard to the browser and simplifies the integration of REST-based services in GWT client applications. Errai can generate proxies based on JAX-RS interfaces which will handle all the underlying communication and serialization logic. All that's left to do is to invoke a Java method.

Errai's JAX-RS support consists of the following:

- A client-side API to communicate with JAX-RS endpoints
- A code generator that runs at your project's build time, providing proxy implementations for each JAX-RS resource interfaces visible within the GWT module
- Errai IoC and CDI providers that allow you to `@Inject` instances of `Caller<T>` (the same API used in Errai RPC)}
- Integration with either Errai Marshalling or Jackson to translate request and response data between Java object and a string-based wire format

To get started with a working demo that makes use of Errai JAX-RS you can either download and unzip the [Errai tutorial project](https://github.com/errai/errai-tutorial/archive/master.zip) [https://github.com/errai/errai-tutorial/archive/master.zip] or check out the CRUD demo part of our [demo collection](https://github.com/errai/errai/tree/master/errai-demos) [https://github.com/errai/errai/tree/master/errai-demos] . If you prefer getting started from scratch keep reading

Figure 7.1. TODO Gliffy image title empty

7.1. Getting Started

7.1.1. Dependencies

To use Errai JAX-RS, you must include it on the compile-time classpath. If you are using Maven for your build, add this dependency:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-jaxrs-client</artifactId>
  <version>${errai.version}</version>
```

```
<scope>provided</scope>
</dependency>
```

or if you are not using Maven for dependency management, add `errai-jaxrs-client-version.jar` to your classpath.

If you intend to use Errai's JSON format on the wire you will need to add Errai's JAX-RS JSON provider to your classpath and make sure it gets deployed to the server.

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-jaxrs-provider</artifactId>
  <version>${errai.version}</version>
</dependency>
```

or manually add `errai-jaxrs-provider-version.jar` in case you're not using Maven. If your REST service returns Jackson generated JSON you do not need the `errai-jaxrs-provider` (see [Configuration](#)).

7.1.2. GWT Module

Once you have Errai JAX-RS on your classpath, ensure your application inherits the GWT module as well. Add this line to your application's `*.gwt.xml` file:

```
<inherits name="org.jboss.errai.enterprise.Jaxrs"/>
```

7.1.3. Server-Side JAX-RS Implementation

Errai's JAX-RS support consists mostly of features that make the client side easier and more reliable to maintain. You will need to use an existing third-party JAX-RS implementation on the server side. All Java EE 6 application servers include such a module out-of-the-box. If you are developing an application that you intend to deploy on a plain servlet container, you will have to choose a JAX-RS implementation (for example, RestEasy) and configure it properly in your `web.xml`.

Alternatively, you could keep your REST resource layer in a completely separate web application hosted on the same server (perhaps build an Errai JAX-RS client against an existing REST service you developed previously). In this case, you could factor out the shared JAX-RS interface into a shared library, leaving the implementation in the non-Errai application.

Finally, you can take advantage of the cross-origin resource sharing (CoRS) feature in modern browsers and use Errai JAX-RS to send requests to a third-party server. The third-party server

would have to be configured to allow cross-domain requests. In this case, you would write a JAX-RS-Annotated interface describing the remote REST resources, but you would not create an implementation of that interface.

7.1.4. Shared JAX-RS Interface

Errai JAX-RS works by leveraging standard Java interfaces that bear JAX-RS annotations. You will also want these interfaces visible to server-side code so that your JAX-RS resource classes can implement them (and inherit the annotations). This keeps the whole setup typesafe, and reduces duplication to the bare minimum. The natural solution, then is to put the JAX-RS interfaces under the `client.shared` package within your GWT module:

- project
 - src
 - main
 - java
 - `com.mycompany.myapp`
 - `MyApp.gwt.xml` [*the app's GWT module*]
 - `com.mycompany.myapp.client.local`
 - `MyAppClientStuff.java` [*code that @Injects Caller<MyAppRestResource>*]
 - `com.mycompany.myapp.client.shared`
 - `CustomerService.java` [*the JAX-RS interface*]
 - `com.mycompany.myapp.server`
 - `CustomerServiceImpl.java` [*the server-side JAX-RS resource implementation*]

The contents of the server-side files would be as follows:

Example 7.1. CustomerService.java

```
@Path( "customers" )
public interface CustomerService {
    @GET
    @Produces( "application/json" )
    public List<Customer> listAllCustomers();

    @POST
    @Consumes( "application/json" )
```

```
@Produces("text/plain")
public long createCustomer(Customer customer);
}
```

The above interface is visible both to server-side code and to client-side code. It is used by client-side code to describe the available operations, their parameter types, and their return types. If you use your IDE's refactoring tools to modify this interface, both the server-side and client-side code will be updated automatically.

Example 7.2. CustomerServiceImpl.java

```
public class CustomerServiceImpl implements CustomerService {

    @Override
    public List<Customer> listAllCustomers() {
        // Use a database API to look up all customers in back-end data store
        // Return the resulting list
    }

    @Override
    public long createCustomer(Customer customer) {
        // Store new Customer instance in back-end data store
    }
}
```

The above class implements the shared interface. Since it performs database and/or filesystem operations to manipulate the persistent data store, it is not GWT translatable, and it's therefore kept in a package that is not part of the GWT module.



Save typing and reduce duplication

Note that all JAX-RS annotations (`@Path` , `@GET` , `@Consumes` , and so on) can be inherited from the interface. You do not need to repeat these annotations in your resource implementation classes.

7.2. Creating Requests

This section assumes you have already set up the `CustomerService` JAX-RS endpoint as described in the previous section.

To create a request on the client, all that needs to be done is to invoke `RestClient.create()` , thereby providing the JAX-RS interface, a response callback and to invoke the corresponding interface method:

Example 7.3. App.java

```
...
Button create = new Button("Create", new ClickHandler() {
    public void onClick(ClickEvent clickEvent) {
        Customer customer = new Customer(firstName, lastName, postalCode);
        RestClient.create(CustomerService.class, callback).createCustomer(customer);
    }
});
...
```

For details on the callback mechanism see [Handling Responses](#).

7.2.1. Proxy Injection

Injectable proxies can be used as an alternative to calling `RestClient.create()`.

```
@Inject
private Caller<CustomerService> customerService;
```

To create a request, the callback objects need to be provided to the `call` method before the corresponding interface method is invoked.

```
customerService.call(callback).listAllCustomers();
```

To use caller injection, your application needs to inherit the Errai IOC GWT module. To do this, just add this line to your application's `*.gwt.xml` file and make sure it comes after the Errai JAX-RS module (see [Getting Started](#)):

```
<inherits name="org.jboss.errai.ioc.Container"/>
```



Note

The JAX-RS interfaces need to be visible to the GWT compiler and must therefore reside within the client packages (e.g. `client.shared`).

7.3. Handling Responses

An instance of Errai's `RemoteCallback<T>` has to be passed to the `RestClient.create()` call, which will provide access to the JAX-RS resource method's result. `T` is the return type of the JAX-RS resource method. In the example below it's just a `Long` representing a customer ID, but it can be any serializable type (see [Chapter 5, Marshalling](#)).

```
RemoteCallback<Long> callback = new RemoteCallback<Long>() {
    public void callback(Long id) {
        Window.alert("Customer created with ID: " + id);
    }
};
```

A special case of this `RemoteCallback` is the `ResponseCallback` which can be used as an alternative. It provides access to the `Response` object representing the underlying HTTP response. This is useful when more details of the HTTP response are needed, such as headers and the status code. The `ResponseCallback` can also be used for JAX-RS interface methods that return a `javax.ws.rs.core.Response` type. In this case, the `MarshallingWrapper` class can be used to manually demarshal the response body to an entity of the desired type.

```
ResponseCallback callback = new ResponseCallback() {
    public void callback(Response response) {
        Window.alert("HTTP status code: " + response.getStatusCode());
        Window.alert("HTTP response body: " + response.getText());
    }
};
```

For handling errors, Errai's error callback mechanism can be reused and an instance of `ErrorCallback` can optionally be passed to the `RestClient.create()` call. In case of an HTTP error, the `ResponseException` provides access to the `Response` object. All other `Throwables` indicate a communication problem.

```
ErrorCallback errorCallback = new RestErrorCallback() {
    public boolean error(Request request, Throwable throwable) {
        try {
            throw throwable;
        }
        catch (ResponseException e) {
            Response response = e.getResponse();
            // process unexpected response
        }
    }
};
```

```

        response.getStatusCode();
    }
    catch (Throwable t) {
        // process unexpected error (e.g. a network problem)
    }
    return false;
}
};

```

7.4. Client-side Interceptors

Client-side remote call interceptors provide the ability to manipulate or bypass the request before it's being sent. This is useful for implementing crosscutting concerns like caching or security features e.g:

- avoiding the request when the data is cached locally
- adding special HTTP headers or parameters to the request

To have a JAX-RS remote call intercepted, either an interface method or the remote interface type has to be annotated with `@InterceptedCall`. If the type is annotated, all interface methods will be intercepted.

```

@Path("customers")
public interface CustomerService {

    @GET
    @Path("/{id}")
    @Produces("application/json")
    @InterceptedCall(MyCacheInterceptor.class)
    public Customer retrieveCustomerById(@PathParam("id") long id);
}

```

Note that an ordered list of interceptors can be used for specifying an interceptor chain e.g.

```

@InterceptedCall({MyCacheInterceptor.class, MySecurityInterceptor.class})
public Customer retrieveCustomerById(@PathParam("id") long id);

```

Implementing an interceptor is easy:

```
public class MyCacheInterceptor implements RestClientInterceptor {

    @Override
    public void aroundInvoke(final RestCallContext context) {
        RequestBuilder builder = context.getRequestBuilder();
        builder.setHeader("headerName", "value");
        context.proceed();
    }
}
```

The `RestCallContext` passed to the `aroundInvoke` method provides access to the context of the intercepted JAX-RS (REST) remote call. It allows to read and write the parameter values provided at the call site and provides read/write access to the `RequestBuilder` instance which has the URL, HTTP headers and parameters set.

Calling `proceed` executes the next interceptor in the chain or the actual remote call if all interceptors have already been executed. If access to the result of the (asynchronous) remote call is needed in the interceptor, one of the overloaded versions of `proceed` accepting a `RemoteCallback` has to be used instead.

The result of the remote call can be manipulated by calling `RestCallContext.setResult()`.

Not calling `proceed` in the interceptor bypasses the actual remote call, passing `RestCallContext.getResult()` to the `RemoteCallback` provided at the call site.

7.5. Wire Format

Errai's JSON format will be used to serialize/deserialize your custom types. See [Chapter 5, Marshalling](#) for details.

Alternatively, a Jackson compatible JSON format can be used on the wire. See [Configuration](#) for details on how to enable Jackson marshalling.

7.6. Configuration

7.6.1. Configuring the default root path of JAX-RS endpoints

All paths specified using the `@Path` annotation on JAX-RS interfaces are by definition relative paths. Therefore, by default, it is assumed that the JAX-RS endpoints can be found at the specified paths relative to the GWT client application's context path.

To configure a relative or absolute root path, the following JavaScript variable can be set in either the host HTML page

```
<script type="text/javascript">
```

```
erraiJaxRsApplicationRoot = "/MyJaxRsEndpointPath";
</script>
```

or by using a JSNI method:

```
private native void setMyJaxRsAppRoot(String path) /*-{
    $wnd.erraiJaxRsApplicationRoot = path;
}-*/;
```

or by simply invoking:

```
RestClient.setApplicationRoot("/MyJaxRsEndpointPath");
```

The root path will be prepended to all paths specified on the JAX-RS interfaces. It serves as the base URL for all requests sent from the client.

7.6.2. Enabling Jackson marshalling

The following options are available for activating Jackson marshalling on the client. Note that this is a client-side configuration, the JAX-RS endpoint is assumed to already return a Jackson representation (Jackson is supported by all JAX-RS implementations). The `errai-jaxrs-provider.jar` does not have to be deployed on the server in this case!

```
<script type="text/javascript">
    erraiJaxRsJacksonMarshallingActive = true;
</script>
```

or by using a JSNI method:

```
private native void setJacksonMarshallingActive(boolean active) /*-{
    $wnd.erraiJaxRsJacksonMarshallingActive = active;
}-*/;
```

or by simply invoking:

```
RestClient.setJacksonMarshallingActive(true);
```

Errai JPA

Starting with Errai 2.1, Errai implements a subset of JPA 2.0. With Errai JPA, you can store and retrieve entity objects on the client side, in the browser's local storage. This allows the reuse of JPA-related code (both entity class definitions and procedural logic that uses the EntityManager) between client and server.

Errai JPA implements the following subset of JPA 2.0:

- Annotation-based configuration
- Entity Types with
 - Identifiers of any numeric type (int, long, short, etc.)
 - Generated identifiers
 - Regular attributes of any JPA Basic type (Java primitive types, boxed primitives, enums, BigInteger, BigDecimal, String, Date, Time, and Timestamp)
 - Singular and Plural (collection-valued) attributes of other entity types
 - All association types (one-to-one, one-to-many, many-to-one, many-to-many)
 - All association cascade rules (ALL, PERSIST, MERGE, REMOVE, REFRESH, DETACH)
 - Circular and self references work properly
 - Property access by field or get/set methods
- Named, typed JPQL queries that select exactly one entity type
 - With cascading fetch of related entities
 - With or without `WHERE` clause
 - All boolean, arithmetic, and string operators supported
 - All String manipulation functions supported
 - With or without `ORDER BY` clause
- Lifecycle events and entity lifecycle listeners
- Much of the Metamodel API (`Metamodel` , `EntityType` , `SingularAttribute` , `PluralAttribute` , etc.)



It's all client-side

Errai JPA is a declarative, typesafe interface to the web browser's `localStorage` object. As such it is a **client-side implementation** of JPA. Objects are stored and fetched from the browser's local storage, *not* from the JPA provider on the server side.

8.1. Getting Started

8.1.1. Compile-time dependency

To use Errai JPA, you must include it on the compile-time classpath. If you are using Maven for your build, add this dependency:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-jpa-client</artifactId>
  <version>${errai.version}</version>
</dependency>
```

If you are not using Maven for dependency management, add `errai-jpa-client-version.jar`, Hibernate 4.1.1, and Google Guava for GWT 12.0 to your compile-time classpath.

8.1.2. GWT Module Descriptor

Once you have Errai JPA on your classpath, ensure your application inherits the GWT module as well. Add this line to your application's `*.gwt.xml` file:

```
<inherits name="org.jboss.errai.jpa.JPA" />
```

8.1.3. INF/persistence.xml

Errai ignores META-INF/persistence.xml for purposes of client-side JPA. Instead, Errai scans all Java packages that are part of your GWT modules for classes annotated with `@Entity`. This allows you the freedom of defining a persistence.xml that includes both shared entity classes that you use on the client and the server, plus server-only entities that are defined in a server-only package.

8.1.4. Declaring an Entity Class

Classes whose instances can be stored and retrieved by JPA are called *entities*. To declare a class as a JPA entity, annotate it with `@Entity`.

JPA requires that entity classes conform to a set of rules. These are:

- The class must have an ID attribute
- The class must have a public or protected constructor that takes no arguments
- The class must be public and nonfinal
- No methods or persistent fields of the class may be final
- The class must be a top-level type (not a nested or inner class)

Here is an example of a valid entity class with an ID attribute (`id`) and a String-valued persistent attribute (`name`):

```
@Entity
public class Genre {

    @Id @GeneratedValue
    private int id;

    private String name;

    // This constructor is used by JPA
    public Genre() {}

    // This constructor is not used by JPA
    public Genre(String name) {
        this();
        this.name = name;
    }

    // These getter and Setter methods are optional:

    public int getId() { return id; }
    public void setId(int id) { this.id = id; }

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }
}
```

8.1.4.1. Entity Attributes

The state of fields and JavaBeans properties of entities are generally persisted with the entity instance. These persistent things are called *attributes* .

JPA Attributes are subdivided into two main types: *singular* and *plural* . Singular attributes are scalar types like `Integer` or `String` . Plural attributes are collection values, such as `List<Integer>` or `Set<String>` .

The values of singular attributes (and the elements of plural attributes) can be of any application-defined entity type or a JPA Basic type. The JPA basic types are all of the Java primitive types, all boxed primitives, enums, `BigInteger`, `BigDecimal`, `String`, `Date` (`java.util.Date` or `java.sql.Date`), `Time`, and `Timestamp`.

You can direct JPA to read and write your entity's attributes by direct field access or via JavaBeans property access methods (that is, "getters and setters"). Direct field access is the default. To request property access, annotate the class with `@Access(AccessType.PROPERTY)` . If using direct field access, attribute-specific JPA annotations should be on the fields themselves; when using property access, the attribute-specific annotations should be on the getter method for that property.

8.1.4.2. ID Attributes and Auto-Generated Identifiers

Each entity class must have exactly one ID attribute. The value of this attribute together with the fully-qualified class name uniquely identifies an instance to the entity manager.

ID values can be assigned by the application, or they can be generated by the JPA entity manager. To declare a generated identifier, annotate the field with `@GeneratedValue` . To declare an application-assigned identifier, leave off the `@GeneratedValue` annotation.

Generated identifier fields must not be initialized or modified by application code. Application-assigned identifier fields must be initialized to a unique value before the entity is persisted by the entity manager, but must not be modified afterward.

8.1.4.3. Single-valued Attributes

By default, every field of a JPA basic type is a persistent attribute. If a basic type field should not be persistent, mark it with `transient` or annotate it with `@Transient` .

Single-valued attributes of entity types must be annotated with `@OneToOne` or `@ManyToOne` .

Single-valued types that are neither entity types nor JPA Basic types are not presently supported by Errai JPA. Such attributes must be marked transient.

Here is an example of an entity with single-valued basic attributes and a single-valued relation to another entity type:

```

@Entity
public class Album {

    @GeneratedValue
    @Id
    private Long id;

    private String name;

    @ManyToOne
    private Artist artist;

    private Date releaseDate;

    private Format format;

    public Long getId() { return id; }
    public void setId(Long id) { this.id = id; }

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }

    public Artist getArtist() { return artist; }
    public void setArtist(Artist artist) { this.artist = artist; }

    public Date getReleaseDate() { return releaseDate; }
    public void setReleaseDate(Date releaseDate) { this.releaseDate = releaseDate; }

    public Format getFormat() { return format; }
    public void setFormat(Format format) { this.format = format; }
}

```

8.1.4.4. Plural (collection-valued) Attributes

Collection-valued types `Collection<T>`, `Set<T>`, and `List<T>` are supported. JPA rules require that all access to the collections are done through the collection interface method; never by specific methods on an implementation.

The element type of a collection attribute can be a JPA basic type or an entity type. If it is an entity type, the attribute must be annotated with `@OneToMany` or `@ManyToMany`.

Here is an example of an entity with two plural attributes:

```

@Entity
public class Artist {

    @Id

```

```

private Long id;

private String name;

// a two-way relationship (albums refer back to artists)
@OneToMany(mappedBy="artist", cascade=CascadeType.ALL)
private Set<Album> albums = new HashSet<Album>();

// a one-way relationship (genres don't reference artists)
@OneToMany(cascade={CascadeType.PERSIST, CascadeType.MERGE})
private Set<Genre> genres = new HashSet<Genre>();

public Long getId() { return id; }
public void setId(Long id) { this.id = id; }

public String getName() { return name; }
public void setName(String name) { this.name = name; }

public Set<Album> getAlbums() { return albums; }
public void setAlbums(Set<Album> albums) { this.albums = albums; }

public Set<Genre> getGenres() { return genres; }
public void setGenres(Set<Genre> genres) { this.genres = genres; }
}

```

8.1.5. Entity Lifecycle States

8.1.5.1. Cascade Rules

When an entity changes state (more on this later), that state change can be cascaded automatically to related entity instances. By default, no state changes are cascaded to related entities. To request cascading of entity state changes, use the `cascade` attribute on any of the relationship quantifiers `@OneToOne`, `@ManyToOne`, `@OneToMany`, and `@ManyToMany`.

CascadeType value	Description
PERSIST	Persist the related entity object(s) when this entity is persisted
MERGE	Merge the attributes of the related entity object(s) when this entity is merged
REMOVE	Remove the related entity object(s) from persistent storage when this one is removed
REFRESH	Not applicable in Errai JPA
DETACH	Detach the related entity object(s) from the entity manager when this object is detached
ALL	Equivalent to specifying all of the above

For an example of specifying cascade rules, refer to the `Artist` example above. In that example, the cascade type on `albums` is `ALL`. When a particular `Artist` is persisted or removed, detached, etc., all of that artist's albums will also be persisted or removed, or detached correspondingly. However, the cascade rules for `genres` are different: we only specify `PERSIST` and `MERGE`. Because a `Genre` instance is reusable and potentially shared between many artists, we do not want to remove or detach these when one artist that references them is removed or detached. However, we still want the convenience of automatic cascading persistence in case we persist an `Artist` which references a new, unmanaged `Genre`.

8.1.6. Obtaining an instance of EntityManager

The entity manager provides the means for storing, retrieving, removing, and otherwise affecting the lifecycle state of entity instances.

To obtain an instance of `EntityManager` on the client side, use Errai IoC (or CDI) to inject it into any client-side bean:

```
@EntryPoint
public class Main {
    @Inject EntityManager em;
}
```

8.1.6.1. Storing and Updating Entities

To store an entity object in persistent storage, pass that object to the `EntityManager.persist()` method. Once this is done, the entity instance transitions from the *new* state to the *managed* state.

If the entity references any related entities, these entities must be in the managed state already, or have cascade-on-persist enabled. If neither of these criteria are met, an `IllegalStateException` will be thrown.

See an example in the following section.

8.1.6.2. Fetching Entities by ID

If you know the unique ID of an entity object, you can use the `EntityManager.find()` method to retrieve it from persistent storage. The object returned from the `find()` method will be in the managed state.

Example:

```
// make it
Album album = new Album();
album.setArtist(null);
```

```
album.setName("Abbey Road");
album.setReleaseDate(new Date(-8366400000L));

// store it
EntityManager em = getEntityManager();
em.persist(album);
em.flush();
em.detach(album);
assertNotNull(album.getId());

// fetch it
Album fetchedAlbum = em.find(Album.class, album.getId());
assertNotSame(album, fetchedAlbum);
assertEquals(album.toString(), fetchedAlbum.toString());
```

8.1.6.3. Removing Entities from Persistent Storage

To remove a persistent managed entity, pass it to the `EntityManager.remove()` method. As the cascade rules specify, related entities will also be removed recursively.

Once an entity has been removed and the entity manager's state has been flushed, the entity object is unmanaged and back in the *new* state.

8.1.6.3.1. Clearing all Local Storage

Errai's `EntityManager` class provides a `removeAll()` method which removes everything from the browser's persistent store for the domain of the current webpage.

This method is not part of the JPA standard, so you must down-cast your client-side `EntityManager` instance to `ErraiEntityManager`. Example:

```
@EntryPoint
public class Main {

    @Inject EntityManager em;

    void resetJpaStorage() {
        ((ErraiEntityManager) em).removeAll();
    }
}
```

8.1.6.4. Detaching Entity Instances from the Entity Manager

For every entity instance in the managed state, changes to the attribute values of that entity are persisted to local storage whenever the entity manager is flushed. To prevent this automatic

updating from happening, you can *detach* an entity from the entity manager. When an instance is detached, it is not deleted. All information about it remains in persistent storage. The next time that entity is retrieved, the entity manager will create a new and separate managed instance for it.

To detach one particular object along with all related objects whose cascade rules say so, call `EntityManager.detach()` and pass in that object.

To detach all objects from the entity manager at once, call `EntityManager.detachAll()`.

8.1.6.5. Testing if an Entity is in the Managed State

To check if a given object is presently managed by the entity manager, call `EntityManager.contains()` and pass in the object of interest.

8.1.7. Named Queries

To retrieve one or more entities that match a set of criteria, Errai JPA allows the use of JPA *named queries*. Named queries are declared in annotations on entity classes.

8.1.7.1. Declaring Named Queries

Queries in JPA are written in the JPQL language. As of Errai 2.1, Errai JPA does not support all JPQL features. Most importantly, implicit and explicit joins in queries are not yet supported. Queries of the following form generally work:

```
SELECT et FROM EntityType et WHERE [expression with constants, named parameters and attributes
```

Here is how to declare a JPQL query on an entity:

```
@NamedQuery(name="selectAlbumByName", query="SELECT a FROM Album a WHERE
a.name=:name")
@Entity
public class Album {
    ... same as before ...
}
```

To declare more than one query on the same entity, wrap the `@NamedQuery` annotations in `@NamedQueries` like this:

```
@NamedQueries({
    @NamedQuery(name="selectAlbumByName", query="SELECT a FROM Album a WHERE a.name
= :name"),
```

```

    @NamedQuery(name="selectAlbumsAfter", query="SELECT a FROM Album a WHERE
    a.releaseDate >= :startDate")
    })
    @Entity
    public class Album {
        ... same as before ...
    }

```

8.1.7.2. Executing Named Queries

To execute a named query, retrieve it by name and result type from the entity manager, set the values of its parameters (if any), and then call one of the execution methods `getSingleResult()` or `getResultList()`.

Example:

```

TypedQuery<Album> q = em.createNamedQuery("selectAlbumByName", Album.class);
q.setParameter("name", "Let It Be");
List<Album> fetchedAlbums = q.getResultList();

```

8.1.8. Entity Lifecycle Events

To receive a notification when an entity instance transitions from one lifecycle state to another, use an entity lifecycle listener.

These annotations can be applied to methods in order to receive notifications at certain points in an entity's lifecycle. These events are delivered for direct operations initiated on the `EntityManager` as well as operations that happen due to cascade rules.

Annotation	Meaning
<code>@PrePersist</code>	The entity is about to be persisted or merged into the entity manager.
<code>@PostPersist</code>	The entity has just been persisted or merged into the entity manager.
<code>@PreUpdate</code>	The entity's state is about to be captured into the browser's local storage.
<code>@PostUpdate</code>	The entity's state has just been captured into the browser's local storage.
<code>@PreRemove</code>	The entity is about to be removed from persistent storage.
<code>@PostRemove</code>	The entity has just been removed from persistent storage.

Annotation	Meaning
@PostLoad	The entity's state has just been retrieved from the browser's localStorage.

JPA lifecycle event annotations can be placed on methods in the entity type itself, or on a method of any type with a public no-args constructor.

To receive lifecycle event notifications directly on the affected entity instance, create a no-args method on the entity class and annotate it with one or more of the lifecycle annotations in the above table.

For example, here is a variant of the Album class where instances receive notification right after they are loaded from persistent storage:

```
@Entity
public class Album {

    ... same as before ...

    @PostLoad
    public void postLoad() {
        System.out.println("Album " + getName() + " was just loaded into the entity
manager");
    }
}
```

To receive lifecycle methods in a different class, declare a method that takes one parameter of the entity type and annotate it with the desired lifecycle annotations. Then name that class in the @EntityListeners annotation on the entity type.

The following example produces the same results as the previous example:

```
@Entity
@EntityListeners(StandaloneLifecycleListener.class)
public class Album {

    ... same as always ...

}

public class StandaloneLifecycleListener {

    @PostLoad
    public void albumLoaded(Album a) {
```

```
public void postLoad() {
    System.out.println("Album " + a.getName() + " was just loaded into the
entity manager");
}
}
```

8.1.9. JPA Metamodel

Errai captures structural information about entity types at compile time and makes them available in the GWT runtime environment. The JPA metamodel includes methods for enumerating all known entity types and enumerating the singular and plural attributes of those types. Errai extends the JPA 2.0 Metamodel by providing methods that can create new instances of entity classes, and read and write attribute values of existing entity instances.

As an example of what is possible, this functionality could be used to create a reusable UI widget that can present an editable table of any JPA entity type.

To access the JPA Metamodel, call the `EntityManager.getMetamodel()` method. For details on what can be done with the stock JPA metamodel, see the API's javadoc or consult the JPA specification.

8.1.9.1. Errai Extensions to JPA Metamodel API

Wherever you obtain an instance of `SingularAttribute` from the metamodel API, you can down-cast it to `ErraiSingularAttribute`. Likewise, you can down-cast any `PluralAttribute` to `ErraiPluralAttribute`.

In either case, you can read the value of an arbitrary attribute by calling `ErraiAttribute.get()` and passing in the entity instance. You can set any attribute's value by calling `ErraiAttribute.set()`, passing in the entity instance and the new value.

In addition to `get()` and `set()`, `ErraiPluralAttribute` also has the `createEmptyCollection()` method, which creates an empty collection of the correct interface type for the given attribute.

8.1.10. JPA Features Not Implemented in Errai 2.1

The following features are not yet implemented, but could conceivably be implemented in a future Errai JPA release:

- Flush modes other than immediate
- Transactions, including `EntityManager.getTransaction()`
- More than one persistence context
- In named queries:

- Joins and nested attribute paths (`a.b.c`) do not yet work, although single-step attribute paths (`a.b`) do.
- The `SELECT` clause must specify exactly one entity type. Selection of individual attributes is not yet implemented.
- Embedded collections
- Compound identifiers (presently, only basic types are supported for entity IDs)
- Polymorphic relations (eg. relationship to a collection of a base entity type)
- `EntityManager.merge()`
- `EntityManager.refresh()` to pick up changes made in `localStorage` from a different browser window/tab.
- Criteria Queries
 - The generated static Metamodel
- The `@PersistenceContext` annotation currently has no effect in client-side code (use `@Inject` instead)

The following may never be implemented due to limitations and restrictions in the GWT client-side environment:

- `EntityManager.createQuery(String, ...)` (that is, unnamed queries) are impractical because JPQL queries are parsed at compile time, not in the browser.
- `EntityManager.createNativeQuery(String, ...)` don't make sense because the underlying database is just a hash table. It does not have a query language.
- Persistent attributes of type `java.util.Calendar` because the `Calendar` class is not in GWT's JRE emulation library.

8.1.11. Other Caveats for Errai 2.1 JPA

We hope to remedy these shortcomings in a future release.

- In Dev Mode, changes to entity classes are not discovered on page refresh. You need to restart Dev Mode.
- The local data stored in the browser is not encrypted

8.2. Errai JPA Data Sync

Traditional JPA implementations allow you to store and retrieve entity objects on the server side. Errai's JPA implementation allows you to store and retrieve entity objects in the web browser using

the same APIs. All that's missing is the ability to synchronize the stored data between the server side and the client side.

This is where Errai JPA Data Sync comes in: it provides an easy mechanism for two-way synchronization of data sets between the client and the server.

8.2.1. How To Use It

8.2.1.1. Dependencies

First, ensure your `pom.xml` includes a dependency on the Data Sync module. This module must be packaged in your application's WAR file, so include it with the default scope (compile):

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-jpa-datasync</artifactId>
  <version>${errai.version}</version>
</dependency>
```

Then, ensure your project's `gwt.xml` module descriptor includes a dependency on the Data Sync GWT module:

```
<inherits name="org.jboss.errai.jpa.sync.DataSync" />
```

8.2.1.2. A Running Example

For the rest of this chapter, we will refer to the following Entity classes, which are defined in a shared package that's visible to client and server code:

```
@Portable
@Entity
@NamedQuery(name = "allUsers", query = "SELECT u FROM User u")
public class User {

  @Id
  @GeneratedValue
  private long id;

  private String name;

  // getters and setters omitted
```

```
}

```

```
@Portable
@Entity
@NamedQuery(name = "groceryListsForUser", query = "SELECT gl FROM GroceryList
gl WHERE gl.owner=:user")
public class GroceryList {

    @Id
    @GeneratedValue
    private long id;

    @ManyToOne
    private User owner;

    @OneToMany(cascade = { CascadeType.PERSIST, CascadeType.MERGE, CascadeType.REFRESH })
    private List<Item> items = new ArrayList<Item>();

    // getters and setters omitted
}

```

```
@Portable
@Entity
@NamedQuery(name = "allItems", query = "SELECT i FROM Item i")
public class Item {

    @Id
    @GeneratedValue
    private long id;

    private String name;
    private String department;
    private String comment;
    private Date addedOn;

    @ManyToOne(cascade = { CascadeType.PERSIST, CascadeType.MERGE, CascadeType.REFRESH })
    private User addedBy;

    // getters and setters omitted
}

```

To summarize: there are three entity types: `User`, `GroceryList`, and `Item`. Each `GroceryList` belongs to a `User` and has a list of `Item` objects.



Note

All the entities involved in the data synchronization request must be marshallable via Errai Marshalling. This is normally accomplished by adding the `@Portable` annotation to each JPA entity class, but it is also acceptable to list them in `ErraiApp.properties`. See the [Chapter 5, Marshalling](#) section for more details.

Now let's say we want to synchronize the data for all of a user's grocery lists. This will make them available for offline use through Errai JPA, and at the same time it will update the server with the latest changes made on the client. Ultimately, the sync operation is accomplished in one asynchronous call, but first we have to prepare a few things on the client and the server.

8.2.1.3. Client Side

```
@Inject private ClientSyncManager syncManager;
@Inject private EntityManager em;

public void syncGroceryLists(User forUser) {
    RemoteCallback<List<SyncResponse<GroceryList>>> onCompletion = new RemoteCallback<List<SyncResponse<GroceryList>>>() {
        @Override
        public void callback(List<SyncResponse<GroceryList>> response) {
            Window.alert("Data Sync Complete!");
        }
    };

    errorCallback<?> onError = new BusErrorCallback() {

        @Override
        public boolean error(Message message, Throwable throwable) {
            Window.alert("Data Sync failed!");
            return false;
        }
    };

    Map<String, Object> queryParams = new HashMap<String, Object>();
    queryParams.put("user", forUser);

    syncManager.coldSync("groceryListsForUser", GroceryList.class, queryParams, onCompletion, onError);
}
```



Important

The `onCompletion` and `onError` callbacks are optional. In the unlikely case that your application doesn't care if a data sync request completed successfully, you can pass `null` for either callback.

Once your `onCompletion` callback has been notified, the server and client will have the same entities stored in their respective databases for all entities reachable from the given query result.

8.2.1.4. Server Side – `DataSyncServiceImpl`

During the `coldSync()` call, the client-side sync manager sends an *Errai RPC* request to the server. Although a server-side implementation of the remote interface is provided, you are responsible for implementing a thin wrapper around it. This wrapper serves two purposes:

1. It allows you to determine how to obtain a reference to the JPA `EntityManager` (and to choose which persistence context the server-side data sync will operate on)
2. It allows you to inspect the contents of each sync request and make security decisions about access to particular entities

If you are deploying to a container that supports CDI and EJB 3, you can use this `DataSyncServiceImpl` as a template for your own:

```
@Stateless @org.jboss.errai.bus.server.annotations.Service
public class DataSyncServiceImpl implements DataSyncService {

    @PersistenceContext
    private EntityManager em;

    private final JpaAttributeAccessor attributeAccessor = new JavaReflectionAttributeAccessor();

    @Inject private LoginService loginService;

    @Override
    public <X> List<SyncResponse<X>> coldSync(SyncableDataSet<X> dataSet, List<SyncRequestOperati

    // Ensure a user is logged in
    User currentUser = loginService.whoAmI();
    if (currentUser == null) {
        throw new IllegalStateException("Nobody is logged in!");
    }

    // Ensure user is accessing their own data!
    if (dataSet.getQueryName().equals("groceryListsForUser")) {
```

```
    User requestedUser = (User) dataSet.getParameters().get("user");
    if (!currentUser.getId().equals(requestedUser.getId())) {
        throw new AccessDeniedException("You don't have permission to sync user
" + requestedUser.getId());
    }
}
else {
    throw new IllegalArgumentException("You don't have permission to sync
dataset " + dataSet.getQueryName());
}

DataSyncService dss = new org.jboss.errai.jpa.sync.server.DataSyncServiceImpl(em, attribute
return dss.coldSync(dataSet, remoteResults);
}
}
```

If you are not using EJB 3, you will not be able to use the `@PersistenceContext` annotation. In this case, obtain a reference to your `EntityManager` the same way you would anywhere else in your application.

8.2.1.5. Dealing With Conflicts

When the client sends the sync request to the server, it includes information about the state it expects each entity to be in. If an entity's state on the server does not match this expected state on the client, the server ignores the client's change request and includes a `ConflictResponse` object in the sync reply.

When the client processes the sync responses from the server, it applies the new state from the server to the local data store. This overwrites the change that was initially requested from the client. In short, you could call this the "server wins" conflict resolution policy.

In some cases, your application may be able to do something smarter: apply domain-specific knowledge to merge the conflict automatically, or prompt the user to perform a manual merge. In order to do this, you will have to examine the server response from inside the `onCompletion` callback you provided to the `coldSync()` method:

```
RemoteCallback<List<SyncResponse<GroceryList>>> onCompletion = new RemoteCallback<List<Sync
@Override
public void callback(List<SyncResponse<GroceryList>> responses) {
    for (SyncResponse<GroceryList> response : responses) {
        if (response instanceof ConflictResponse) {
            ConflictResponse<GroceryList> cr = (ConflictResponse<GroceryList>) response;
            List<Item> expectedItems = cr.getExpected().getItems();
            List<Item> serverItems = cr.getActualNew().getItems();
            List<Item> clientItems = cr.getRequestedNew().getItems();
```

```
        // merge the list of items by comparing each to expectedItems
        List<Item> merged = ...;

        // update local storage with the merged list
        em.find(GroceryList.class, cr.getActualNew().getId()).setItems(merged);
        em.flush();
    }
}
};
```

Remember, because of Errai's default "server wins" resolution policy, the call to `em.find(GroceryList.class, cr.getActualNew().getId())` will return a `GroceryList` object that has already been updated to match the state present in `serverItems`.



Note

Searching for `ConflictResponse` objects in the `onCompletion` callback is the only way to recover client data that was clobbered in a conflict. If you do not merge this data back into local storage, or at least retain a reference to the `cr.getRequestNew()` object, this conflicting client data will be lost forever.

In a future release of Errai JPA, we plan to provide a client-side callback mechanism for custom conflict handling. If such a callback is registered, it will override the default behaviour.

Data Binding

Errai's data binding module provides the ability to bind model objects to UI fields/widgets. The bound properties of the model and the UI components will automatically be kept in sync for as long as they are bound. So, there is no need to write code for UI updates in response to model changes and no need to register listeners to update the model in response to UI changes.

9.1. Getting Started

The data binding module is directly integrated with [Chapter 10, Errai UI](#) and [Chapter 8, Errai JPA](#) but can also be used as a standalone project in any GWT client application:

9.1.1. Compile-time dependency

To use Errai's data binding module, you must include it on the compile-time classpath. If you are using Maven for your build, add this dependency:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-data-binding</artifactId>
  <version>${errai.version}</version>
</dependency>
```

If you are not using Maven for dependency management, add `errai-data-binding-
version.jar` to your classpath.

9.1.2. GWT module descriptor

You must also inherit the Errai data binding module by adding the following line to your GWT module descriptor (`gwt.xml`).

Example 9.1. App.gwt.xml

```
<inherits name="org.jboss.errai.databinding.DataBinding" />
```

9.1.3. Bindable Objects

Objects that should participate in data bindings have to be marked as `@Bindable` and must follow Java bean conventions. All editable properties of these objects are then bindable to UI widgets.

Example 9.2. Customer.java

```
@Bindable
public class Customer {
    ...
    private String name;

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }
    ...
}
```



Important

If you cannot or prefer not to annotate your classes with `@Bindable`, you can alternatively specify bindable types in your `ErraiApp.properties` using a whitespace-separated list of fully qualified class names:
`errai.ui.bindableTypes=org.example.Model1 org.example.Model2`

9.1.4. Initializing a DataBinder

An instance of `DataBinder` is required to create bindings. It can either be injected into a client-side bean:

```
public class CustomerView {
    @Inject
    private DataBinder<Customer> dataBinder;
}
```

or created manually:

```
DataBinder<Customer> dataBinder = DataBinder.forType(Customer.class);
```

In both cases above, the `DataBinder` instance is associated with a new instance of the model (e.g. a new `Customer` object). A `DataBinder` can also be associated with an already existing object:

```
DataBinder<Customer> dataBinder = DataBinder.forModel(existingCustomerObject);
```

In case there is existing state in either the model object or the UI components before they are bound, initial state synchronization can be carried out to align the model and the corresponding UI fields.

For using the model object's state to set the initial values in the UI:

```
DataBinder<Customer> dataBinder = DataBinder.forModel(existingCustomerObject, InitialState.FROM_MODEL);
```

For using the UI values to set the initial state in the model object:

```
DataBinder<Customer> dataBinder = DataBinder.forModel(existingCustomerObject, InitialState.FROM_UI);
```

9.2. Creating Bindings

Bindings can be created by calling the `bind` method on a `DataBinder` instance, thereby specifying which widgets should be bound to which properties of the model. It is possible to use property chains for bindings, given that all nested properties are of bindable types. When binding to `customer.address.streetName`, for example, both `customer` and `address` have to be of a type annotated with `@Bindable`.

```
public class CustomerView {
    @Inject
    private DataBinder<Customer> dataBinder;

    private Customer customer;
    private TextBox nameTextBox = new TextBox();
    // more UI widgets...

    @PostConstruct
    private void init() {
        customer = dataBinder
            .bind(nameTextBox, "name")
            .bind(idLabel, "id")
    }
}
```

```
        .getModel();
    }
}
```

After the call to `dataBinder.bind()` in the example above, the customer object's name property and the `nameTextBox` are kept in sync until either the `dataBinder.unbind()` method is called or the `CustomerView` bean is destroyed.

That means that a call to `customer.setName()` will automatically update the value of the `TextBox` and any change to the `TextBox`'s value in the browser will update the customer object's name property. So, `customer.getName()` will always reflect the currently displayed value of the `TextBox`.



Note

It's important to retrieve the model instance using `dataBinder.getModel()` before making changes to it as the data binder will provide a proxy to the model to ensure that changes will update the corresponding UI components.



Tip

Errai also provides a *declarative binding API* that can be used to create bindings automatically based on matching field and model property names.

9.3. Specifying Converters

Errai has built-in conversion support for all Number types as well as Boolean and Date to `java.lang.String` and vice versa. However, in some cases it will be necessary to provide custom converters (e.g. if a custom date format is desired). This can be done on two levels.

9.3.1. Registering a global default converter

```
@DefaultConverter
public class MyCustomDateConverter implements Converter<Date, String> {

    private static final String DATE_FORMAT = "YY_DD_MM";

    @Override
    public Date toModelValue(String widgetValue) {
        return DateTimeFormat.getFormat(DATE_FORMAT).parse(widgetValue);
    }
}
```

```

@Override
public String toWidgetValue(Date modelValue) {
    return DateTimeFormat.getFormat(DATE_FORMAT).format((Date) modelValue);
}
}

```

All converters annotated with `@DefaultConverter` will be registered as global defaults calling `Convert.registerDefaultConverter()`. Note that the `Converter` interface specifies two type parameters. The first one represents the type of the model field, the second one the type held by the widget (e.g. `String` for widgets implementing `HasValue<String>`). These default converters will be used for all bindings with matching model and widget types.

9.3.2. Providing a binding-specific converter

Alternatively, converter instances can be passed to the `dataBinder.bind()` calls.

```
dataBinder.bind(textBox, "name", customConverter);
```

Converters specified on the binding level take precedence over global default converters with matching types.

9.4. Property Change Handlers

In some cases keeping the model and the UI in sync is not enough. Errai's `DataBinder` allows for the registration of `PropertyChangeHandlers` for specific properties, property expressions or all properties of a bound model. A property expression can be a property chain such as `customer.address.street`. It can end in a wildcard to indicate that changes of any property of the corresponding bean should be observed (e.g. `"customer.address.*"`). A double wildcard can be used at the end of a property expression to register a cascading change handler for any nested property (e.g. `"customer.**"`).

This provides a uniform notification mechanism for model and UI value changes. `PropertyChangeHandlers` can be used to carry out any additional logic that might be necessary after a model or UI value has changed.

```

dataBinder.addPropertyChangeListener(new PropertyChangeListener() {
    @Override
    public void onPropertyChange(PropertyChangeEvent event) {
        Window.alert(event.getPropertyName() + " changed to:" + event.getNewValue());
    }
});

```

```
dataBinder.addPropertyChangeListener("name", new PropertyChangeListener() {
    @Override
    public void onPropertyChange(PropertyChangeEvent event) {
        Window.alert("name changed to:" + event.getNewValue());
    }
});
```

9.5. Declarative Binding

Programmatic binding as described above (see [Creating Bindings](#)) can be tedious when working with UI components that contain a large number of input fields. Errai provides an annotation-driven binding API that can be used to create bindings automatically which cuts a lot of boilerplate code. The declarative API will work in any [Errai IOC](#) managed bean (including [Chapter 10, Errai UI templates](#)). Simply inject a data binder or model object and declare the bindings using `@Bound`.

Here is a simple example using an injected model object provided by the `@Model` annotation (field injection is used here, but constructor and method injection are supported as well):

```
@Dependent
public class CustomerView {
    @Inject @Model
    private Customer customer;

    @Inject @Bound
    private TextBox name;

    @Bound
    private Label id = new Label();

    ....
}
```

Here is the same example injecting a `DataBinder` instead of the model object. This is useful when more control is needed (e.g. the ability to register property change handlers). The `@AutoBound` annotation specifies that this `DataBinder` should be used to bind the model to all enclosing widgets annotated with `@Bound`. This example uses field injection again but constructor and method injection are supported as well.

```
@Dependent
public class CustomerView {
    @Inject @AutoBound
```

```

private DataBinder<Customer> customerBinder;

@Inject @Bound
private TextBox name;

@Bound
private Label id = new Label();

...
}

```

In both examples above an instance of the `Customer` model is automatically bound to the corresponding UI widgets based on matching field names. The model object and the UI fields will automatically be kept in sync. The widgets are inferred from all enclosing fields and methods annotated with `@Bound` of the class that defines the `@AutoBound DataBinder` or `@Model` and all its super classes.

9.5.1. Default, Simple, and Chained Property Bindings

By default, bindings are determined by matching field names to property names on the model object. In the examples above, the field `name` was automatically bound to the JavaBeans property name of the model (`user` object). If the field name does not match the model property name, you can use the `property` attribute of the `@Bound` annotation to specify the name of the property. The property can be a simple name (for example, "name") or a property chain (for example, `user.address.streetName`). When binding to a property chain, all properties but the last in the chain must refer to `@Bindable` values.

The following example illustrates all three scenarios:

```

@Bindable
public class Address {
    private String line1;
    private String line2;
    private String city;
    private String stateProv;
    private String country;

    // getters and setters
}

@Bindable
public class User {
    private String name;
    private String password;
    private Date dob;
    private Address address;
}

```

```
private List<Role> roles;

// getters and setters
}

@Templated
public class UserWidget {
    @Inject @AutoBound DataBinder<User> user;
    @Inject @Bound TextBox name;
    @Inject @Bound("dob") DatePicker dateOfBirth;
    @Inject @Bound("address.city") TextBox city;
}
```

In `UserWidget` above, the `name` text box is bound to `user.name` using the default name matching; the `dateOfBirth` date picker is bound to `user.dob` using a simple property name mapping; finally, the `city` text box is bound to `user.address.city` using a property chain. Note that the `Address` class is required to be `@Bindable` in this case.

9.5.2. Data Converters

The `@Bound` annotation further allows to specify a converter to use for the binding (see [Specifying Converters](#) for details). This is how a binding specific converter can be specified on a data field:

```
@Inject
@Bound(converter=MyDateConverter.class)
@DataField
private TextBox date;
```

9.5.3. Replacing a model object

The injected model objects in the examples above are always proxies to the actual model since method invocations on these objects need to trigger additional logic for updating the UI. Special care needs to be taken in case a model object should be replaced.

When working with an `@AutoBound DataBinder`, simply calling `setModel()` on the `DataBinder` will be enough to replace the underlying model instance. However, when working with `@Model` the instance cannot be replaced directly. Errai provides a special method level annotation `@ModelSetter` that will allow replacing the model instance. Here's an example:

```
@Dependent
public class CustomerView {
    @Inject @Model
    private Customer customer;
```

```
@Inject @Bound
private TextBox name;

@Bound
private Label id = new Label();

@ModelSetter
public void setModel(TestModel model) {
    this.model = model;
}
}
```

The `@ModelSetter` method is required to have a single parameter. The parameter type needs to correspond to the type of the managed model.

9.6. Bean validation

Java bean validation (JSR 303) provides a declarative programming model for validating entities. More details and examples can be found [here](http://docs.jboss.org/hibernate/validator/4.3/reference/en-US/html_single/) [http://docs.jboss.org/hibernate/validator/4.3/reference/en-US/html_single/]. Errai provides a bean validation module that makes `Validator` instances injectable and work well with Errai's data binding module. The following line needs to be added to the GWT module descriptor to inherit Errai's bean validation module:

Example 9.3. App.gwt.xml

```
<inherits name="org.jboss.errai.validation.Validation" />

<inherits name="org.hibernate.validator.HibernateValidator" />
```

To use Errai's bean validation module, you must add the module, the `javax.validation` API and an implementation such as `hibernate validator` to your classpath. If you are using Maven for your build, add these dependencies:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-validation</artifactId>
  <version>${errai.version}</version>
</dependency>

<dependency>
  <groupId>javax.validation</groupId>
  <artifactId>validation-api</artifactId>
```

```
<scope>provided</scope>
</dependency>

<dependency>
  <groupId>javax.validation</groupId>
  <artifactId>validation-api</artifactId>
  <classifier>sources</classifier>
  <scope>provided</scope>
</dependency>

<dependency>
  <groupId>org.hibernate</groupId>
  <artifactId>hibernate-validator</artifactId>
  <version>4.2.0.Final</version>
  <scope>provided</scope>
</dependency>

<dependency>
  <groupId>org.hibernate</groupId>
  <artifactId>hibernate-validator</artifactId>
  <version>4.2.0.Final</version>
  <scope>provided</scope>
  <classifier>sources</classifier>
</dependency>
```

Now it is as simple as injecting a `Validator` instance into an *Errai IOC* managed bean and calling the `validate` method.

```
@Inject
private Validator validator;
```

```
Set<ConstraintViolation<Customer>> violations = validator.validate(customer);
// display violations
```

9.6.1. Excluding Classes from Validation

By default, Errai scans the entire classpath for classes with constraints. But sometimes it is necessary or desirable to exclude some shared classes from being validated on the client side. This can be done by adding a list of classes and package masks to the `ErraiApp.properties` file like so:

```
# The following blacklists the class some.fully.qualified.ClassName and all
classes in some.package.mask (and subpackages thereof).
errai.validation.blacklist = some.fully.qualified.ClassName \
                             some.package.mask.*
```


Errai UI

One of the primary complaints of GWT to date has been that it is difficult to use "pure HTML" when building and skinning widgets. Inevitably one must turn to Java-based configuration in order to finish the job. Errai, however, strives to remove the need for Java styling. HTML template files are placed in the project source tree, and referenced from custom "Composite components" (Errai UI Widgets) in Java. Since Errai UI depends on Errai IOC and Errai CDI, dependency injection is supported in all custom components. Errai UI provides rapid prototyping and HTML5 templating for GWT.



Figure 10.1. TODO Gliffy image title empty

[<http://get.adobe.com/flashplayer/>]

10.1. Get started

The Errai UI module is directly integrated with [Chapter 9, Data Binding](#) and Errai JPA but can also be used as a standalone project in any GWT client application by simply inheriting the Errai UI GWT module, and ensuring that you have properly using [Errai CDI's @Inject](#) to instantiate your widgets:

10.1.1. App.gwt.xml

```
<inherits name="org.jboss.errai.ui.UI" />
```

10.1.2. pom.xml

The easiest way to get Errai UI on your classpath is to depend on the special `errai-javaee-all` artifact, which brings in most Errai modules:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-javaee-all</artifactId>
  <version>${errai.version}</version>
</dependency>
```

Or if you prefer to manage your project's dependency in a finer-grained way, you can depend on `errai-ui` directly:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-ui</artifactId>
  <version>${errai.version}</version>
</dependency>
```

10.1.3. Working Demo

If you work better by playing with a finished product, you can see a simple client-server project *implemented using Errai UI here* [<https://github.com/errai/summit-demo-2013>].

10.2. Use Errai UI Composite components

Before explaining how to create Errai UI components, it should be noted that these components behave no differently from any other GWT Widget once built. The primary difference is in A) their construction, and B) their instantiation. As with most other features of Errai, dependency injection with CDI is the programming model of choice, so when interacting with components defined using Errai UI, you should always `@Inject` references to your Composite components.

10.2.1. Inject a single instance

```
@EntryPoint
public class Application {
    @Inject
    private ColorComponent comp;

    @PostConstruct
    public void init() {
        comp.setColor("blue");
        RootPanel.get().add(comp);
    }
}
```

10.2.2. Inject multiple instances (for iteration)

```
@EntryPoint
public class Application {
    private String[] colors = new String[]{"Blue", "Yellow", "Red"};

    @Inject
```

```

private Instance<ColorComponent> instance;

@PostConstruct
public void init() {
    for(String color: colors) {
        ColorComponent comp = instance.get();
        comp.setColor(c);
        RootPanel.get().add();
    }
}
}

```

10.3. Create a @Templated Composite component

Custom components in Errai UI are single classes extending from `com.google.gwt.user.client.ui.Composite`, and must be annotated with `@Templated`.

10.3.1. Basic component

```

@Templated
public class LoginForm extends Composite {
    /* looks for LoginForm.html in LoginForm's package */
}

```

10.3.2. Custom template names

With default values, `@Templated` informs Errai UI to look in the current package for a parallel `".html"` template next to the Composite component Class; however, the template name may be overridden by passing a String into the `@Templated` annotation, like so:

```

@Templated("my-template.html")
public class LoginForm extends Composite {
    /* looks for my-template.html in LoginForm's package */
}

```

Fully qualified template paths are also supported, but must begin with a leading `"/`:

```

@Templated("/org/example/my-template.html")
public class LoginForm extends Composite {
    /* looks for my-template.html in package org.example */
}

```

```
}
```

10.4. Create an HTML template

Templates in Errai UI may be designed either as an HTML snippet or as a full HTML document. You can even take an existing HTML page and use it as a template. With either approach, the `id`, `class`, and `data-field` attributes in the template identify elements by name. These elements and their children are used in the Composite component to add behavior, and use additional components to add functionality to the template. There is no limit to how many component classes may share a given HTML template.

We will begin by creating a simple HTML login form to accompany our `@Templated LoginForm` composite component.

```
<form>
  <legend>Log in to your account</legend>

  <label for="username">Username</label>
  <input id="username" type="text" placeholder="Username">

  <label for="password">Password</label>
  <input id="password" type="password" placeholder="Password">

  <button>Log in</button>
  <button>Cancel</button>
</form>
```

10.4.1. Select a template from a larger HTML file

Or as a full HTML document which may be more easily previewed during design without running the application; however, in this case we must also specify the location of our component's root DOM Element using a `"data-field"`, `id`, or `class` attribute matching the value of the `@Templated` annotation. There is no limit to how many component classes may share a given HTML template.

```
@Templated("my-template.html#login-form")
public class LoginForm extends Composite {
    /* Specifies that <... id="login-form"> be used as the root Element of this
    Widget */
}
```

Notice the corresponding HTML `id` attribute in the form Element below (we could have used `data-field` or `class` instead). Note that multiple components may use the same template provided that they specify a corresponding `data-field`, `id`, or `class` attribute. Also note that two or more components may share the same DOM elements; there is no conflict since components each receive a unique copy of the template DOM rooted at the designated element at runtime (or from the root element if a fragment is not specified.)

```

<!DOCTYPE html>
<html lang="en">
<head>
  <title>A full HTML snippet</title>
</head>
<body>
  <div>
    <form id="login-form">
      <legend>Log in to your account</legend>

      <label for="username">Username</label>
      <input id="username" type="text" placeholder="Username">

      <label for="password">Password</label>
      <input id="password" type="password" placeholder="Password">

      <button>Log in</button>
      <button>Cancel</button>
    </form>
  </div>

  <hr>
  <footer id="theme-footer">
    <p>(c) Company 2012</p>
  </footer>
</body>
</html>

```

For example's sake, the component below could also use the same template. All it needs to do is reference the template name, and specify a fragment.

```

@Templated("my-template.html#theme-footer")
public class Footer extends Composite {
  /* Specifies that <... id="theme-footer"> be used as the root Element of
  this Widget */
}

```

10.5. Use other Widgets in a composite component

Now that we have created the `@Templated Composite` component and an HTML template, we can start wiring in functionality and behavior; this is done by annotating fields and methods to replace specific sub-elements of the template DOM with other Widgets. We can even replace portions of the template with other Errai UI Widgets!

10.5.1. Annotate Widgets in the template with `@DataField`

In order to composite Widgets into the template DOM, you annotate fields in your `@Templated Composite` component with `@DataField`, and mark the HTML template Element with a correspondingly named `data-field`, `id`, or `class` attribute. This informs Errai UI which element in the template the Widget should replace. All replacements happen while the `@Templated Composite` component is being constructed; thus, fields annotated with `@DataField` must either be `#{@Inject}`ed or provide their own Widget or Element instances in field initializers.

```
@Templated
public class LoginForm extends Composite {
    // This element must be initialized manually because Element is not @Inject-
    // able*/
    @DataField
    private Element form = DOM.createForm();

    // If not otherwise specified, the name to match in the HTML template defaults
    // to the name of the field; in this case, the name would be "username"
    @Inject
    @DataField
    private TextBox username;

    // The name to reference in the template can also be specified manually
    @Inject
    @DataField("pass")
    private PasswordTextBox password;

    // We can also choose to instantiate our own Widgets. Injection is not required.
    @DataField
    private Button submit = new Button();
}
```



Important

Note: Field, method, and constructor injection are all supported by `@DataField`.

10.5.2. Add corresponding attributes to the HTML template

Each `@DataField` reference in the Java class must match an element in the HTML template. The matching of Java references to HTML elements is performed as follows:

1. A *name* for the Java reference is determined. If the `@DataField` annotation has a value argument, that is used as the reference name. For fields, the default reference name is the field name. Method and constructor parameters have no default name, so they must always specify a value.
2. If there is an element in the HTML template with attribute `data-field=name`, the Java reference will point to this element. If there is more than one such element, the Java reference points to the first.
3. Otherwise, if there is an element in the HTML template with attribute `id=name`, the Java reference will point to this element. If there is more than one such element, the Java reference points to the first.
4. Otherwise, if there is an element in the HTML template with a CSS style class *name*, the Java reference will point to this element. If there is more than one such element, the Java reference points to the first. For elements with more than one CSS style, each style name is considered individually. For example:

```
<div class="eat drink be-merry">
```

matches Java references named `eat`, `drink`, or `be-merry`.

5. If no matching element is found by this point, it is an error.

If more than one Java reference matches the same HTML element in the template, it is an error. For example, given a template containing the element `<div class="eat drink be-merry">`, the following Java code is in error:

```
@Templated
public class ErroneousTemplate extends Composite {
    @Inject @DataField
    private Label eat;

    @Inject @DataField
    private Label drink;
}
```

because both fields `eat` and `drink` refer to the same HTML `div` element.

So now we must ensure there are `data-field`, `id`, or `class` attributes in the right places in our template HTML file. This, combined with the `@DataField` annotation in our Composite component allow Errai UI to determine where and what should be composited when creating component instances.

```
<form id="form">
  <legend>Log in to your account</legend>

  <label for="username">Username</label>
  <input id="username" type="text" placeholder="Username">

  <label for="password">Password</label>
  <input data-field="pass" id="password" type="password" placeholder="Password">

  <button id="submit">Log in</button>
  <button>Cancel</button>
</form>
```

Now, when we run our application, we will be able to interact with these fields in our Widget.

10.6. How HTML templates are merged with Components

Three things are merged or modified when Errai UI creates a new Composite component instance:

1. Element attributes are merged from the template to the component
2. DOM Elements are merged from the component to the template
3. Template element inner text and inner HTML are preserved when the given `@DataField` widget implements `HasText` or `HasHTML`

10.6.1. Example

10.6.1.1. Composite component class:

```
@Templated
public class StyledComponent extends Composite {
  @Inject
  @DataField("field-1")
  private Label div = new Label();

  public StyledComponent() {
```

```

    div.getElement().setAttribute("style", "position: fixed; top: 0; left: 0;");
    this.getElement().setId("outer-id");
  }
}

```

10.6.1.2. Template:

```

<form>
    <span data-
    field="field-1" style="display:inline;"> This element will become a div </span>
</form>

```

This text will be ignored.

10.6.1.3. Output / result:

```

<form id="outer-id">
    <div data-
    field="field-1" style="display:inline;"> This element will become a div </div>
</form>

```

But why does the output look the way it does? Some things happened that may be unsettling at first, but we find that once you understand why these things occur, you'll find the mechanisms extremely powerful.

10.6.2. Element attributes (template wins)

When styling your templates, you should keep in mind that all attributes defined in the template file will take precedence over any preset attributes in your Widgets. This "attribute merge" occurs only when the components are instantiated; subsequent changes to any attributes after Widget construction will function normally. In the example we defined a Composite component that applied several styles to a child Widget in its constructor, but we can see from the output that the styles from the template have overridden them. If styles must be applied in Java, instead of the template, `@PostConstruct` or other methods should be favored over constructors to apply styles to fully-constructed Composite components.

10.6.3. DOM Elements (component field wins)

Element composition, however, functions inversely from attribute merging, and the `` defined in our template was actually replaced by the `<div>` Label in our Composite component field. This does not, however, change the behavior of the attribute merge - the new `<div>` was still be

rendered inline, because we have specified this style in our template, and the template always wins in competition with attributes set programatically before composition occurs. In short, whatever is inside the `@DataField` in your class will replace the children of the corresponding element in your template.

10.6.4. Inner text and inner HTML (preserved when component implements `HasText` or `HasHTML`)

Additionally, because `Label` implements both `HasText` and `HasHTML` (only one is required,) the contents of this ` "field-1"` Element in the template were preserved; however, this would not have been the case if the `@DataField` specified for the element did not implement `HasText` or `HasHTML`. In short, if you wish to preserve text or HTML contents of an element in your template, you can do one of two things: do not composite that Element with a `@DataField` reference, or ensure that the Widget being composited implements `HasText` or `HasHTML`.

10.7. Event handlers

Dealing with User and DOM Events is a reality in rich web development, and Errai UI provides several approaches for dealing with all types of browser events using its "quick handler" functionality. It is possible to handle:

1. GWT events on Widgets
2. GWT events on DOM Elements
3. Native DOM events on Elements



Important

It is not possible to handle Native DOM events on Widgets because GWT overrides native event handlers when Widgets are added to the DOM. You must programatically configure such handlers after the Widget has been added to the DOM.

10.7.1. Concepts

Each of the three scenarios mentioned above use the same basic programming model for event handling: Errai UI wires methods annotated with `@EventHandler("my-data-field")` (*event handler methods*) to handle events on the corresponding `@DataField("my-data-field")` in the same component. Event handler methods annotated with a bare `@EventHandler` annotation (no annotation parameter) are wired to receive events on the `@Templated` component itself.

10.7.2. GWT events on Widgets

Probably the simplest and most common use-case, this approach handles GWT Event classes for Widgets that explicitly handle the given event type. If a Widget does not handle the Event type

given in the `@EventHandler` method's signature, the application will fail to compile and appropriate errors will be displayed.

```
@Templated
public class WidgetHandlerComponent extends Composite {

    @Inject
    @DataField("b1")
    private Button button;

    @EventHandler("b1")
    public void doSomethingC1(ClickEvent e) {
        // do something
    }
}
```

10.7.3. GWT events on DOM Elements

Errai UI also makes it possible to handle GWT events on native Elements which are specified as a `@DataField` in the component class. This is useful when a full GWT Widget is not available for a given Element, or for GWT events that might not normally be available on a given Element type. This could occur, for instance, when clicking on a `<div>`, which would normally not have the ability to receive the GWT `ClickEvent`, and would otherwise require creating a custom DIV Widget to handle such an event.

```
@Templated
public class ElementHandlerComponent extends Composite {

    @DataField("div-1")
    private DivElement button = DOM.createDiv();

    @EventHandler("div-1")
    public void doSomethingC1(ClickEvent e) {
        // do something
    }
}
```

10.7.4. Native DOM events on Elements

The last approach is handles the case where native DOM events must be handled, but no such GWT event handler exists for the given event type. Alternatively, it can also be used for situations where Elements in the template should receive events, but no handle to the Element

the component class is necessary (aside from the event handling itself.) Native DOM events do not require a corresponding `@DataField` be configured in the class; only the HTML `data-field`, `id`, or `class` template attribute is required.

```
<div>
  <a id="link" href="/page">this is a hyperlink</a>
  <div data-field="div"> Some content </div>
</div>
```

The `@SinkNative` annotation specifies (as a bit mask) which native events the method should handle; this sink behaves the same in Errai UI as it would with `DOM.sinkEvents(Element e, int bits)`. Note that a `@DataField` reference in the component class is optional.



Important

Only one `@EventHandler` may be specified for a given template element when `@SinkNative` is used to handle native DOM events.

```
@Templated
public class QuickHandlerComponent extends Composite {

  @DataField
  private AnchorElement link = DOM.createAnchor().cast();

  @EventHandler("link")
  @SinkNative(Event.ONCLICK | Event.ONMOUSEOVER)
  public void doSomething(Event e) {
    // do something
  }

  @EventHandler("div")
  @SinkNative(Event.ONMOUSEOVER)
  public void doSomethingElse(Event e) {
    // do something else
  }
}
```

10.8. Data Binding

A recurring implementation task in rich web development is writing event handler code for updating model objects to reflect input field changes in the user interface. The requirement to update user interface fields in response to changed model values is just as common. These tasks require a significant amount of boilerplate code which can be alleviated by Errai. Errai's [data binding module](#) provides the ability to bind model objects to user interface fields, so they will automatically be kept in sync. While the module can be used on its own, it can cut even more boilerplate when used together with Errai UI.

In the following example, all `@DataFields` annotated with `@Bound` have their contents bound to properties of the data model (a `User` object). The model object is injected and annotated with `@Model`, which indicates automatic binding should be carried out. Alternatively, the model object could be provided by an injected `DataBinder` instance annotated with `@AutoBound`, see [Declarative Binding](#) for details.

```
@Templated
public class LoginForm extends Composite {

    @Inject
    @Model
    private User user;

    @Inject
    @Bound
    @DataField
    private TextBox name;

    @Inject
    @Bound
    @DataField
    private PasswordTextBox password;

    @DataField
    private Button submit = new Button();
}
```

Now the user object and the `username` and `password` fields in the UI are automatically kept in sync. No event handling code needs to be written to update the user object in response to input field changes and no code needs to be written to update the UI fields when the model object changes. So, with the above annotations in place, it will always be true that `user.getUsername().equals(username.getText())` and `user.getPassword().equals(password.getText())`.

10.8.1. Default, Simple, and Chained Property Bindings

By default, bindings are determined by matching field names to property names on the model object. In the example above, the field `name` was automatically bound to the JavaBeans property name of the model (`user` object). If the field name does not match the model property name, you can use the `property` attribute of the `@Bound` annotation to specify the name of the property. The property can be a simple name (for example, "name") or a property chain (for example, `user.address.streetName`). When binding to a property chain, all properties but the last in the chain must refer to `@Bindable` values.

The following example illustrates all three scenarios:

```
@Bindable
public class Address {
    private String line1;
    private String line2;
    private String city;
    private String stateProv;
    private String country;

    // getters and setters
}

@Bindable
public class User {
    private String name;
    private String password;
    private Date dob;
    private Address address;
    private List<Role> roles;

    // getters and setters
}

@Templated
public class UserWidget extends Composite {
    @Inject @AutoBound DataBinder<User> user;
    @Inject @Bound TextBox name;
    @Inject @Bound("dob") DatePicker dateOfBirth;
    @Inject @Bound("address.city") TextBox city;
}
```

In `UserWidget` above, the `name` text box is bound to `user.name` using the default name matching; the `dateOfBirth` date picker is bound to `user.dob` using a simple property name mapping; finally, the `city` text box is bound to `user.address.city` using a property chain. Note that the `Address` class is required to be `@Bindable` in this case.

10.8.2. Binding of Lists

Often you will need to bind a list of model objects so that every object in the list is bound to a corresponding widget. This task can be accomplished using Errai UI's `ListWidget` class. Here's an example of binding a list of users using the `UserWidget` class from the previous example. First, we need to enhance `UserWidget` to implement `HasModel`.

```
@Templated
public class UserWidget extends Composite implements HasModel<User> {
    @Inject @AutoBound DataBinder<User> userBinder;
    @Inject @Bound TextBox name;
    @Inject @Bound("dob") DatePicker dateOfBirth;
    @Inject @Bound("address.city") TextBox city;

    public User getModel() {
        userBinder.getModel();
    }

    public void setModel(User user) {
        userBinder.setModel(user);
    }
}
```

Now we can use `UserWidget` to display items in a list.

```
@Templated
public class MyComposite extends Composite {

    @Inject @DataField ListWidget<User, UserWidget> userListWidget;

    @PostConstruct
    public void init() {
        List<User> users = .....
        userListWidget.setItems(users);
    }
}
```

Calling `setItems` on the `userListWidget` causes an instance of `UserWidget` to be displayed for each user in the list. The `UserWidget` is then bound to the corresponding user object. By default, the widgets are arranged in a vertical panel. However, `ListWidget` can also be subclassed to provide alternative behaviour. In the following example, we use a horizontal panel to display the widgets.

```

public class UserListWidget extends ListWidget<User, UserWidget> {

    public UserList() {
        super(new HorizontalPanel());
    }

    @PostConstruct
    public void init() {
        List<User> users = .....
        setItems(users);
    }

    @Override
    public Class<UserWidget> getItemWidgetType() {
        return UserWidget.class;
    }
}

```

10.8.2.1. Binding lists with @Bound

An instance of `ListWidget` can also participate in automatic bindings using `@Bound`. In this case, `setItems` never needs to be called manually. The bound list property and displayed items will automatically be kept in sync. In the example below a list of user roles is bound to a `ListWidget` that displays and manages a `RoleWidget` for each role in the list. Every change to the list returned by `user.getRoles()` will now trigger a corresponding update in the UI.

```

@Templated
public class UserDetailView extends Composite {

    @Inject
    @Bound
    @DataField
    private TextBox name;

    @Inject
    @Bound
    @DataField
    private PasswordTextBox password;

    @Inject
    @Bound
    @DataField
    private ListWidget<Role, RoleWidget> roles;
}

```

```

@DataField
private Button submit = new Button();

@Inject @Model
private User user;
}

```

10.8.3. Data Converters

The `@Bound` annotation further allows to specify a converter to use for the binding (see [Specifying Converters](#) for details). This is how a binding specific converter can be specified on a data field:

```

@Inject
@Bound(converter=MyDateConverter.class)
@DataField
private TextBox date;

```

Errai's `DataBinder` also allows to register `PropertyChangeHandlers` for the cases where keeping the model and UI in sync is not enough and additional logic needs to be executed (see [Property Change Handlers](#) for details).

10.9. Nest Composite components

Using Composite components to build up a hierarchy of widgets functions exactly the same as when building hierarchies of GWT widgets. The only distinction might be that with Errai UI, `@Inject` is preferred to manual instantiation.

```

@Templated
public class ComponentOne extends Composite {

    @Inject
    @DataField("other-comp")
    private ComponentTwo two;
}

```

10.10. Extend Composite components

Templating would not be complete without the ability to inherit from parent templates, and Errai UI also makes this possible using simple Java inheritance. The only additional requirement is that Composite components extending from a parent Composite component must also be annotated with `@Templated`, and the path to the template file must also be specified in the child component's

annotation. Child components may specify `@DataField` references that were omitted in the parent class, and they may also override `@DataField` references (by using the same `data-field` name) that were already specified in the parent component.

10.10.1. Template

Extension templating is particularly useful for creating reusable page layouts with some shared content (navigation menus, side-bars, footers, etc...,) where certain sections will be filled with unique content for each page that extends from the base template; this is commonly seen when combined with the MVP design pattern traditionally used in GWT applications.

```
<div class="container">
  <div id="header"> Default header </div>
  <div id="content"> Default content </div>
  <div id="footer"> Default footer </div>
</div>
```

10.10.2. Parent component

This component provides the common features of our page layout, including header and footer, but does not specify any content. The missing `@DataField` "content" will be provided by the individual page components extending from this parent component.

```
@Templated
public class PageLayout extends Composite {

    @Inject
    @DataField
    private HeaderComponent header;

    @Inject
    @DataField
    private FooterComponent footer;

    @PostConstruct
    public final void init() {
        // do some setup
    }
}
```

10.10.3. Child component

We are free to fill in the missing "content" `@DataField` with a `Widget` of our choosing. Note that it is not required to fill in all omitted `@DataField` references.

```
@Templated("PageLayout.html")
public class LoginLayout extends PageLayout {

    @Inject
    @DataField
    private LoginForm content;

}
```

We could also have chosen to override one or more `@DataField` references defined in the parent component, simply by specifying a `@DataField` with the same name in the child component, as is done with the "footer" data field below.

```
@Templated("PageLayout.html")
public class LoginLayout extends PageLayout {

    @Inject
    @DataField
    private LoginForm content;

    /* Override footer defined in PageLayout */
    @Inject
    @DataField
    private CustomFooter footer;

}
```

10.11. Stylesheet binding

When developing moderately-complex web applications with Errai, you may find yourself needing to do quite a bit of programmatic style changes. A common case being: showing or enabling controls only if a user has the necessary permissions to use them. One part of the problem is securing those features from being used, and the other part – which is an important usability consideration – is communicating that state to the user.

Let's start with the example case I just described. We have a control that we only want to be visible if the user is an admin. So the first thing we do is create a style binding annotation.

```
@StyleBinding
@Retention(RetentionPolicy.RUNTIME)
public @interface Admin {
}
```

This defines `Admin` as a stylebinding now we can use it like this:

```
@EntryPoint
@Templated
public class HelloWorldForm extends Composite {
    @Inject @Admin @DataField Button deleteButton;
    @Inject SessionManager sessionManager;

    @EventHandler("deleteButton")
    private void handleSendClick(ClickEvent event) {
        // do some deleting!
    }

    @Admin
    private void applyAdminStyling(Style style) {
        if (!sessionManager.isAdmin()) {
            style.setVisibility(Style.Visibility.HIDDEN);
        }
    }
}
```

Now before the form is shown to the user the `applyAdminStyling` method will be executed where the `sessionManager` is queried to see if the user is an admin if not the delete button that is also annotated with `@Admin` will be hidden from the view.

In addition when using this in conjunction with Errai Databinding. Any Errai UI component which uses `@AutoBound`, will get live updating of the style rules for free, anytime the model changes. Allowing dynamic styling based on user input and other state changes.

10.12. Internationalization (i18n)

User interfaces often need to be available in multiple languages. To get started with Errai's internationalization support, simply put the `@Bundle("bundle.json")` annotation on your entry point and add an empty `bundle.json` file to your classpath (e.g. to `src/main/java` or `src/main/resources`). Of course, you can name it differently.

Errai will scan your HTML templates and process all text elements to generate key/value pairs for translation. It will generate a file called `errai-bundle-all.json` and put it in your `.errai` directory. You can copy this generated file and use it as a starting point for your custom translation bundles. If the text value is longer than 128 characters the key will get cut off and a hash appended at the end.

The translation bundle files use the same naming scheme as Java (e.g. `bundle_nl_BE.json` for Belgian Dutch and `bundle_nl.json` for plain Dutch). Errai will also generate a file called `errai-bundle-missing.json` in the `.errai` folder containing all template values for which no translations have been defined. You can copy the key/value pairs out of this file to create our own translations:

```
{
  "StoresPage.Stores!" : "Stores!",
  "WelcomePage.As_you_move_toward_a_more_and_more_declarative_style,_you_allow_the_compiler_and_the_framework_to_catch_more_mistakes_up_front._Broken_links?_A_thing_of_the_past!" : "As you move toward a more and more declarative style, you allow the compiler and the framework to catch more mistakes up front. Broken links? A thing of the past!"
}
```

If you want to use your own keys instead of these generated ones you can specify them in your templates using the `data-i18n-key` attribute:

```
<html>
<body>
  <div id="content">
    <p data-i18n-key="welcome">Welcome to errai-ui i18n.</p>
  </div>
  ...
```

By adding this attribute in the template you can translate it with the following:

```
{
  "Widget.welcome" : "Willkommen bei Errai-ui i18n."
}
```

Because your templates are designer templates and can contain some mock data that doesn't need to be translated, Errai has the ability to indicate that with an attribute `data-role=dummy` :

```
<div id=navbar data-role=dummy>
  <div class="navbar navbar-fixed-top">
    <div class=navbar-inner>
      <div class=container>
        <span class=brand>Example Navbar</span>
        <ul class=nav>
          <li><a>Item</a>
          <li><a>Item</a>
        </ul>
      </div>
    </div>
  </div>
</div>
```

Here the template fills out a navbar with dummy elements, useful for creating a design, adding `data-role=dummy` will not only exclude it from being translated it will also strip the children nodes from the template that will be used by the application.

When you have setup a translation of your application Errai will look at the browser locale and select the locale, if it's available, if not it will use the default (`bundle.json`). If the users of your application need to be able to switch the language manually, Errai offers a pre build component you can easily add to your page: `LocaleListBox` will render a Listbox with all available languages. If you want more control of what this language selector looks like there is also a `LocaleSelector` that you can use to query and select the locale for example:

```
@Templated
public class NavBar extends Composite {

    @Inject
    private LocaleSelector selector;

    @Inject @DataField @OrderedList
    ListWidget<Locale, LanguageItem> language;

    @AfterInitialization
    public void buildLangaugeList() {
        language.setItems(new ArrayList<Locale>(selector.getSupportedLocales()));
    }

    ...
    // in LanguageItem we add a click handler on a link

    @Inject
    Navigation navigation;

    @Inject
```

```

private LocaleSelector selector;

link.addClickHandler(new ClickHandler() {
    @Override
    public void onClick(ClickEvent event) {
        selector.select(model.getLocale());
        navigation.goTo(navigation.getCurrentPage().name());
    }
});

```

10.13. Extended styling with LESS

Errai also supports [LESS](http://lesscss.org) [http://lesscss.org] stylesheets. To get started using these you'll have to create a LESS stylesheet and place it on the classpath of your project. Errai will convert the LESS stylesheet to css perform optimisations on it and ensure that is get injected into the pages of your application. It will also obfuscate the class selectors and replace the use of those in your templates. To be able to use the selectors in your code you can use:

```

public class MyComponent extends Component {
    # @Inject
    # private LessStyle lessStyle;

    ...

    # @PostCreate
    # private void init() {
    # # # #textBox.setStyleName(lessStyle.get("input"));
    # #}
    }

```

Finally it will also add any deferred binding properties to the top of your LESS stylesheet, so for example you could use the user.agent in LESS like this:

```

.mixin (@a) when (@a = "safari") {
    background-color: black;
}

.mixin (@a) when (@a = "gecko1_8") {
    background-color: white;
}

.class1 { .mixin(@user_agent) }

```

Because a dot is not allowed in LESS variables it's replaced with an underscore, so in the example above `class1` will have a black background on Safari and Chrome and white on Firefox. On the top of this LESS stylesheet `@user_agent: "safari"` will get generated.

Errai UI Navigation

Starting in version 2.1, Errai offers a system for creating applications that have multiple bookmarkable pages. This navigation system has the following features:

- Declarative, statically-analyzable configuration of pages and links
 - Compile time referential safety (i.e. “no broken links”)
 - Generates a storyboard of the application’s navigation flow at compile time
- Decentralized configuration
 - Create a new page by creating a new annotated class. No need to edit a second file.
 - Make navigational changes in the natural place in the code.
- Integrates cleanly with Errai UI templates, but also works well with other view technologies.
- Builds on Errai IoC & CDI

11.1. Getting Started

11.1.1. Compile-time dependency

To use Errai UI Navigation, you must include it on the compile-time classpath. If you are using Maven for your build, add these dependencies:

```
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-navigation</artifactId>
  <version>${errai.version}</version>
  <scope>provided</scope>
</dependency>
<dependency>
  <groupId>org.jboss.errai</groupId>
  <artifactId>errai-cdi-client</artifactId>
  <version>${errai.version}</version>
  <scope>provided</scope>
</dependency>
```

If you are not using Maven for dependency management, add `errai-navigation-version.jar` to the compile-time classpath of a project that's already set up for Errai UI templating.

11.1.2. GWT Module Descriptor

Once you have Errai UI Navigation on your classpath, ensure your application inherits the GWT module as well. Add this line to your application's `*.gwt.xml` file:

```
<inherits name="org.jboss.errai.ui.nav.Navigation" />
```

11.2. How it Works

Errai Navigation has three main parts: the `@Page` annotation marks any widget as a page; the `TransitionTo<P>` interface is an injectable type that provides a link to another page; and the `Navigation` singleton offers control over the navigation system as a whole.

The `Navigation` singleton owns a GWT Panel called the *navigation panel*. This panel always contains a widget corresponding to the the fragment ID (the part after the `#` symbol) in the browser's location bar. Whenever the fragment ID changes for any reason (for example, because the user pressed the back button, navigated to a bookmarked URL, or simply typed a fragment ID by hand), the widget in the navigation panel is replaced by the widget associated with that fragment ID. Likewise, when the application asks the navigation system to follow a link, the fragment ID in the browser's location bar is updated to reflect the new current page.

11.2.1. Declaring a Page

To declare a page, annotate any subclass of `Widget` with the `@Page` annotation:

```
@Page
public class ItemListPage extends Composite {
    // Anything goes...
}
```

By default, the name of a page is the simple name of the class that declares it. In the above example, the `ItemListPage` will fill the navigation panel whenever the browser's location bar ends with `#ItemListPage`. If you prefer a different page name, use the `@Page` annotation's `path` attribute:

```
@Page(path="items")
public class ItemListPage extends Composite {
    // Anything goes...
}
```



Navigation and Errai UI

Any widget can be a page. This includes Errai UI `@Templated` classes! Simply annotate any Errai UI templated class with `@Page`, and it will become a page that can be navigated to.

11.2.1.1. The Starting Page

Each application must have exactly one *starting page*. This requirement is enforced at compile time. The starting page is displayed when there is no fragment ID present in the browser's location bar.

Use the `startingPage` attribute to declare the starting page, like this:

```
@Page(startingPage=true)
public class WelcomePage extends Composite {
    // Anything goes...
}
```

Pages are looked up as CDI beans, so you can inject other CDI beans into fields or a constructor. Pages can also have `@PostConstruct` and `@PreDestroy` CDI methods.

11.2.1.2. Page Lifecycle

There are four annotations related to page lifecycle events: `@PageShowing`, `@PageShown`, `@PageHiding`, and `@PageHidden`. These annotations designate methods so a page widget can be notified when it is displayed or hidden:

```
@Page
public class ItemPage extends VerticalPanel {

    @PageShowing
    private void preparePage() {
    }

    @PageHiding
    private void unpreparePage() {
    }

    // Anything goes...
}
```

Page Lifecycle:

1. The fragment identifier in the URL changes
2. The `@PageHiding` method on the current (about-to-be-navigated-away-from) page is invoked
3. The current page is removed from the browser's DOM
4. The `@PageHidden` method on the just-removed page is invoked
5. The navigation system looks up the corresponding `@Page` bean in the client-side bean manager (we'll call this bean "the new page")
6. The navigation system writes to all `@PageState` fields in the new page bean (more on this in the next section)
7. The `@PageShowing` method of the new page is invoked
8. The new page widget is added to the DOM (as a direct child of the navigation content panel)
9. The `@PageShown` method of the new page is invoked.

The `@PageShowing` and `@PageShown` methods are permitted one optional parameter of type `HistoryToken` ---more on this in the next section.

The lifespan of a `Page` instance is governed by CDI scope: Dependent and implicit-scoped page beans are instantiated each time the user navigates to them, whereas `Singleton` and `ApplicationScoped` beans are created only once over the lifetime of the application. If a particular page is slow to appear because its UI takes a lot of effort to build, try marking it as a singleton.

11.2.1.3. Page State Parameters

A page widget will often represent a view on an instance of a class of things. For example, there might be an `ItemPage` that displays a particular item available at a store. In cases like this, it's important that the bookmarkable navigation URL includes not only the name of the page but also an identifier for the particular item being displayed.

This is where page state parameters come in. Consider the following page widget:

```
@Page
public class ItemPage extends VerticalPanel {

    @PageState
    private int itemId;

    // Anything goes...
}
```

This page would be reachable at a URL like `http://www.company.com/store/#ItemPage;itemId=4`. Before the page was displayed, the Errai UI Navigation framework would write the `int` value 4 into the `itemId` field.

There are three ways to pass state information to a page: by passing a `Multimap` to `TransitionTo.go()`; by passing a `Multimap` to `Navigation.goTo()`, or by including the state information in the fragment identifier of a hyperlink as illustrated in the previous paragraph (use the `HistoryToken` class to construct such a fragment ID properly.)

A page widget can have any number of `@PageState` fields. The fields can be of any primitive or boxed primitive type (except `char` or `Character`), `String`, or a `Collection`, `List`, or `Set` of the allowable scalar types. Nested collections are not supported.

`@PageState` fields can be private, protected, default access, or public. They are always updated by direct field access; never via a setter method. The updates occur just before the `@PageShowing` method is invoked.

In addition to receiving page state information via direct writes to `@PageState` fields, you can also receive the whole `Multimap` in the `@PageShowing` and `@PageShown` methods through a parameter of type `HistoryToken`. Whether or not a lifecycle method has such a parameter, the `@PageState` fields will still be written as usual.

Page state values are represented in the URL much like HTML form parameters: as key=value pairs separated by the ampersand (&) character. Multi-valued page state fields are represented by repeated occurrences of the same key. If a key corresponding to a `@PageState` field is absent from the state information passed to the page, the framework writes a default value: `null` for scalar Object fields, the JVM default (0 or false) for primitives, and an empty collection for collection-valued fields. To construct and parse state tokens programmatically, use the `HistoryToken` class.

11.2.2. Declaring a Link with TransitionAnchor

The easiest way to declare a link between pages is to inject an instance of `TransitionAnchor<P>`, where `P` is the class of the target page.

Here is an example declaring an anchor link from the templated welcome page to the item list page. The first code sample would go in `WelcomePage.java` while the second would go in the `WelcomePage.html`, the associated html template.

```
@Page(startingPage=true)
@Templated
public class WelcomePage extends Composite {

    @Inject @DataField TransitionAnchor<ItemListPage> itemLink;

}
```

```
<div>
  <a data-field="itemLink">Go to Item List Page</a>
</div>
```

You can inject any number of links into a page. The only restriction is that the target of the link must be a Widget type that is annotated with `@Page`. When the user clicks the link Errai will transition to the item list page.

11.2.3. Declaring a Manual Link

Sometimes it is necessary to manually transition between pages (such as in response to an event being fired). To declare a manual link from one page to another, inject an instance of `TransitionTo<P>`, where `P` is the class of the target page.

This code declares a manual transition from the welcome page to the item list page:

```
@Page(startingPage=true)
public class WelcomePage extends Composite {

    @Inject TransitionTo<ItemListPage> startButtonClicked;

}
```

You do not need to implement the `TransitionTo` interface yourself; the framework creates the appropriate instance for you.

As with `TransitionAnchor`, the only restriction is that the target of the link must be a Widget type that is annotated with `@Page`.

11.2.4. Following a Manual Link

To follow a manual link, simply call the `go()` method on an injected `TransitionTo` object. For example:

```
@Page(startingPage=true)
public class WelcomePage extends Composite {

    @Inject TransitionTo<ItemListPage> startButtonClicked;

    public void onStartButtonPressed(ClickEvent e) {
        startButtonClicked.go();
    }
}
```

```
}
}
```

11.2.5. Installing the Navigation Panel into the User Interface

Beginning in version 2.4, Errai will automatically attach the Navigation Panel to the Root Panel, but it is possible to override this behaviour by simply adding the Navigation Panel to another component manually. The best time to do this is during application startup, for example in the `@PostConstruct` method of your `@EntryPoint` class. By using the default behaviour you can allow Errai Navigation to control the full contents of the page, or you can opt to keep some parts of the page (headers, footers, and sidebars, for example) away from Errai Navigation by choosing an alternate location for the Navigation Panel.

The following example reserves space for header and footer content that is not affected by the navigation system:

```
@EntryPoint
public class Bootstrap {

    @Inject
    private Navigation navigation;

    @PostConstruct
    public void clientMain() {
        VerticalPanel vp = new VerticalPanel();
        vp.add(new HeaderWidget());
        vp.add(navigation.getContentPanel());
        vp.add(new FooterWidget());

        RootPanel.get().add(vp);
    }
}
```

This last example demonstrates a simple approach to defining the page structure with an Errai UI template. The final product is identical to the above example, but in this case the overall page structure is declared in an HTML template rather than being defined programmatically in procedural logic:

```
@Templated
@EntryPoint
public class OverallPageStructure extends Composite {

    @Inject
```

```
private Navigation navigation;

@Inject @DataField
private HeaderWidget header;

@Inject @DataField
private SimplePanel content;

@Inject @DataField
private FooterWidget footer;

@PostConstruct
public void clientMain() {

    // give over the contents of this.content to the navigation panel
    content.add(navigation.getContentPanel());

    // add this whole templated widget to the root panel
    RootPanel.get().add(this);
}
}
```

11.2.6. Overriding the default Navigating Panel type

By default Errai uses `com.google.gwt.user.client.ui.SimplePanel` as a container for navigation panel. Sometimes this is not sufficient and users would prefer using another implementation. For example a `com.google.gwt.user.client.ui.SimpleLayoutPanel` that manages child size state.

To provide your own implementation of the navigation panel you must implement `org.jboss.errai.ui.nav.client.local.NavigatingContainer`. For example:

```
public class NavigatingPanel implements NavigatingContainer {

    # SimplePanel panel = new SimpleLayoutPanel();

    # public void clear() {
    # # this.panel.clear();
    # }

    # public Widget asWidget() {
    # # return panel.asWidget();
    # }

    # public Widget getWidget() {
```

```

# # return panel.getWidget();
# }

# public void setWidget(Widget childWidget) {
# # panel.add(childWidget);
# }

# public void setWidget(IsWidget childWidget) {
# # panel.add(childWidget);
# }

}

```

Then in your GWT module descriptor you need to override the default navigation panel (`org.jboss.errai.ui.nav.client.local.NavigatingContainer`) by adding:

```

<replace-with class="com.company.application.client.NavigatingPanel">
#                                     <when-type-
is class="org.jboss.errai.ui.nav.client.local.NavigatingContainer"/>
</replace-with>

```

11.2.7. Viewing the Generated Navigation Graph

Because the pages and links in an Errai Navigation application are declared structurally, the framework gets a complete picture of the app's navigation structure at compile time. This knowledge is saved out during compilation (and at page reload when in Dev Mode) to the file `.errai/navgraph.gv`. You can view the navigation graph using any tool that understands the GraphViz (also known as DOT) file format.

One popular open source tool that can display GraphViz/DOT files is [GraphViz](http://www.graphviz.org/) [http://www.graphviz.org/]. Free downloads are available for all major operating systems.

When rendered, a navigation graph looks like this:

Figure 11.1. TODO InformalFigure image title empty

In the rendered graph, the pages are nodes (text surrounded by an ellipse). The starting page is drawn with a heavier stroke. The links are drawn as arrows from one page to another. The labels on these arrows come from the Java field names the `TransitionTo` objects were injected into.

Errai Cordova (Mobile Support)

Starting with version 2.4.0, Errai now supports mobile development. One of the modules that makes this feasible is the Cordova module. It offers a way to integrate with native hardware in an Errai way.

12.1. Get started

Add the following to your application's .gwt.xml module file:

12.1.1. App.gwt.xml

```
<inherits name="org.jboss.errai.ui.Cordova"/>
```

12.2. Integrate with native hardware

When the Cordova module is included you can integrate with native hardware by injecting the native components into your code:

```
@Templated("#main")
public class KitchenSinkClient extends Composite {
    @Inject
    Camera camera;

    @Inject
    @DataField
    Button takePicture;

    @EventHandler("takePicture")
    public void onTakePicktureClicked(ClickEvent event) {
        PictureOptions options = new PictureOptions(25);
        options.setDestinationType(PictureOptions.DESTINATION_TYPE_DATA_URL);
        options.setSourceType(PictureOptions.PICTURE_SOURCE_TYPE_CAMERA);

        camera.getPicture(options, new PictureCallback() {

            @Override
            public void onSuccess(String data) {
                image.setUrl(UriUtils.fromSafeConstant("data:image/jpeg;base64," + data));
            }

            @Override
```

```
public void onFailure(String error) {
    setGeneralErrorMessage("Could not take picture: " + error);
}
});
}
```

The components that are supported come from the [gwt-phonegap](https://code.google.com/p/gwt-phonegap/) [https://code.google.com/p/gwt-phonegap/] project have a look there form more documentation.

Here are the native hardware components you can inject:

- Camera
- Accelerometer
- Contacts
- Capture (Provides access to the audio, image, and video capture capabilities of the device).
- Compass
- Notification ([see documentation on phonegap site](http://docs.phonegap.com/en/edge/cordova_notification_notification.md.html#Notification) [http://docs.phonegap.com/en/edge/cordova_notification_notification.md.html#Notification])
- File create a native file
- Device Get general information about the device.

So to integrate with these things all we have to do is `@Inject` these classes. There are also a couple of CDI events one can observe to be informed about hardware state:

- BackButtonEvent
- BatteryCriticalEvent
- BatteryEvent
- BatteryLowEvent
- BatteryStatusEvent
- EndCallButtonEvent
- MenuButtonEvent
- OffLineEvent

- OnlineEvent
- PauseEvent
- ResumeEvent
- SearchButtonEvent
- StartCallButtonEvent
- VolumeDownButtonEvent
- VolumeUpButtonEvent

Example of how to use these events:

```
private void batteryIsLow(@Observes BatteryLowEvent event) {  
    //mission accomplished. we can stop the infinite loop now.  
}
```

12.3. Maven build

All that is left to do is build this and put it on a actual device. In order to make this as easy as possible we have a maven plugin that will create a native binary that you can install on a device. It will put the html and javascript of you application in a [cordova](http://cordova.apache.org/) application, because by doing so the client is no longer servered by the server the client will need to know how it can reach the server to do that place the following in your gwt.xml:

```
<replace-with class="com.company.application.Config">  
    <when-type-is class="org.jboss.errai.bus.client.framework.Configuration" />  
</replace-with>
```

This class must implement `org.jboss.errai.bus.client.framework.Configuration` and return the url where the server is configured.

```
import org.jboss.errai.bus.client.framework.Configuration;  
  
public class Config implements Configuration {  
    @Override  
    public String getRemoteLocation() {  
        // you probably want to do something environment specify here instead  
of something like this:  
        return "https://grocery-edewit.rhcloud.com/errai-jpa-demo-grocery-list";  
    }  
}
```

```
}  
}
```

Now all that is left is to add the plugin to the pom.xml like so:

```
<build>  
  ...  
  <plugins>  
    <plugin>  
      <groupId>org.jboss.errai</groupId>  
      <artifactId>cordova-maven-plugin</artifactId>  
      <version>${errai.version}</version>  
    </plugin>  
  </plugins>  
</build>
```

Now you can execute a native build with the following maven command:

```
#will build all supported platforms for now only ios and android  
mvn cordova:build-project  
  
#only build android  
mvn cordova:build-project -Dplatform=android  
  
#start the ios emulator with the deployed application  
mvn cordova:emulator -Dplatform=ios
```



Important

For these to work you'll need to have the SDK's installed and on your path! In case of android you will additionally have to have ANDROID_HOME environment variable set.

12.4. AeroGear Wrappers

These wrappers allow your Errai client to talk to an AeroGear server. Also have a look at the [documentation](http://aerogear.org/docs) [http://aerogear.org/docs] of the AeroGear project.

12.4.1. Pipes

Pipes are for getting data from the server. Right now the only implementation is REST it will use Id to construct urls.

```

Pipe<Task> pipe = new PipeFactory().createPipe(Task.class, "tasks");

pipe.save(new Task(123, "new", "2012-01-01"), new AsyncCallback<Task>() {
    @Override
    public void onSuccess(Task result) {
        Window.alert("jipee saved a taks");
    }
    @Override
    public void onFailure(Throwable caught) {
    }
});

```

This will perform a PUT /tasks URL

12.4.2. Stores

Another concept that comes with AeroGear is Stores. Currently there are 2 Store types supported: Memory and SessionLocal. Memory is just a big javascript array to hold your data. Here is how you create and configure a Store:

```

Store<User> store = new DataManager().store(User.class);

store.save(new User(2, "test2"));
Collection<User> collection = store.readAll();

User user = store.read(2);

```

12.4.3. Authentication

Pipes can be authenticated by just adding the authenticator into the Pipe and you are good to go.

```

Authenticator authenticator = new AuthenticationFactory().createAuthenticator("name");
Pipe<Task> pipe = new PipeFactory().createPipe(Task.class, "tasks", authenticator);

authenticator.login(username.getText(), password.getText(), new AsyncCallback<String>() {
    @Override
    public void onSuccess(String result) {
        Window.alert("successful login");
    }
}

@Override
public void onFailure(Throwable caught) {

```

```
        message.setText("Login failed, please try again");  
    }  
});
```

There is also a method called `enroll()` for adding new users.

Logging

Errai now supports using the [slf4j](http://www.slf4j.org/) logging api on the server and client. This gives you the flexibility of choosing your own logging back-end for your server-side code, while still allowing a uniform logging interface that can be used in shared packages.

13.1. What is slf4j?

sl4j is logging abstraction. Using the slf4j api, you can add log statements to your code using a fixed api while maintaining the ability to switch the logging implementation at run-time. For example, the slf4j api can be used with java.util.logging (JUL) as the back-end.

13.2. Client-Side Setup

The client-side slf4j code uses the [GWT Logging](http://www.gwtproject.org/doc/latest/DevGuideLogging.html) as the back-end. Using slf4j in client-side code has two steps:

1. Add the errai-common artifact as a maven dependency to your project
2. Inherit the gwt module `org.jboss.errai.common.Logging`

The GWT logging back-end works analogously to JUL. See the above GWT Logging link for instructions on how to adjust settings such as the log level.

13.3. Server-Side Setup

On the server you are free to use any logging back-end that has slf4j bindings (or to make your own). Just make sure to add dependencies for the slf4j-api artifact and the slf4j binding you choose. **Note:** Some application servers provide their own slf4j bindings (such as JBoss AS), in which case you should add your binding dependency as provided scope.

To learn more about how to setup slf4j for your server-side code, see [their website](http://www.slf4j.org/).

13.4. Example Usage

Here is sample usage of the slf4j code (which with the above setup can be run on the client or server):

Example 13.1. LogExample.java

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
```

```
import javax.inject.Inject;

public class LogExample {

    public void logStuff() {
        // Get a logger for this class
        @Inject Logger logger;

        // Logging going from most to least detailed
        logger.trace("this is extremely specific!");
        logger.debug("this is still pretty specific");
        logger.info("this is an average log message");
        logger.warn("there might be something fishy here...");
        logger.error("uh oh... abandon ship!", new Exception("I am a logged
exception"));
    }
}
```

13.5. Logger Names

By default, the above example will provide a logger with the fully qualified class name of the enclosing class. To inject a logger with an alternate name, use the `NamedLogger` annotation:

Example 13.2. NamedLogExample.java

```
import org.slf4j.Logger;
import javax.inject.Inject;
import org.jboss.errai.common.client.api.NamedLogger;

public class NamedLogExample {

    // Get a logger with the name "Logger!"
    @Inject @NamedLogger("Logger!") logger;

    // Get the root logger
    @Inject @NamedLogger rootLogger;

}
```

Configuration

This section contains information on configuring Errai.

14.1. ErraiApp.properties

ErraiApp.properties acts both as a marker file for JARs that contain Errai-enabled GWT modules, and as a place to put configuration settings for those modules in the rare case that non-default configuration is necessary.

14.1.1. As a Marker File

An `ErraiApp.properties` file must appear at the root of each classpath location that contains an Errai module. The contents of JAR and directory classpath entries that do not contain an `ErraiApp.properties` are effectively invisible to Errai's classpath scanner.

14.1.2. As a Configuration File

ErraiApp.properties is usually left empty, but it can contain configuration settings for both the core of Errai and any of its extensions. Configuration properties defined and used by Errai components have keys that start with "errai.". Third party extensions should each choose their own prefix for keys in ErraiApp.properties.

14.1.2.1. Configuration Merging

In a non-trivial application, there will be several instances of ErraiApp.properties on the classpath (one per JAR file that contains Errai modules, beans, or portable classes).

Before using the configuration information from ErraiApp.properties, Errai reads the contents of every ErraiApp.properties on the classpath. The configuration information in all these files is merged together to form one set of key=value pairs.

If the same key appears in more than one ErraiApp.properties file, only one of the values will be associated with that key. The other values will be ignored. In future versions of Errai, this condition may be made into an error. It's best to avoid specifying the same configuration key in multiple ErraiApp.properties files.

14.1.2.2. Errai Marshalling Configuration

- **errai.marshalling.use_static_marshallers** when set to `false`, Errai will not use the precompiled server-sidemarshallers even if the generated `ServerMarshallingFactoryImpl` class is found on the classpath. This is useful when using Dev Mode in conjunction with an external server such as JBoss AS 7 or EAP 6.

- **errai.marshalling.force_static_marshallers** when set to `true`, Errai will not use dynamic marshallers. If the generated `ServerMarshallingFactoryImpl` cannot be loaded (possibly after an attempt to generate it on-the-fly), the Errai web app will fail to start.

Errai also supports configuring portable types in `ErraiApp.properties` as an alternative to the `@Portable` annotation. See [the Errai Marshalling section on Manual Mapping](#) for details.

14.1.2.3. Errai IoC Configuration

- **errai.ioc.QualifyingMetaDataFactory** specifies the fully-qualified class name of the `QualifyingMetadataFactory` implementation to use with Errai IoC.
- **errai.ioc.enabled.alternatives** specifies a whitespace-separated list of fully-qualified class names for *alternative beans*. See [Section 3.6, “Alternatives and Mocks”](#) for details.
- **errai.ioc.blacklist** specifies a whitespace-separated list of classes that should be hidden from Errai IOC and that will be excluded when generating the bean graph and wiring components. Wildcards are supported to exclude all types underneath a package e.g. `org.jboss.myapp.exclude.*` (all types under the `exclude` package will be hidden from ERRAI IOC).
- **errai.ioc.whitelist** when this property is present all types in your application are hidden from Errai IOC by default. It specifies a whitespace-separated list of classes that should be visible to IOC and that will be included when generating the bean graph and wiring components. Wildcards are supported to include all types underneath a package e.g. `org.jboss.myapp.include.*` (all types under the `include` package will be visible to ERRAI IOC).

14.1.3.

14.2. Messaging (Errai Bus) Configuration

14.2.1. Disabling remote communication

In some cases it might be desirable to prevent the client bus from communicating with the server. One use case for this is when all communication with the server is handled using JAX-RS and the constant long polling requests for message exchange are not needed.

To turn off remote communication in the client bus the following JavaScript variable can be set in the HTML host page:

```
<script type="text/javascript">
  erraiBusRemoteCommunicationEnabled = false;
</script>
```

14.2.2. Configuring an alternative remote remote bus endpoint

By default the remote bus is expected at the GWT web application's context path. In case the remote bus is part of a different web application or deployed on a different server, the following configuration can be used in the HTML host page to configure the remote bus endpoint used on the client.

```
<script type="text/javascript">
  erraiBusApplicationRoot = "/MyRemoteMessageBusEndpoint";
</script>
```

14.2.3. ErraiService.properties

The `ErraiService.properties` file contains basic configuration for the bus itself. Unlike `ErraiApp.properties`, there should be at most one `ErraiService.properties` file on the classpath of a deployed application. If you do not need to set any properties to their non-default values, this file can be omitted from the deployment entirely.

14.2.3.1. Message Dispatching

Dispatchers encapsulate the strategy for taking messages that need to be delivered somewhere and seeing that they are delivered to where they need to go. There are two primary implementations that are provided with Errai, depending on your needs.

14.2.3.1.1. SimpleDispatcher

`SimpleDispatcher` is basic implementation that provides no asynchronous delivery mechanism. Rather, when you configure the Errai to use this implementation, messages are delivered to their endpoints synchronously. The incoming HTTP thread will be held open until the messages are delivered.

While this sounds like it has almost no advantages, especially in terms of scalability. Using the `SimpleDispatcher` can be far preferable when you're developing your application, as any errors and stack traces will be far more easily traced and some cloud services may not permit the use of threads in any case.

14.2.3.1.2. AsyncDispatcher

The `AsyncDispatcher` provides full asynchronous delivery of messages. When this dispatcher is used, HTTP threads will have control immediately returned upon dispatch of the message.

This dispatcher provides far more efficient use of resources in high-load applications, and will significantly decrease memory and thread usage overall.

- **errai.dispatcher.implementation** specifies the dispatcher implementation to be used by the bus. There are two implementations which come with Errai out of the box: the `SimpleDispatcher` and the `AsyncDispatcher`. See `ERRAI:Dispatcher Implementations` for more information about the differences between the two.

14.2.3.2. Threading

- **errai.async_thread_pool_size** specifies the total number of worker threads in the worker pool for handling and delivering messages. Adjusting this value does not have any effect if you are using the `SimpleDispatcher`.
- **errai.async.worker_timeout** specifies the total amount of time (in seconds) that a service is given to finish processing an incoming message before the pool interrupts the thread and returns an error. Adjusting this value has no effect if you are using the `SimpleDispatcher`.

14.2.3.3. Buffering

- **errai.bus.buffer_size** The total size of the transmission buffer, in megabytes. If this attribute is specified along with `errai.bus.buffer_segment_count`, then the segment count is inferred by the calculation `buffer_segment_count / buffer_size`. If `{errai.bus.buffer_segment_count` is also defined, it will be ignored in the presence of this property. Default value: 32.
- **errai.bus.buffer_segment_size** The transmission buffer segment size in bytes. This is the minimum amount of memory each message will consume while stored within the buffer. Default value: 8.
- **errai.bus.buffer_segment_count** The number of segments in absolute terms. If this attribute is specified in the absence of `errai.bus.buffer_size`, the buffer size is inferred by the calculation `buffer_segment_size / buffer_segment_count`.
- **errai.bus.buffer_allocation_mode** Buffer allocation mode. Allowed values are `direct` and `heap`. Direct allocation puts buffer memory outside of the JVM heap, while heap allocation uses buffer memory inside the Java heap. For most situations, heap allocation is preferable. However, if the application is data intensive and requires a substantially large buffer, it is preferable to use a direct buffer. From a throughput perspective, current JVM implementations pay about a 20% performance penalty for direct-allocated memory access. However, your

application may show better scaling characteristics with direct buffers. Benchmarking under real load conditions is the only way to know the optimal setting for your use case and expected load. Default value: `direct`.

14.2.3.4. Security

- **errai.authentication_adapter** specifies the authentication modelAdapter the bus should use for determining whether calls should be serviced based on authentication and security principals.
- **errai.require_authentication_for_all** indicates whether or not the bus should always require the use of authentication for all requests inbound for the bus. If this is turned on, an authentication model adapter must be defined, and any user must be authenticated before the bus will deliver any messages from the client to any service.


14.2.3.5. Clustering

- **errai.bus.enable_clustering** A boolean indicating whether or not Errai's server side bus should attempt to orchestrate with its peers. The orchestration mechanism is dependent on the configured clustering provider (e.g. UDP based multicast discovery in case of the default JGroups provider). The default value is `false`.
- **errai.bus.clustering_provider** The fully qualified class name of the clustering provider implementation. A class that implements `org.jboss.errai.bus.server.cluster.ClusteringProvider`. Currently the only build-in provider is the `org.jboss.errai.bus.server.cluster.jgroups.JGroupsClusteringProvider`.

14.2.3.6. Startup Configuration

- **errai.auto_discover_services** A boolean indicating whether or not the Errai bootstrapper should automatically scan for services. **This property must be set to `true` if and only if Errai CDI is not on the classpath**. The default value is `false`.
- **errai.auto_load_extensions** A boolean indicating whether or not the Errai bootstrapper should automatically scan for extensions. The default value is `true`.

14.2.3.7. Example Configuration



```
##
## Request dispatcher implementation (default is SimpleDispatcher)
##
#errai.dispatcher_implementation=org.jboss.errai.bus.server.SimpleDispatcher
errai.dispatcher_implementation=org.jboss.errai.bus.server.AsyncDispatcher

#
## Worker pool size. This is the number of threads the asynchronous worker pool
  should provide for
processing
## incoming messages. This option is only valid when using the AsyncDispatcher
  implementation.
##
errai.async.thread_pool_size=5

##
## Worker timeout (in seconds). This defines the time that a single asynchronous
  process may run,
before the worker pool
## terminates it and reclaims the thread. This option is only valid when using
  the AsyncDispatcher
  implementation.
##
errai.async.worker.timeout=5

##
## Specify the Authentication/Authorization Adapter to use
##
#errai.authentication_adapter=org.jboss.errai.persistence.server.security.HibernateAuthenticati
#errai.authentication_adapter=org.jboss.errai.bus.server.security.auth.JAASAdapter

##
## This property indicates whether or not authentication is required for all
  communication with the
bus. Set this
## to 'true' if all access to your application should be secure.
##
#errai.require_authentication_for_all=true
```

14.2.4. Servlet Configuration

Errai has several different implementations for HTTP traffic to and from the bus. We provide a universally-compatible blocking implementation that provides fully synchronous communication to/from the server-side bus. Where this introduces scalability problems, we have implemented many webserver-specific implementations that take advantage of the various proprietary APIs to provide true asynchrony.

These included implementations are packaged at: `org.jboss.errai.bus.server.servlet`.



One is Enough!

You should use just one of the options below. Configuring multiple ErraiServlet implementations in the same application will lead to unpredictable behaviour!

Remember that all Errai demos and archetypes are preconfigured with DefaultBlockingServlet as a servlet. You will need to remove this default setup if you choose to use a different ErraiServlet implementation in your app.



Rolling your own security? Beware!

All of the following examples use a wildcard mapping for `*.erraiBus` with no path prefix. This allows Errai Bus to communicate from any point in your application's URI hierarchy, which allows bus communication to work properly no matter where you choose to put your GWT host page.

For example, all of the following are equivalent from Errai's point of view:

- `/in.erraiBus`
- `/foo/bar/in.erraiBus`
- `/long/path/to/get/to.erraiBus`

If you rely on your own security rules or a custom security filter to control access to Errai Bus (rather than the security framework within Errai Bus,) ensure you use the same mapping pattern for that `filter-mapping` or `security-constraint` as you do for the Errai Servlet itself.

14.2.4.1. DefaultBlockingServlet

This ErraiServlet implementation should work in virtually any servlet container that supports Java Servlets 2.0 or higher. It provides purely synchronous request handling. The one scenario where this servlet will not work is in servers that put restrictions on putting threads into sleep states.

The default DefaultBlockingServlet which provides the HTTP-protocol gateway between the server bus and the client buses.

As its name suggests, DefaultBlockingServlet is normally configured as an HTTP Servlet in the `web.xml` file:

```
<servlet>
  <servlet-name>ErraiServlet</servlet-name>
```

```
<servlet-class>org.jboss.errai.bus.server.servlet.DefaultBlockingServlet</servlet-class>
  <load-on-startup>1</load-on-startup>
</servlet>

<servlet-mapping>
  <servlet-name>ErraiServlet</servlet-name>
  <url-pattern>*.erraiBus</url-pattern>
</servlet-mapping>
```

14.2.4.2. DefaultBlockingServlet configured as Filter

Alternatively, the `DefaultBlockingServlet` can be deployed as a Servlet Filter. This may be necessary in cases where an existing filter is configured in the web application, and that filter interferes with the Errai Bus requests. In this case, configuring `DefaultBlockingServlet` to handle `*.erraiBus` requests ahead of other filters in `web.xml` will solve the problem:

```
<filter>
  <filter-name>ErraiServlet</filter-name>
  <filter-class>org.jboss.errai.bus.server.servlet.DefaultBlockingServlet</filter-class>
</filter>

<filter-mapping>
  <filter-name>ErraiServlet</filter-name>
  <url-pattern>*.erraiBus</url-pattern>
</filter-mapping>
```

14.2.4.3. JettyContinuationsServlet

The Jetty implementation leverages Jetty's continuations support, which allows for threadless pausing of port connections. This servlet implementation should work without any special configuration of Jetty.

```
<servlet>
  <servlet-name>ErraiServlet</servlet-name>
  <servlet-class>org.jboss.errai.bus.server.servlet.JettyContinuationsServlet</servlet-class>
  <load-on-startup>1</load-on-startup>
</servlet>
```

```
<servlet-mapping>
  <servlet-name>ErraiServlet</servlet-name>
  <url-pattern>*.erraiBus</url-pattern>
</servlet-mapping>
```

14.2.4.4. StandardAsyncServlet

This implementation leverages asynchronous support in Servlet 3.0 to allow for threadless pausing of port connections. Note that `<async-supported>true</async-supported>` has to be added to the servlet definition in `web.xml`.

```
<servlet>
  <servlet-name>ErraiServlet</servlet-name>
  <servlet-class>org.jboss.errai.bus.server.servlet.StandardAsyncServlet</
servlet-class>
  <load-on-startup>1</load-on-startup>
  <async-supported>true</async-supported>
</servlet>

<servlet-mapping>
  <servlet-name>ErraiServlet</servlet-name>
  <url-pattern>*.erraiBus</url-pattern>
</servlet-mapping>
```


Troubleshooting & FAQ

This section explains the cause of and solution to some common problems that people encounter when building applications with Errai.

Of course, when lots of people trip over the same problem, it's probably because there is a deficiency in the framework! A FAQ list like this is just a band-aid solution. If you have suggestions for permanent fixes to these problems, please get in touch with us: file an issue in our issue tracker, chat with us on IRC, or post a suggestion on our forum.

But for now, on to the FAQ:

15.1. Why does it seem that Errai can't see my class at compile time?

Possible symptoms:

- uncaught exception: `java.lang.RuntimeException: No proxy provider found for type: my.fully.qualified.ServiceName`

Answer: Make sure the [Section 14.1](#), “*ErraiApp.properties*” file is actually making it into your runtime classpath.

One common cause of this problem is a `<resources>` section in `pom.xml` that includes `src/main/java` (to expose `.java` sources to the GWT compiler) that does not also include `src/main/resources` as a resource path. You must include both explicitly:

```
<resources>
  <resource>
    <directory>src/main/java</directory>
  </resource>
  <resource>
    <directory>src/main/resources</directory>
  </resource>
</resources>
```

15.2. Why am I getting "java.lang.ClassFormatError: Illegal method name "<init>\$" in class org/xyz/package/MyClass"?

Answer: This error message means that your project has a (direct or indirect) subclass of `JavaScriptObject` that lacks a protected no-args constructor. All subtypes of `JavaScriptObject`

(also known as *overlay types*) must declare a protected no-args constructor, but the error message could be much clearer. There is an issue filed in the GWT project's bug tracker for improving the error message: [GWT issue 3383](http://code.google.com/p/google-web-toolkit/issues/detail?id=3383) [http://code.google.com/p/google-web-toolkit/issues/detail?id=3383] .

15.3. I'm getting "java.lang.RuntimeException: There are no proxy providers registered yet." in my @PostConstruct method!

Answer: You can't invoke RPC methods via `Caller<?>` or by other means until after the Errai Bus has finished its initial handshake. Try changing your `@PostConstruct` annotation to `@AfterInitialization` . This will cause your method to be invoked later—after the bus handshake has completed.

If this doesn't help, it is also possible that the proxies were never generated in the first place. Check in `.errai/RpcProxyLoaderImpl.java` to see if proxy code exists for the `@Remote` and/or `@Path` interface in question. If not, your `@Remote` interfaces were not present on the GWT compiler's classpath when your application module was compiled. Double-check your GWT compilation classpath: all `@Remote` interfaces must be visible to (in or inherited by) the GWT module that contains the `Caller<?>` types. Pay special attention that your `@Remote` and `@Path` interfaces are not in a package excluded from the GWT module (by default, every subpackage other than `client` and `shared` is invisible to the GWT compiler).

Upgrade Guide

This chapter contains important information for migrating to newer versions of Errai. If you experience any problems, don't hesitate to get in touch with us. See [Chapter 19, Reporting problems](#).

16.1. Upgrading from 1.* to 2.0

The first issues that will arise after replacing the jars or after changing the version numbers in the `pom.xml` are unresolved package imports. This is due to refactorings that became necessary when the project grew. Most of these import problems can be resolved automatically by modern IDEs (Organize Imports). So, this should replace `org.jboss.errai.bus.client.protocols.*` with `org.jboss.errai.common.client.protocols.*` for example.

The following is a list of manual steps that have to be carried out when upgrading:

- `@ExposedEntity` became `@Portable` (`org.jboss.errai.common.client.api.annotations.Portable`). See [Chapter 5, Marshalling](#) for details.
- The `@Conversational` annotation must now target the event objects themselves, not the observer methods of the events. So an *event type* is either conversational or not; you no longer specify that listeners receive arbitrary events in a conversational context. See the [Conversational Events](#) section of the CDI chapter for details.
- Errai CDI projects must now use the `SimpleDispatcher` instead of the `AsyncDispatcher`. This has to be configured in [Section 14.2, "Messaging \(Errai Bus\) Configuration"](#).
- The `bootstrap` listener (configured in `WEB-INF/web.xml`) for Errai CDI has changed (`org.jboss.errai.container.DevModeCDIBootstrap` is now `org.jboss.errai.container.CDIServletStateListener`).
- gwt 2.3.0 or newer must be used and replace older versions.
- mvel2 2.1.Beta8 or newer must be used and replace older versions.
- weld 1.1.5.Final or newer must be used and replace older versions.
- slf4j 1.6.1 or newer must be used and replace older versions.
- This step can be skipped if Maven is used to build the project. If the project is NOT built using Maven, the following jar files have to be added manually to project's build/class path: `errai-common-2.x.jar`, `errai-marshalling-2.x.jar`, `errai-codegen-2.x.jar`, `netty-4.0.0.Alpha1.errai.r1.jar`.

- If the project was built using an early version of an Errai archetype the configuration of the maven-gwt-plugin has to be modified to contain the `<hostedWebapp>path-to-your-standard-webapp-folder</hostedWebapp>`. This is usually either `war` or `src/main/webapp`.

16.2. Upgrading from 2.0.Beta to 2.0.*.Final

The following is a list of manual steps that have to be carried out when upgrading from a 2.0.Beta version to 2.0.CR1 or 2.0.Final:

- Starting with 2.0.CR1 the default for automatic service discovery has been changed in favour of CDI based applications. That means it has to be explicitly turned on for plain bus applications (Errai applications that do not use Errai-CDI). Not doing so will result in `NoSubscribersToDeliverTo` exceptions. The snippet below shows how to activate automatic service discovery:

Example 16.1. web.xml

```
<servlet>
  <servlet-name>ErraiServlet</servlet-name>
  <servlet-class>org.jboss.errai.bus.server.servlet.DefaultBlockingServlet</servlet-class>
  <init-param>
    <param-name>auto-discover-services</param-name>
    <param-value>true</param-value>
  </init-param>
  <load-on-startup>1</load-on-startup>
</servlet>
```

- The `jboss7-support` module was deleted and is no longer needed as a dependency.

16.3. Upgrading from Errai 2.2.x to 2.4 or 3.0

There are some breaking API changes in the update from Errai 2.2.x to Errai 2.4.x and 3.0.x.

Here are the steps you'll need to take to get your project compiling after you update:

- Starting with Errai 2.3.0, GWT 2.5.0 or higher is required.
- Use your IDE to organize imports at the top level. In eclipse, you'd click in the Project Explorer, press Ctrl-A (select all) and then Ctrl-O (Organize Imports). Other IDEs have similar features.
- The `ErrorCallback` interface has been made more general so the same type can be shared between Errai modules. This allows you reuse your own generic error handler class for, eg,

Errai JAX-RS and ErraiBus callbacks. If you want to use a generic error handler throughout your app, change your `ErrorCallback` implementations to `ErrorCallback<?>` and change the first argument type of your `error()` method to `Object`. Otherwise, if you have use-case-specific error callbacks, implement the interfaces `RestErrorCallback` or `BusErrorCallback` as appropriate.

- `IOBeanManager` was replaced by two new types `SyncBeanManager` and `AsyncBeanManager` that need to be used instead. See [Section 3.5, “Client-Side Bean Manager”](#) for details.

Note: Errai 3 is still changing rapidly, so this section is a work in progress. Please add any additional steps you had to take in upgrading your own codebase.

Downloads

The distribution packages can be downloaded from [jboss.org *http://jboss.org/errai/Downloads.html*](http://jboss.org/errai/Downloads.html)

Sources

Errai is currently managed using Github. You can clone our repositories from <http://github.com/errai>.

Reporting problems

If you run into trouble don't hesitate to get in touch with us:

- JIRA Issue Tracking: <https://jira.jboss.org/jira/browse/ERRAI>
- User Forum: <http://community.jboss.org/en/errai?view=discussions>
- Mailing List: <http://jboss.org/errai/MailingLists.html>
- IRC: <irc://irc.freenode.net/errai>

Errai License

Errai is distributed under the terms of the Apache License, Version 2.0. See [the full Apache license text](http://www.apache.org/licenses/LICENSE-2.0) [http://www.apache.org/licenses/LICENSE-2.0] .

Appendix A. Revision History

Revision History

Revision

<>

