

Overlord S-RAMP Guide

1. Introduction to S-RAMP	1
1.1. The S-RAMP Specification	1
1.2. Purpose	1
1.3. Overview	1
1.4. Core Properties	1
1.5. Custom Properties	2
1.6. Classifiers	2
1.7. Relationships	2
2. Getting Started	5
2.1. Prerequisites	5
2.2. Download and Installation	5
2.3. User Management	5
2.4. Startup	6
2.5. Check your Installation	6
3. S-RAMP Data Models	9
3.1. Core Data Model (core)	9
3.2. XML Schema (XSD) Data Model (xsd)	9
3.3. WSDL Data Model (wsdl)	9
3.4. Policy Data Model (policy)	10
3.5. SOA Data Model (soa)	10
3.6. Service Implementation Data Model (serviceImplementation)	11
3.7. Custom/Extension Data Models (ext)	11
3.8. Java Data Model	12
3.9. KIE Data Model (Knowledge is Everything)	12
3.10. SwitchYard Data Model	13
3.11. Teiid Data Model (Teiid)	14
4. Query Language	17
5. Overlord S-RAMP REST API Endpoints	19
5.1. API: Get Service Document	20
5.2. Artifacts	21
5.2.1. API: Publish Artifact	21
5.2.2. API: Update Artifact	27
5.2.3. API: Update Artifact Content	28
5.2.4. API: Get Artifact	28
5.2.5. API: Get Artifact Content	30
5.2.6. API: Delete Artifact	30
5.2.7. Queries	31
5.2.8. Stored Queries	46
5.3. Ontologies	53
5.3.1. API: Add Ontology	53
5.3.2. API: List Ontologies	55
5.3.3. API: Update Ontology	56
5.3.4. API: Get Ontology	58
5.3.5. API: Delete Ontology	60

5.4. Auditing	60
5.4.1. API: Get Artifact Audit History	60
5.4.2. API: Get User Audit History	61
5.4.3. API: Add Artifact Audit Entry	62
5.4.4. API: Get Artifact Audit Entry	63
6. Clients	65
6.1. Java Client	65
6.1.1. Basic Usage	65
6.1.2. Extended Feature: Ontologies	66
6.1.3. Extended Feature: Auditing	67
6.1.4. Extending: Custom Expander	67
6.1.5. Important Notes	67
6.2. EJB Client	68
6.3. JMS Client	69
6.3.1. Installation and Setup	69
6.3.2. Authorization	71
6.3.3. Artifact JMS Events	71
6.3.4. Ontology JMS Events	73
7. Overlord S-RAMP Command Line	77
7.1. Connecting to S-RAMP server	77
7.2. Browsing the S-RAMP repository	77
7.3. Updating artifact MetaData	78
7.3.1. Properties	78
7.3.2. Custom Properties	79
7.3.3. Classifications	80
7.4. Querying the S-RAMP Repository using XPath2 Syntax	80
7.4.1. Stored Queries	83
7.5. Extending the S-RAMP CLI	83
7.6. Running Commands in Batch	83
7.7. Batch File Property Interpolation	84
7.8. Log-to-File	84
8. Overlord S-RAMP Maven Integration	85
8.1. Overview	85
8.2. Deploying to S-RAMP	85
8.3. Adding S-RAMP Artifacts as Dependencies	86
8.4. Maven Integration in the CLI	88
9. The S-RAMP Browser (UI)	89
9.1. Overview	89
10. Overlord S-RAMP Extension Points	91
10.1. ArtifactBuilder	91
10.2. ArtifactTypeDetector	91
11. Overlord S-RAMP Implementation	93
11.1. Overview	93
11.2. Server	93

11.2.1. Description	93
11.2.2. Configuration	93
11.2.3. Security	94
12. S-RAMP Samples	95
13. Overlord S-RAMP Server Configuration	97
13.1. Datasource	97
13.2. WARNINGS	97
Bibliography	99

Chapter 1. Introduction to S-RAMP

1.1. The S-RAMP Specification

S-RAMP stands for SOA Repository Artifact Model and Protocol. [S-RAMP](https://www.oasis-open.org/committees/s-ramp/charter.php) [https://www.oasis-open.org/committees/s-ramp/charter.php] is a new specification worked on by the OASIS Technical Committee.

The SOA Repository Artifact Model and Protocol (S-RAMP) TC defines a common data model for SOA repositories as well as an interaction protocol to facilitate the use of common tooling and sharing of data. The TC will define an ATOM binding which documents the syntax for interaction with a compliant repository for create, read, update, delete and query operations.

— OASIS Charter <https://www.oasis-open.org/committees/s-ramp/charter.php>

The first version of the specification (1.0) should be finalized in the first half of 2013. Two of the developers on the project participated in the Technical Committee.

1.2. Purpose

The OASIS S-RAMP (SOA Repository Artifact Model and Protocol) specification is intended to provide a common data model and protocol for interacting with a repository of (primarily) SOA artifacts. The goal of the specification is to foster interoperability between repository implementations by standardizing on a data model and API.

This guide will discuss both the OASIS standard and the Overlord open source implementation.

1.3. Overview

The S-RAMP specification includes a foundation document and an Atom based protocol binding document. The foundation document describes core concepts and will be the focus of the first part of this guide. The Atom binding document describes an Atom based API that implementations should provide.

An S-RAMP repository primarily stores artifacts. An artifact is comprised of the following meta-data:

1.4. Core Properties

Relationships. All artifacts in S-RAMP contain a set of core properties such as name, description, creation date, etc. Many of these properties are automatically set by the server when the artifact is added and/or updated. Others, such as description, can be set by clients.

However, most importantly every artifact has an Artifact Model and an Artifact Type. These two properties determine what kind of artifact it is (more on artifact types later, in the Data Models section of this Guide).

Additionally, some artifact types contain additional core properties. For example, the Document artifact type includes additional core properties of `contentType` and `contentSize`, while the `XsdDocument` artifact type includes the `targetNamespace` property.

1.5. Custom Properties

An artifact may have additional properties set on it by clients. These custom properties are simply arbitrary name/value pairs. The only restriction is that a custom property may not have the same name as a Core Property.

1.6. Classifiers

Another type of meta-data found on S-RAMP artifacts are classifiers. Classifiers are a lot like keywords or tags except that they are hierarchical. Every artifact has a collection of classifiers configured by the client, where each classifier must be a node in an ontology previously uploaded to the repository (presumably by an admin).

An ontology is simply a hierarchy of tags (defined as a subset of the OWL Lite format). This approach allows the repository to be configured with a pre-defined set of hierarchical tags (classifiers) that can be associated with an artifact.

An example is helpful in this case. First, a repository administrator would define and upload an ontology:

```
World
  |-> North America
    |-> United States
      |-> Alabama
      |-> Alaska
    |-> Mexico
    |-> Canada
  |-> South America
  |-> Australia
```

Once this ontology has been added to the repository, then clients can add, for example, `#Alaska` or `#Canada` as classifiers on artifacts. This provides a way to "tag" artifacts in interesting and meaningful ways, and provides a useful means of querying (more on that later).

For more information about ontologies and classifiers, have a look at Section 3 of the S-RAMP Foundation document.

1.7. Relationships

The final bit of meta-data that can be found on an artifact are relationships. An S-RAMP relationship is a uni-directional link between a source artifact and a target artifact. Artifacts can have arbitrary, client-defined relationships. Every relationship has a name and a target artifact. For example, a

client might define a relationship named "documentedBy" between a wsdl artifact and a text or PDF artifact, indicating that the latter provides documentation for the former.

Chapter 2. Getting Started

2.1. Prerequisites

The S-RAMP application is written in Java. To get started make sure your system has the following:

- Java JDK 1.6 or newer
- Apache Ant 1.7 or newer to use the installer
- Maven 3.0.3 or newer to build and run the examples

2.2. Download and Installation

The `s-ramp-<version>.zip` (or `tar.gz`) archive can be downloaded from the <http://www.jboss.org/overlord> website. Grab the latest, extract the archive and run:

```
ant install
```

The installer will ask you to choose a runtime platform. Currently the following platforms are supported:

- Wildfly 8
- JBoss EAP 6.2+

Simply follow the installer instructions to install onto the platform of your choice. We recommend installing into a clean version of which platform you choose, to minimize the risk of colliding with other projects. Note that you must have already downloaded and installed the platform on which you wish to run

Finally, please make sure the admin password you choose (the installer will prompt you for this) contains letters, numbers, and punctuation (and is at least 8 characters long).



Tip

Read the installer output carefully - extra instructions are given for certain platforms.

2.3. User Management

The S-RAMP WARs are protected using web application security mechanisms configured in the `web.xml`. By default, S-RAMP uses single-sign-on (SSO) as the actual authentication mechanism.

The SSO is provided via integration with the Keycloak framework, a powerful out-of-the-box auth solution. The actual web.xml configuration uses a standard basic security-context, but SSO is provided under-the-hood.

The S-RAMP distribution ships with a **artificer-realm.json** file that's completely pre-configured and can be directly imported into Keycloak. Startup Wildfly/EAP and visit **localhost:8080/auth/admin/master/console/#/create/realm**. The initial administrator account uses "admin" for both the username and password. There, you can upload the **artificer-realm.json** file and tweak the realm/accounts.

By default, the realm import creates an "admin" user (password: "artificer1!"). This user is used to access the S-RAMP server, UI, shell, and other tools. Again, the user is configurable through the Keycloak admin console.

Feel free to manually create a realm for scratch. However, there are a few requirements (see **artificer-realm.json** for example values):

1. The realm must be named **artificer**
2. Defined applications must include **s-ramp-server** and **s-ramp-ui**
3. To use our themed login page, use **artificer** for the **loginTheme**
4. Each user must have at least **admin** and **user** values for the **realmRole**

2.4. Startup

Once S-RAMP is installed on your preferred platform, you should be able to go ahead and start it up.

Wildfly & EAP (standalone-full is required)

```
bin/standalone.sh -c standalone-full.xml
```

2.5. Check your Installation

To make sure your installation works you can fire up the [s-ramp-ui](http://localhost:8080/s-ramp-ui) [http://localhost:8080/s-ramp-ui]. By default, the username is "admin" and the password "artificer1!". You should see the GUI dashboard and be able to navigate to either the Artifacts or Ontologies management pages:

Figure 2.1. Welcome screen of the s-ramp-ui.

You can click on `Artifacts` and see a list of files related to the S-RAMP default workflows.

Alternatively you can fire up the `s-ramp shell` in the `bin` directory of the distribution:

```

./bin/s-ramp.sh
*****

  _____
 /  ____|   |   |  \  _ \  \  \  |   ____ \
 \  `--. ____|   |  /  /  \  \  .  .  |  |  /
  `--. \____|   |  /  _  |  | \  |  |  _/
 / \  /  /   |   | \  \  |  |  |  |  |  |
 \___/      \__| \__\  |  |  |  |  |  |

JBoss S-RAMP Kurt Stam and Eric Wittmann, Licensed under the
Apache License, V2.0, Copyright 2012
*****

s-ramp>

```

To connect the shell to the server type `connect` and hit the tab key. It should auto-complete to say `s-ramp:connect http://localhost:8080/s-ramp-server` and when hitting the return key you should be prompted for user credentials. Use *admin* and whatever password you entered during installation. If this succeeds, the shell cursor/prompt will go from red to green. To browse the artifacts in the repository (there will likely not be any) run the following query:

```

s-ramp> s-ramp:query "/s-ramp"
Querying the S-RAMP repository:
/s-ramp
Atom Feed (0 entries)
  Idx                Type Name
  ---                -

```

In later chapters will go into more detail, but if this all worked you can be sure that your installation is in good working order.

Chapter 3. S-RAMP Data Models

The S-RAMP specification defines a number of built-in artifact types, while also allowing clients to define their own (implicit) types. This section of the Guide describes these different models.

An artifact may have document (e.g file) content or it may be a purely logical artifact. In either case, clients typically add artifacts to the repository directly (e.g. via the S-RAMP Atom API, described later in this guide).

Additionally, some document style artifact types when added to the repository, will result in the creation of a set of "derived" artifacts. For example, if an XSD document is added to the repository, the server will automatically extract the element declarations from the content of the file resulting in a set of additional artifacts "related" to the original. This will be described in detail further in the XSD Data Model section.

3.1. Core Data Model (core)

The S-RAMP core model defines some basic artifact types including Document and XmlDocument. These basic types allow clients to add simple files to the repository as artifacts.

Artifact Type	Parent Type	Properties
Document		contentType, contentSize, contentHash
XmlDocument	Document	contentEncoding

3.2. XML Schema (XSD) Data Model (xsd)

The XSD model defines a single document style artifact, XsdDocument, and a number of derived artifact types. When an XSD document is added to the repository, the server will additionally "index" the artifact by automatically creating a number of derived artifacts of the following types from the XSD content.

Artifact Type	Parent Type	Properties
XsdDocument	XmlDocument	targetNamespace
AttributeDeclaration	<derived>	ncName, namespace
ElementDeclaration	<derived>	ncName, namespace
SimpleTypeDeclaration	<derived>	ncName, namespace
ComplexTypeDeclaration	<derived>	ncName, namespace

3.3. WSDL Data Model (wsdl)

The WSDL model defines a single document style artifact, WsdlDocument, and a number of derived artifact types. Similarly to the XsdDocument type, when a WSDL document is added to the

repository, the server will automatically derive additional artifacts (listed below) from the content of the WSDL file.

For further details about the WSDL Model, please see the S-RAMP specification's foundation document, section 2.4.2.

Artifact Type	Parent Type	Properties
WSDLDocument	XmlDocument	targetNamespace, xsdTargetNamespaces
WSDLService	<derived>	ncName, namespace
Port	<derived>	ncName, namespace
WSDLExtension	<derived>	ncName, namespace
Part	<derived>	ncName, namespace
Message	<derived>	ncName, namespace
Fault	<derived>	ncName, namespace
PortType	<derived>	ncName, namespace
Operation	<derived>	ncName, namespace
OperationInput	<derived>	ncName, namespace
OperationOutput	<derived>	ncName, namespace
Binding	<derived>	ncName, namespace
BindingOperation	<derived>	ncName, namespace
BindingOperationInput	<derived>	ncName, namespace
BindingOperationOutput	<derived>	ncName, namespace
BindingOperationFault	<derived>	ncName, namespace

3.4. Policy Data Model (policy)

This data model is present to represent the primary components of a WS-Policy document.

Artifact Type	Parent Type	Properties
PolicyDocument	XmlDocument	
PolicyExpression	<derived>	
PolicyAttachment	<derived>	

3.5. SOA Data Model (soa)

The SOA model exists to provide a link to the work done by the Open Group SOA Ontology group. All of the artifacts in this model are non-document artifacts which are directly instantiated by clients.

Artifact Type	Parent Type	Properties
HumanActor		

Artifact Type	Parent Type	Properties
Choreography		
ChoreographyProcess		
Collaboration		
CollaborationProcess		
Composition		
Effect		
Element		
Event		
InformationType		
Orchestration		
OrchestrationProcess		
Policy		
PolicySubject		
Process		
Service		
ServiceContract		
ServiceComposition		
ServiceInterface		
System		
Task		

3.6. Service Implementation Data Model (serviceImplementation)

The Service Implementation model adds SOA service implementation artifact types underneath the (already mentioned) SOA Data Model.

Artifact Type	Parent Type	Properties
Organization		end
ServiceEndpoint		end, url
ServiceInstance		end, url
ServiceOperation		end, url

3.7. Custom/Extension Data Models (ext)

Clients can define their own (implicit) data models by using the "ext" model space defined by the S-RAMP specification. This allows clients to add documents with custom artifact types. For

example, a client can add an artifact to /s-ramp/ext/PdfDocument. This provides a way for clients to define their own data models with their own properties and relationships. Note however that the server will not have a definition of the model - it is up to the client to properly conform to their own implicit model. Custom properties and user-defined relationships allow clients to richly define their own models.

As an example, a client might define the following Data Model for a J2EE web application domain:

Artifact Type	Parent Type	Properties
WebXmlDocument	ExtendedDocument	displayName
ServletFilter	ExtendedArtifactType	displayName, filterClass
Servlet	ExtendedArtifactType	servletClass, loadOnStartup

3.8. Java Data Model

The S-RAMP server adds a custom (ext) model for dealing with Java artifacts. The following table lists the Java artifact types that are supported out of the box. These artifacts can either be directly added to the repository or they can be added as part of the expansion of some other artifact. A typical example of the latter is how JavaClass artifacts may be added because they are contained within an archive of some kind.

Artifact Type	Parent Type	File Extension	Properties
JavaArchive	ExtendedDocument	.jar	
JavaWebApplication	ExtendedDocument	.war	
JavaEnterpriseApplication	ExtendedDocument	.ear	
BeanArchiveDescription	ExtendedDocument	.beans.xml	
JavaClass	ExtendedDocument	.class	packageName, className
JavaInterface	ExtendedDocument	.class	packageName, className
JavaEnum	ExtendedDocument	.class	packageName, className

3.9. KIE Data Model (Knowledge is Everything)

The S-RAMP server includes basic out of the box support for Drools (KIE) artifact types. The following table lists the KIE artifact types that are currently supported.

Artifact Type	Parent Type	File Extension	Properties
KieJarArchive	ExtendedDocument	.jar	

Artifact Type	Parent Type	File Extension	Properties
KieXmlDocument	ExtendedDocument	kie.xml	
BpmnDocument	ExtendedDocument	bpmn	
DroolsDocument	ExtendedDocument	drl	

3.10. SwitchYard Data Model

The S-RAMP server includes a custom (ext) data model for SwitchYard artifacts. The following table lists the artifact types currently supported. The non-derived artifacts can be added directly to the repository or expanded out of some archive type artifact.

Artifact Type	Parent Type	Properties
SwitchYardApplication	ExtendedDocument	
SwitchYardXmlDocument	ExtendedDocument	targetNamespace
SwitchYardService	<derived from SwitchYardXmlDocument>	
SwitchYardComponent	<derived from SwitchYardXmlDocument>	requires
SwitchYardComponentService	<derived from SwitchYardXmlDocument>	
SwitchYardTransformer	<derived from SwitchYardXmlDocument>	transformer-type
SwitchYardValidator	<derived from SwitchYardXmlDocument>	validator-type

Additionally, the SwitchYard derived artifacts have various relationships automatically created between and amongst them (as well as to other derived artifacts such as those derived from XML Schema artifacts). The following table outlines all the relationships currently defined in the SwitchYard Model.

Relationship	Source Artifact Type	Target Artifact Type
implementedBy	SwitchYardComponent	JavaClass
implementedBy	SwitchYardTransformer	JavaClass
implementedBy	SwitchYardValidator	JavaClass
implements	SwitchYardService	JavaInterface, PortType
implements	SwitchYardComponentService	JavaInterface, PortType
offers	SwitchYardComponent	SwitchYardComponentService
promotes	SwitchYardService	SwitchYardComponent

Relationship	Source Artifact Type	Target Artifact Type
references	SwitchYardComponent	JavaInterface, PortType
transformsFrom	SwitchYardTransformer	JavaClass, ElementDeclaration
transformsTo	SwitchYardTransformer	JavaClass, ElementDeclaration
validates	SwitchYardValidator	JavaClass, ElementDeclaration

3.11. Teiid Data Model (Teiid)

The Teiid model adds Teiid-related artifact types, derived artifacts, and relationships. There are artifact types for the following Teiid resources: VDBs (*.vdb), models (*.xml), VDB manifests (usually named `vdb.xml`), and VDB configuration files (`ConfigurationInfo.def`). Teiid resources should be added to the repository using the corresponding artifact types listed in the following table:

Artifact Type	Parent Type	Properties
TeiidVdb		
TeiidModel	ExtendedArtifactType	description, maxSetSize, mmuuid, modelType, nameInSource, primaryMetamodelUri, producerName, producerVersion, visible
TeiidVdbConfigInfo	ExtendedArtifactType	
TeiidVdbManifest	ExtendedArtifactType	description, preview, UseConnectorMetadata, vdbVersion, <custom properties>
TeiidVdbDataPolicy	<derived from TeiidVdbManifest>	anyAuthenticated, description, roleNames, tempTableCreatable
TeiidVdbEntry	<derived from TeiidVdbManifest>	description, <custom properties>
TeiidVdbImportVdb	<derived from TeiidVdbManifest>	importDataPolicies, vdbVersion

Artifact Type	Parent Type	Properties
TeiidVdbPermission	<derived from TeiidVdbManifest>	alterable, condition, creatable, deletable, executable, languagable, mask, readable, updatable
TeiidVdbSchema	<derived from TeiidVdbManifest>	builtIn, checksum, description, indexName, metadata, metadataType, modelClass, modelUuid, pathInVdb, schemaType, visible, <custom properties>
TeiidVdbSource	<derived from TeiidVdbManifest>	jndiName, translatorName
TeiidVdbTranslator	<derived from TeiidVdbManifest>	description, translatorType, <custom properties>
TeiidVdbValidationError	<derived from TeiidVdbManifest>	message, severity

When a `TeiidVDB` or a `TeiidVdbManifest` artifact type is added to the repository, relationships between it and its derived artifacts are created. Note that the `TeiidVdbContains` relationship is the inverse of the `expandedFromDocument` relationship. Here is a list of the Teiid relationship types:

Relationship Type	Source Type	Target Type	Multiplicity
TeiidVdbContains	TeiidVdbManifest	TeiidVdbDataPolicy, TeiidVdbEntry, TeiidVdbSchema, TeiidVdbTranslator, TeiidVdbImportVdb	1 to many
TeiidVdbDataPolicyExpandedFromDocument	TeiidVdbDataPolicy	TeiidVdbPermission	1 to many
TeiidVdbPermissionExpandedFromDocument	TeiidVdbPermission	TeiidVdbDataPolicy	1 to 1
TeiidVdbSchemaExpandedFromDocument	TeiidVdbSchema	TeiidVdbSource	1 to 1
TeiidVdbSchemaExpandedFromDocument	TeiidVdbSchema	TeiidVdbValidationErrors	1 to many
TeiidVdbSourceExpandedFromDocument	TeiidVdbSource	TeiidVdbSchema	1 to many
TeiidVdbSourceExpandedFromDocument	TeiidVdbSource	TeiidVdbTranslator	1 to 1

Relationship Type	Source Type	Target Type	Multiplicity
TeiidVdbTranslatorToVdbSource	TeiidVdbTranslator	TeiidVdbSource	1 to many
TeiidVdbValidationToVdbSource	TeiidVdbValidation	TeiidVdbSource	1 to 1
expandedFromDocToVdbManifest	TeiidVdbDataPolicy, TeiidVdbEntry, TeiidVdbSchema, TeiidVdbTranslator, TeiidVdbImportVdb	TeiidVdbManifest	many to 1

Chapter 4. Query Language

Another key aspect of the S-RAMP specification is the query language it defines, which allows clients to find artifacts by various criteria. The S-RAMP query language is a subset of the XPath 2.0 language, designed specifically to find and select S-RAMP artifacts.



Tip

for detailed information about the S-RAMP Query Language, see Section 4 of the S-RAMP specification's foundation document.

As you might imagine, the query language allows clients to find artifacts based on any of the already discussed artifact meta-data, including:

*Core Properties *Custom Properties *Classifiers *Relationships

The basic structure of a typical S-RAMP query looks like this:

```
/s-ramp/<artifactModel>/<artifactType>[ <artifact-predicate> ]/
relationship[ <target-artifact-predicate> ]
```

Of course, not all of the components of the above query are required. It is likely best to provide the following table of examples of a range of queries:

Query	What It Selects
/s-ramp	All artifacts.
/s-ramp/core	All Core Model artifacts.
/s-ramp/xsd/XsdDocument	All XsdDocument artifacts.
/s-ramp/xsd/XsdDocument[@my-prop]	All XsdDocument artifacts that have the custom property <i>my-prop</i> defined (with any value).
/s-ramp/xsd/XsdDocument[@name='core.xsd']	XsdDocument artifacts named <i>core.xsd</i> .
/s-ramp/xsd/XsdDocument[@name='core.xsd' and @version='1.0']	XsdDocument artifacts named <i>core.xsd</i> and versioned as <i>1.0</i> .
/s-ramp/soa[@myCustomProperty='foo']	SOA artifacts with a custom property named <i>myCustomProperty</i> that has value <i>foo</i> .
/s-ramp/core[classifiedByAnyOf(., 'Maine', 'Alaska')]	Core artifacts classified by either <i>Maine</i> or <i>Alaska</i> (presumably from the <i>Regions</i> ontology).

Query	What It Selects
/s-ramp/wSDL/ PortType[@name='OrderServicePT']/ operation	Artifacts related to any <i>PortType</i> artifact named <i>OrderServicePT</i> via a relationship named <i>operation</i> . (This effectively returns all of the order service port type's operations)
/s-ramp/ext/ ServletFilter[relatedDocument[@uuid='12345']]	All servlet filter artifacts derived from (i.e. contain a <i>relatedDocument</i> relationship to) an artifact with UUID <i>12345</i> .
/s-ramp/wSDL/Message[xp2:matches(.,'get.*')]/ part[element]	Element style WSDL parts from WSDL messages with names starting with <i>get</i> .

In addition, Overlord S-RAMP provides extensions to the S-RAMP query language, providing extra capabilities.

Query	What It Selects
/s-ramp/xsd/ XsdDocument[someRelationship[s- ramp:getRelationshipAttribute(., <i>someName</i>)]]	All XSD artifacts that contain a generic relationship named <i>someRelationship</i> , and that relationship has an <i>otherAttribute</i> named <i>someName</i> .
/s-ramp/xsd/ XsdDocument[someRelationship[s- ramp:getRelationshipAttribute(., <i>someName</i>) = <i>someValue</i>]]	All XSD artifacts that contain a generic relationship named <i>someRelationship</i> , and that relationship has an <i>otherAttribute</i> named <i>someName</i> with a <i>someValue</i> value.
/s-ramp/xsd/ XsdDocument[someRelationship[s- ramp:getTargetAttribute(., <i>someName</i>)]]	All XSD artifacts that contain a generic relationship named <i>someRelationship</i> , and that relationship's target has an <i>otherAttribute</i> named <i>someName</i> .
/s-ramp/xsd/ XsdDocument[someRelationship[s- ramp:getTargetAttribute(., <i>someName</i>) = <i>someValue</i>]]	All XSD artifacts that contain a generic relationship named <i>someRelationship</i> , and that relationship's target has an <i>otherAttribute</i> named <i>someName</i> with a <i>someValue</i> value.

Chapter 5. Overlord S-RAMP REST API Endpoints

The intent of the S-RAMP specification is to outline the data model and protocol designed to define how a repository should store and manipulate artifacts. The foundation document defines the former, while various protocol binding documents define the latter. Version 1 of the S-RAMP specification includes a single, Atom based protocol binding.

The S-RAMP specification does not dictate the format of the Atom REST endpoints. Instead, the client is expected to query a [service document endpoint](#) and inspect it to find the various relevant endpoints. The specification does present a notional format, but implementations are not required to follow it. This Guide will give examples based on the spec's notional format, as well as Overlord-specific extensions. But it bears repeating that for any given server implementation, a client should first query the [Atom service document](#).

However, the Atom Binding document does outline the inputs, outputs, and REST verbs that must be used for each of the supported operations. In general, the Atom API data models are used to wrap custom S-RAMP specific XML structures. Atom Entry documents are used when dealing with individual artifacts, while Atom Feed documents are used when dealing with lists of documents.

The following table lists the endpoints available in the Overlord implementation:

Endpoint	Name
GET /s-ramp/servicedocument	Get Service Document
POST /s-ramp/{model}/{type}	Publish Artifact
PUT /s-ramp/{model}/{type}/{uuid}	Update Artifact
PUT /s-ramp/{model}/{type}/{uuid}/media	Update Artifact Content
GET /s-ramp/{model}/{type}/{uuid}	Get Artifact
GET /s-ramp/{model}/{type}/{uuid}/media	Get Artifact Content
DELETE /s-ramp/{model}/{type}/{uuid}	Delete Artifact
GET /s-ramp/{model}	Get Artifact Feed (by model)
GET /s-ramp/{model}/{type}	Get Artifact Feed (by type)
GET /s-ramp	Query
POST /s-ramp	Query
POST /s-ramp	Batch Processing
POST /s-ramp/query	Create Stored Query
PUT /s-ramp/query/{queryName}	Update Stored Query
GET /s-ramp/query	List Stored Queries

Endpoint	Name
GET /s-ramp/query/{queryName}	Get Stored Query
GET /s-ramp/query/{queryName}/results	Execute Stored Query
DELETE /s-ramp/query/{queryName}	Delete Stored Query
POST /s-ramp/ontology	Add Ontology
GET /s-ramp/ontology	List Ontologies
PUT /s-ramp/ontology/{uuid}	Update Ontology
GET /s-ramp/ontology/{uuid}	Get Ontology
DELETE /s-ramp/ontology/{uuid}	Delete Ontology
GET /s-ramp/audit/artifact/{artifactUuid}	Get Artifact Audit History
GET /s-ramp/audit/user/{username}	Get User Audit History
POST /s-ramp/audit/artifact/{artifactUuid}	Add Artifact Audit Entry
GET /s-ramp/audit/artifact/{artifactUuid}/ {auditEntryUuid}	Get Artifact Audit Entry

5.1. API: Get Service Document

/s-ramp/servicedocument

Retrieves the service document.

HTTP Method	Request	Response
GET	N/A	Atom Service Document

The resulting service document will contain a set of workspaces representing the artifact collections supported by the server, along with endpoints indicating how to manipulate them.

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<app:service xmlns:atom="http://www.w3.org/2005/Atom" xmlns:app="http://
www.w3.org/2007/app">
  <app:workspace>
    <atom:title>Core Model</atom:title>
    <app:collection href="http://example.org/s-ramp/core">
      <atom:title>Core Model Objects</atom:title>
      <app:accept>application/zip</app:accept>
```

```

        <app:categories fixed="yes">
            <atom:category label="Document" scheme="urn:x-s-
ramp:2013:type" term="Document" />
            <atom:category label="XML Document" scheme="urn:x-s-
ramp:2013:type" term="XmlDocument" />
        </app:categories>
    </app:collection>
    <app:collection href="http://example.org/s-ramp/core/Document">
        <atom:title>Documents</atom:title>
        <app:accept>application/octet-stream</app:accept>
        <app:categories fixed="yes">
            <atom:category label="Document" scheme="urn:x-s-
ramp:2013:type" term="Document" />
        </app:categories>
    </app:collection>
    <app:collection href="http://example.org/s-ramp/core/XmlDocument">
        <atom:title>XML Documents</atom:title>
        <app:accept>application/xml</app:accept>
        <app:categories fixed="yes">
            <atom:category label="XML Document" scheme="urn:x-s-
ramp:2013:type" term="XmlDocument" />
        </app:categories>
    </app:collection>
</app:workspace>
</app:service>

```



Tip

The above example only includes the Core data model and thus the service document has a single workspace. The full service document would have multiple workspaces - one for each data model supported by the server.

5.2. Artifacts

5.2.1. API: Publish Artifact

Publishes a new artifact into the repository. There are two basic types of artifacts from the protocol standpoint: document style artifacts (those artifacts that are based on files/binary content) and logical (direct instantiation) artifacts. In the case of a document-style artifact, the client must POST the binary content to the correct Atom Endpoint. In the case of a direct artifact (no document content) the client must POST an Atom Entry containing an S-RAMP artifact XML entity to the appropriate endpoint. The server will respond with an Atom Entry containing the full meta data of the newly created artifact (if successful).

There are three ways this endpoint can be invoked, depending on the type of artifact being published:

- Document Style Artifact
- Non-Document Style Artifact
- Document Style Artifact with Meta Data

5.2.1.1. Publish a Document Style Artifact

```
/s-ramp/{model}/{type}
```

<i>HTTP Method</i>	<i>Request</i>	<i>Response</i>
POST	Binary File	Atom Entry

Publishing a document style artifact is simply a matter of POSTing the binary content of the document to the appropriate endpoint.

Example Request

```
POST /s-ramp/core/Document HTTP/1.1
```

```
This is a simple text document, uploaded as an artifact  
into S-RAMP.
```

Example Response

```
HTTP/1.1 200 OK
```

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>  
<atom:entry xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://  
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"  
  xmlns:xlink="http://www.w3.org/1999/xlink" s-ramp:derived="false">  
  <atom:title>test.txt</atom:title>  
  <atom:link  
    href="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-  
d889a27f1f6e/media"  
    rel="alternate" type="text/plain" />  
  <atom:link href="http://example.org/s-ramp/core/Document/05778de3-  
be85-4696-b5dc-d889a27f1f6e"  
    rel="self" type="application/atom+xml;type="entry"" />  
  <atom:link  
    href="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-  
d889a27f1f6e/media"  
    rel="edit-media" type="application/atom+xml;type="entry"" />  
  <atom:link href="http://example.org/s-ramp/core/Document/05778de3-  
be85-4696-b5dc-d889a27f1f6e"  
    rel="edit" type="application/atom+xml;type="entry"" />  
</atom:entry>
```

```

<atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
<atom:category label="Document" scheme="x-s-ramp:2013:model" term="core" /
>
<atom:updated>2013-05-14T13:43:09.708-04:00</atom:updated>
<atom:id>05778de3-be85-4696-b5dc-d889a27f1f6e</atom:id>
<atom:published>2013-05-14T13:43:09.708-04:00</atom:published>
<atom:author>
  <atom:name>ewittman</atom:name>
</atom:author>
<atom:content
  src="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-
d889a27f1f6e/media"
  type="text" />
<s-ramp:artifact>
  <s-ramp:Document artifactType="Document" contentSize="69"
contentType="text/plain"
    createdBy="eric" createdTimestamp="2013-05-14T13:43:09.708-04:00"
    lastModifiedBy="eric"
    lastModifiedTimestamp="2013-05-14T13:43:09.708-04:00" name="test.txt"
    uuid="05778de3-be85-4696-b5dc-d889a27f1f6e" />
</s-ramp:artifact>
</atom:entry>

```

5.2.1.2. Publish a Non-Document Style Artifact

```
/s-ramp/{model}/{type}
```

HTTP Method	Request	Response
POST	Atom Entry	Atom Entry

Publishing a non-document style artifact requires an Atom Entry (which contains an *s-ramp:artifact* child element) to be POSTed to the appropriate endpoint. The appropriate endpoint is based on the desired artifact model and type.

Example Request

```

POST /s-ramp/ext/MyArtifact HTTP/1.1

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:entry xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" s-ramp:derived="false">
  <atom:title>Example Artifact</atom:title>
  <s-ramp:artifact>
    <s-ramp:ExtendedArtifactType extendedType="MyArtifact"
      artifactType="ExtendedArtifactType" name="My Artifact One" />
  </s-ramp:artifact>
</atom:entry>

```

```
</s-ramp:artifact>
</atom:entry>
```

Example Response

```

HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:entry xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink"
  xmlns:atom="http://www.w3.org/2005/Atom" s-ramp:derived="false" s-
ramp:extendedType="MavenPom">
  <atom:title>pom.xml</atom:title>
  <atom:link href="http://example.org/s-ramp/ext/MavenPom/5f4cbf1e-
cafb-4479-8867-fc5df5f21867/media"
    rel="alternate" type="application/xml" />
  <atom:link href="http://example.org/s-ramp/ext/MavenPom/5f4cbf1e-
cafb-4479-8867-fc5df5f21867" rel="self"
    type="application/atom+xml;type="entry"" />
  <atom:link href="http://example.org/s-ramp/ext/MavenPom/5f4cbf1e-
cafb-4479-8867-fc5df5f21867/media"
    rel="edit-media" type="application/atom+xml;type="entry"" />
  <atom:link href="http://example.org/s-ramp/ext/MavenPom/5f4cbf1e-
cafb-4479-8867-fc5df5f21867" rel="edit"
    type="application/atom+xml;type="entry"" />
  <atom:category label="Extended Document" scheme="x-s-ramp:2013:type"
term="MavenPom" />
  <atom:category label="Extended Document" scheme="x-s-ramp:2013:model"
term="ext" />
  <atom:updated>2013-05-14T13:49:20.645-04:00</atom:updated>
  <atom:id>5f4cbf1e-cafb-4479-8867-fc5df5f21867</atom:id>
  <atom:published>2013-05-14T13:49:20.645-04:00</atom:published>
  <atom:author>
    <atom:name>ewittman</atom:name>
  </atom:author>
  <atom:content type="application/xml"
    src="http://example.org/s-ramp/ext/MavenPom/5f4cbf1e-cafb-4479-8867-
fc5df5f21867/media" />
  <s-ramp:artifact>
    <s-ramp:ExtendedDocument extendedType="MavenPom"
contentType="application/xml"
  contentType="application/xml"
  contentSize="4748" artifactType="ExtendedDocument" name="pom.xml"
  createdBy="eric"
  uuid="5f4cbf1e-cafb-4479-8867-fc5df5f21867"
  createdTimestamp="2013-05-14T13:49:20.645-04:00"
  lastModifiedTimestamp="2013-05-14T13:49:20.645-04:00"
  lastModifiedBy="eric"
  s-ramp:contentType="application/xml" s-ramp:contentSize="4748" />
  </s-ramp:artifact>

```

```
</atom:entry>
```

5.2.1.3. Publish a Document Style Artifact with Meta-Data

```
/s-ramp/{model}/{type}
```

HTTP Method	Request	Response
POST	Multipart/ Related	Atom Entry

Sometimes it is convenient to publish an artifact and update its meta-data in a single request. This can be done by POSTing a multipart/related request to the server at the appropriate endpoint. The first part in the request must be an Atom Entry (containing the meta-data being set), while the second part must be the binary content. The appropriate endpoint is based on the desired artifact model and type.

Example Request

```
POST /s-ramp/core/Document HTTP/1.1
Content-Type: multipart/related;boundary="====1605871705==";
type="application/atom+xml"
MIME-Version: 1.0

====1605871705==
Content-Type: application/atom+xml; charset="utf-8"
MIME-Version: 1.0

<?xml version="1.0"?>
<entry xmlns="http://www.w3.org/2005/Atom"
  xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0">
  <title type="text">myfile.txt</title>
  <summary type="text">The description of my text file.</summary>
  <category term="Document" label="Document"
    scheme="urn:x-s-ramp:2013urn:x-s-ramp:2013:type" />
  <s-ramp:artifact xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-
ramp-v1.0"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <s-ramp:Document name="myfile.txt" version="1.0"
      description="The description of my text file." >
      <s-ramp:classifiedBy>
        http://example.org/ontologies/regions.owl/Maine
      </s-ramp:classifiedBy>
      <s-ramp:property>
        <propertyName>foo</propertyName>
        <propertyValue>pity him</propertyValue>
      </s-ramp:property>
```

```
</s-ramp:Document>
</s-ramp:artifact>
</entry>
-----1605871705==
Content-Type: application/xml
MIME-Version: 1.0

This is a simple text document, uploaded as an artifact
into S-RAMP.
-----1605871705===--
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:entry xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" s-ramp:derived="false">
  <atom:title>test.txt</atom:title>
  <atom:link
    href="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-
d889a27f1f6e/media"
    rel="alternate" type="text/plain" />
  <atom:link href="http://example.org/s-ramp/core/Document/05778de3-
be85-4696-b5dc-d889a27f1f6e"
    rel="self" type="application/atom+xml;type="entry";" />
  <atom:link
    href="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-
d889a27f1f6e/media"
    rel="edit-media" type="application/atom+xml;type="entry";" />
  <atom:link href="http://example.org/s-ramp/core/Document/05778de3-
be85-4696-b5dc-d889a27f1f6e"
    rel="edit" type="application/atom+xml;type="entry";" />
  <atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
  <atom:category label="Document" scheme="x-s-ramp:2013:model" term="core" /
>
  <atom:updated>2013-05-14T13:43:09.708-04:00</atom:updated>
  <atom:id>05778de3-be85-4696-b5dc-d889a27f1f6e</atom:id>
  <atom:published>2013-05-14T13:43:09.708-04:00</atom:published>
  <atom:author>
    <atom:name>ewittman</atom:name>
  </atom:author>
  <atom:content
    src="http://example.org/s-ramp/core/Document/05778de3-be85-4696-b5dc-
d889a27f1f6e/media"
    type="text" />
  <s-ramp:artifact>
```



```

<s-ramp:Document artifactType="Document" contentSize="69"
contentType="text/plain"
  name="myfile.txt" uuid="05778de3-be85-4696-b5dc-d889a27f1f6e">
    description="The description of my text file." version="1.0"
    createdBy="eric" createdTimestamp="2013-05-14T13:43:09.708-04:00"
    lastModifiedBy="eric"
    lastModifiedTimestamp="2013-05-14T13:43:09.708-04:00"
    <s-ramp:classifiedBy>
      http://example.org/ontologies/regions.owl/Maine
    </s-ramp:classifiedBy>
    <s-ramp:property>
      <propertyName>foo</propertyName>
      <propertyValue>pity him</propertyValue>
    </s-ramp:property>
  </s-ramp:Document>
</s-ramp:artifact>
</atom:entry>

```

5.2.2. API: Update Artifact

```
/s-ramp/{model}/{type}/{uuid}
```

Updates an artifact's meta data.

HTTP Method	Request	Response
PUT	Atom Entry	N/A

This endpoint is used to update a single artifact's meta data, including core properties, custom properties, classifiers, and relationships. Typically the client should first retrieve the artifact (e.g. by invoking the Get Artifact endpoint), make changes to the artifact, then issue a PUT request to the Update Artifact endpoint.

Example Request

```

PUT /s-ramp/core/Document/098da465-2eae-49b7-8857-eb447f03ac02 HTTP/1.1

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:entry xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
xmlns:xlink="http://www.w3.org/1999/xlink"
xmlns:atom="http://www.w3.org/2005/Atom">
  <atom:title>pom.xml</atom:title>
  <atom:updated>2013-05-15T08:12:01.985-04:00</atom:updated>
  <atom:id>098da465-2eae-49b7-8857-eb447f03ac02</atom:id>
  <atom:published>2013-05-15T08:12:01.985-04:00</atom:published>
  <atom:author>
    <atom:name>ewittman</atom:name>
  </atom:author>
</atom:entry>

```

```
</atom:author>
<atom:summary>Sample description of my document.</atom:summary>
<s-ramp:artifact>
  <s-ramp:Document contentType="text/plain" contentSize="4748"
artifactType="Document"
  name="myfile.txt" description="Sample description of my document."
createdBy="ewittman"
  uuid="098da465-2eae-49b7-8857-eb447f03ac02"
createdTimestamp="2013-05-15T08:12:01.985-04:00"
  lastModifiedTimestamp="2013-05-15T08:12:01.985-04:00"
lastModifiedBy="ewittman">
  <s-ramp:property>
    <s-ramp:propertyName>foo</s-ramp:propertyName>
    <s-ramp:propertyValue>bar</s-ramp:propertyValue>
  </s-ramp:property>
</s-ramp:Document>
</s-ramp:artifact>
</atom:entry>
```

5.2.3. API: Update Artifact Content

```
/s-ramp/{model}/{type}/{uuid}/media
```

Updates an artifact's content.

HTTP Method	Request	Response
PUT	Binary Content	N/A

This endpoint is used to update a single artifact's content, regardless if the artifact is a text document or some sort of binary. The body of the request should be the new binary content of the artifact.

Example Request

```
PUT /s-ramp/core/Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media
HTTP/1.1

Some file content goes here.
```

5.2.4. API: Get Artifact

```
/s-ramp/{model}/{type}/{uuid}
```

Retrieves an artifact's meta data.

HTTP Method	Request	Response
GET	N/A	Atom Entry (full)

This endpoint is used to retrieve the full meta-data for a single artifact in the repository. The data is returned wrapped up in an Atom Entry document. The Atom Entry will contain an extended XML element containing the S-RAMP artifact data.

Example Request

```
PUT /s-ramp/xsd/ComplexTypeDeclaration/0104e848-fe91-4d93-a307-fb69ec9fd638
HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:entry xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0" xmlns:xlink="http://
www.w3.org/1999/xlink" s-ramp:derived="true">
<atom:title>submitOrderResponseType</atom:title>
<atom:link href="http://localhost:8080/s-ramp-server/s-ramp/xsd/
ComplexTypeDeclaration/0104e848-fe91-4d93-a307-fb69ec9fd638" rel="self"
type="application/atom+xml;type="entry""/>
<atom:link href="http://localhost:8080/s-ramp-server/s-ramp/xsd/
ComplexTypeDeclaration/0104e848-fe91-4d93-a307-fb69ec9fd638/media"
rel="edit-media" type="application/atom+xml;type="entry""/>
<atom:link href="http://localhost:8080/s-ramp-server/s-ramp/xsd/
ComplexTypeDeclaration/0104e848-fe91-4d93-a307-fb69ec9fd638" rel="edit"
type="application/atom+xml;type="entry""/>
<atom:category label="XML Schema Complex Type Declaration" scheme="x-s-
ramp:2013:type" term="ComplexTypeDeclaration"/>
<atom:category label="XML Schema Complex Type Declaration" scheme="x-s-
ramp:2013:model" term="xsd"/>
<atom:updated>2013-07-22T12:19:23.554-04:00</atom:updated>
<atom:id>0104e848-fe91-4d93-a307-fb69ec9fd638</atom:id>
<atom:published>2013-07-22T12:19:22.630-04:00</atom:published>
<atom:author>
<atom:name>eric</atom:name>
</atom:author>
<s-ramp:artifact>
<s-ramp:ComplexTypeDeclaration artifactType="ComplexTypeDeclaration"
createdBy="eric" createdTimestamp="2013-07-22T12:19:22.630-04:00"
lastModifiedBy="eric" lastModifiedTimestamp="2013-07-22T12:19:23.554-04:00"
name="submitOrderResponseType" namespace="urn:switchyard-quickstart-
demo:multiapp:1.0" uuid="0104e848-fe91-4d93-a307-fb69ec9fd638">
```

```
<s-ramp:relatedDocument artifactType="XsdDocument">fe7b72ec-5ad9-436c-  
b7aa-0391da5cc972</s-ramp:relatedDocument>  
</s-ramp:ComplexTypeDeclaration>  
</s-ramp:artifact>  
</atom:entry>
```

5.2.5. API: Get Artifact Content

```
/s-ramp/{model}/{type}/{uuid}/media
```

Retrieves an artifact's content.

HTTP Method	Request	Response
GET	N/A	Binary artifact content

This endpoint is used to retrieve the full content of a single artifact in the repository. If the artifact is not a Document style artifact, this call will fail. Otherwise it will return the full artifact content. For example, if the artifact is a PdfDocument, then this call will return the PDF file.

Example Request

```
GET /s-ramp/core/Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media  
HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK  
  
Artifact/file content returned here.
```

5.2.6. API: Delete Artifact

```
/s-ramp/{model}/{type}/{uuid}
```

Deletes an artifact.

HTTP Method	Request	Response
DELETE	N/A	N/A

This endpoint is used to delete a single artifact from the repository. If the artifact does not exist or is a derived artifact, then this will fail. This might also fail if other artifacts have relationships with it. Otherwise this artifact (and all of its derived artifacts) will be deleted.

Example Request

```
DELETE /s-ramp/core/Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0 HTTP/1.1
```

5.2.7. Queries

Performing an S-RAMP query is a matter of issuing a GET or POST to the S-RAMP query endpoint. In addition, full feeds are available for all Artifact Models and Artifact Types. In both cases, the response is an Atom Feed where each Entry provides summary information about an artifact in the repository. To retrieve full details about a given entry in the feed (custom properties, classifiers, relationships), the client must issue an additional GET. Only a subset of the core properties, such as name and description, are mapped to the Atom Entry in a feed.

5.2.7.1. API: Get Artifact Feed (by model)

```
/s-ramp/{model}
```

Retrieves an Atom feed of all artifacts in a given model.

HTTP Method	Request	Response
GET	N/A	Atom Feed

This endpoint is used to retrieve an Atom feed of all artifacts in a single S-RAMP model. The feed contains Atom summary Entries - one for each artifact in the feed. Standard paging options apply.

Example Request

```
GET /s-ramp/core HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="5">
  <atom:title>S-RAMP Feed</atom:title>
  <atom:subtitle>Ad Hoc query feed</atom:subtitle>
  <atom:updated>2013-07-22T12:50:16.605-04:00</atom:updated>
  <atom:id>1647967f-a6f4-4e9c-82d3-ac422fb152f3</atom:id>
  <atom:author>
    <atom:name>anonymous</atom:name>
  </atom:author>
  <atom:entry s-ramp:derived="false">
    <atom:title>sramp.sh</atom:title>
```

```

    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="alternate" type="application/x-sh" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
    <atom:category label="Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:22:01.953-04:00</atom:updated>
    <atom:id>0f6f9b6b-9952-4059-ab70-7ee3442ddcf0</atom:id>
    <atom:published>2013-07-22T12:21:49.499-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      type="application/x-sh" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>beans.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:27.660-04:00</atom:updated>
    <atom:id>20474032-9536-4cef-812c-4fea432fdebd</atom:id>
    <atom:published>2013-07-22T12:19:27.644-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>

```

```

    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>forge.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
      rel="self" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
      rel="edit-media" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
      rel="edit" type="application/atom+xml;type="entry";" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:25.576-04:00</atom:updated>
    <atom:id>2c21a9d3-0d09-41d8-8783-f3e795d8690d</atom:id>
    <atom:published>2013-07-22T12:19:25.555-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
    type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>route.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="self" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="edit-media" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="edit" type="application/atom+xml;type="entry";" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />

```

```

    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:25.602-04:00</atom:updated>
    <atom:id>5b653bfe-4f58-451e-b738-394e61c0c5f9</atom:id>
    <atom:published>2013-07-22T12:19:25.577-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>beans.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:21.498-04:00</atom:updated>
    <atom:id>a3f9d4d7-0f95-4219-85f6-84df445ef270</atom:id>
    <atom:published>2013-07-22T12:19:21.376-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      type="application/xml" />
  </atom:entry>
</atom:feed>

```

5.2.7.2. API: Get Artifact Feed (by type)

```
/s-ramp/{model}/{type}
```

Retrieves an Atom feed of all artifacts of a specific type.

HTTP Method	Request	Response
GET	N/A	Atom Feed

This endpoint is used to retrieve an Atom feed of all artifacts of a specific S-RAMP type. The feed contains Atom summary Entries - one for each artifact in the feed. Standard paging options (as query params) apply.

Example Request

```
GET /s-ramp/core/Document HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="5">
  <atom:title>S-RAMP Feed</atom:title>
  <atom:subtitle>Ad Hoc query feed</atom:subtitle>
  <atom:updated>2013-07-22T12:50:16.605-04:00</atom:updated>
  <atom:id>1647967f-a6f4-4e9c-82d3-ac422fb152f3</atom:id>
  <atom:author>
    <atom:name>anonymous</atom:name>
  </atom:author>
  <atom:entry s-ramp:derived="false">
    <atom:title>sramp.sh</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="alternate" type="application/x-sh" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
    <atom:category label="Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:22:01.953-04:00</atom:updated>
    <atom:id>0f6f9b6b-9952-4059-ab70-7ee3442ddcf0</atom:id>
```

```
<atom:published>2013-07-22T12:21:49.499-04:00</atom:published>
<atom:author>
  <atom:name>eric</atom:name>
</atom:author>
<atom:content src="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
  type="application/x-sh" />
</atom:entry>
<atom:entry s-ramp:derived="false">
  <atom:title>beans.xml</atom:title>
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    rel="alternate" type="application/xml" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
    rel="self" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    rel="edit-media" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
    rel="edit" type="application/atom+xml;type="entry"" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
  <atom:updated>2013-07-22T12:19:27.660-04:00</atom:updated>
  <atom:id>20474032-9536-4cef-812c-4fea432fdebd</atom:id>
  <atom:published>2013-07-22T12:19:27.644-04:00</atom:published>
  <atom:author>
    <atom:name>eric</atom:name>
  </atom:author>
  <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    type="application/xml" />
</atom:entry>
<atom:entry s-ramp:derived="false">
  <atom:title>forge.xml</atom:title>
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
    rel="alternate" type="application/xml" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
    rel="self" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
    rel="edit-media" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
```

```

        rel="edit" type="application/atom+xml;type="entry";" />
        <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
        <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
        <atom:updated>2013-07-22T12:19:25.576-04:00</atom:updated>
        <atom:id>2c21a9d3-0d09-41d8-8783-f3e795d8690d</atom:id>
        <atom:published>2013-07-22T12:19:25.555-04:00</atom:published>
        <atom:author>
            <atom:name>eric</atom:name>
        </atom:author>
        <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
            type="application/xml" />
    </atom:entry>
    <atom:entry s-ramp:derived="false">
        <atom:title>route.xml</atom:title>
        <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
            rel="alternate" type="application/xml" />
        <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
            rel="self" type="application/atom+xml;type="entry";" />
        <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
            rel="edit-media" type="application/atom+xml;type="entry";" />
        <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
            rel="edit" type="application/atom+xml;type="entry";" />
        <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
        <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
        <atom:updated>2013-07-22T12:19:25.602-04:00</atom:updated>
        <atom:id>5b653bfe-4f58-451e-b738-394e61c0c5f9</atom:id>
        <atom:published>2013-07-22T12:19:25.577-04:00</atom:published>
        <atom:author>
            <atom:name>eric</atom:name>
        </atom:author>
        <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
            type="application/xml" />
    </atom:entry>
    <atom:entry s-ramp:derived="false">
        <atom:title>beans.xml</atom:title>
        <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
            rel="alternate" type="application/xml" />

```

```
<atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
    rel="self" type="application/atom+xml;type="entry"" />
<atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
    rel="edit-media" type="application/atom+xml;type="entry"" />
<atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
    rel="edit" type="application/atom+xml;type="entry"" />
<atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
<atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
<atom:updated>2013-07-22T12:19:21.498-04:00</atom:updated>
<atom:id>a3f9d4d7-0f95-4219-85f6-84df445ef270</atom:id>
<atom:published>2013-07-22T12:19:21.376-04:00</atom:published>
<atom:author>
    <atom:name>eric</atom:name>
</atom:author>
<atom:content src="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
    type="application/xml" />
</atom:entry>
</atom:feed>
```

5.2.7.3. API: Query (GET)

```
/s-ramp
```

Performs an S-RAMP query and returns an Atom feed containing the matching artifacts.

HTTP Method	Request	Response
GET	N/A	Atom Feed

This endpoint is used to perform an S-RAMP query and return an Atom Feed of the results. Ordering and paging is supported. The query and other parameters are passed as query params in the request. The feed contains Atom summary Entries - one for each artifact in the feed.

Example Request

```
GET /s-ramp?query=/s-ramp/core/Document HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
```

```

<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="5">
  <atom:title>S-RAMP Feed</atom:title>
  <atom:subtitle>Ad Hoc query feed</atom:subtitle>
  <atom:updated>2013-07-22T12:50:16.605-04:00</atom:updated>
  <atom:id>1647967f-a6f4-4e9c-82d3-ac422fb152f3</atom:id>
  <atom:author>
    <atom:name>anonymous</atom:name>
  </atom:author>
  <atom:entry s-ramp:derived="false">
    <atom:title>sramp.sh</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="alternate" type="application/x-sh" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
    <atom:category label="Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:22:01.953-04:00</atom:updated>
    <atom:id>0f6f9b6b-9952-4059-ab70-7ee3442ddcf0</atom:id>
    <atom:published>2013-07-22T12:21:49.499-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      type="application/x-sh" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>beans.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"

```

```

        rel="edit-media" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
        rel="edit" type="application/atom+xml;type="entry";" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:27.660-04:00</atom:updated>
    <atom:id>20474032-9536-4cef-812c-4fea432fdebd</atom:id>
    <atom:published>2013-07-22T12:19:27.644-04:00</atom:published>
    <atom:author>
        <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
        type="application/xml" />
</atom:entry>
<atom:entry s-ramp:derived="false">
    <atom:title>forge.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
        rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
        rel="self" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
        rel="edit-media" type="application/atom+xml;type="entry";" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
        rel="edit" type="application/atom+xml;type="entry";" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:25.576-04:00</atom:updated>
    <atom:id>2c21a9d3-0d09-41d8-8783-f3e795d8690d</atom:id>
    <atom:published>2013-07-22T12:19:25.555-04:00</atom:published>
    <atom:author>
        <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
        type="application/xml" />
</atom:entry>
<atom:entry s-ramp:derived="false">
    <atom:title>route.xml</atom:title>

```

```

    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:25.602-04:00</atom:updated>
    <atom:id>5b653bfe-4f58-451e-b738-394e61c0c5f9</atom:id>
    <atom:published>2013-07-22T12:19:25.577-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>beans.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:21.498-04:00</atom:updated>
    <atom:id>a3f9d4d7-0f95-4219-85f6-84df445ef270</atom:id>
    <atom:published>2013-07-22T12:19:21.376-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>

```

```
</atom:author>
  <atom:content src="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
    type="application/xml" />
</atom:entry>
</atom:feed>
```

5.2.7.4. API: Query (POST)

```
/s-ramp
```

Performs an S-RAMP query and returns an Atom feed containing the matching artifacts.

HTTP Method	Request	Response
POST	FormData	Atom Feed

This endpoint is used to perform an S-RAMP query and return an Atom Feed of the results. Ordering and paging is supported. The query and other parameters are passed as form data params in the request body. The feed contains Atom summary Entries - one for each artifact in the feed.

Example Request

```
POST /s-ramp HTTP/1.1

--ac709f11-bfc5-48df-8918-e58b254d0490
Content-Disposition: form-data; name="query"
Content-Type: text/plain

core/Document
--ac709f11-bfc5-48df-8918-e58b254d0490
Content-Disposition: form-data; name="startIndex"
Content-Type: text/plain

0
--ac709f11-bfc5-48df-8918-e58b254d0490
Content-Disposition: form-data; name="count"
Content-Type: text/plain

100
--ac709f11-bfc5-48df-8918-e58b254d0490
Content-Disposition: form-data; name="orderBy"
Content-Type: text/plain

uuid
--ac709f11-bfc5-48df-8918-e58b254d0490
Content-Disposition: form-data; name="ascending"
```


Content-Type: text/plain

true

--ac709f11-bfc5-48df-8918-e58b254d0490--

Example Response

HTTP/1.1 200 OK

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="5">
  <atom:title>S-RAMP Feed</atom:title>
  <atom:subtitle>Ad Hoc query feed</atom:subtitle>
  <atom:updated>2013-07-22T12:50:16.605-04:00</atom:updated>
  <atom:id>1647967f-a6f4-4e9c-82d3-ac422fb152f3</atom:id>
  <atom:author>
    <atom:name>anonymous</atom:name>
  </atom:author>
  <atom:entry s-ramp:derived="false">
    <atom:title>sramp.sh</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="alternate" type="application/x-sh" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="Document" scheme="x-s-ramp:2013:type"
term="Document" />
    <atom:category label="Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:22:01.953-04:00</atom:updated>
    <atom:id>0f6f9b6b-9952-4059-ab70-7ee3442ddcf0</atom:id>
    <atom:published>2013-07-22T12:21:49.499-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
Document/0f6f9b6b-9952-4059-ab70-7ee3442ddcf0/media"
      type="application/x-sh" />
  </atom:entry>
```

```
<atom:entry s-ramp:derived="false">
  <atom:title>beans.xml</atom:title>
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    rel="alternate" type="application/xml" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
    rel="self" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    rel="edit-media" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd"
    rel="edit" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
  <atom:updated>2013-07-22T12:19:27.660-04:00</atom:updated>
  <atom:id>20474032-9536-4cef-812c-4fea432fdebd</atom:id>
  <atom:published>2013-07-22T12:19:27.644-04:00</atom:published>
  <atom:author>
    <atom:name>eric</atom:name>
  </atom:author>
  <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/20474032-9536-4cef-812c-4fea432fdebd/media"
    type="application/xml" />
</atom:entry>
<atom:entry s-ramp:derived="false">
  <atom:title>forge.xml</atom:title>
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
    rel="alternate" type="application/xml" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
    rel="self" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
    rel="edit-media" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d"
    rel="edit" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
  <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
  <atom:updated>2013-07-22T12:19:25.576-04:00</atom:updated>
  <atom:id>2c21a9d3-0d09-41d8-8783-f3e795d8690d</atom:id>
  <atom:published>2013-07-22T12:19:25.555-04:00</atom:published>
```

```

    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/2c21a9d3-0d09-41d8-8783-f3e795d8690d/media"
      type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>route.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:25.602-04:00</atom:updated>
    <atom:id>5b653bfe-4f58-451e-b738-394e61c0c5f9</atom:id>
    <atom:published>2013-07-22T12:19:25.577-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/
XmlDocument/5b653bfe-4f58-451e-b738-394e61c0c5f9/media"
      type="application/xml" />
  </atom:entry>
  <atom:entry s-ramp:derived="false">
    <atom:title>beans.xml</atom:title>
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="alternate" type="application/xml" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link href="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270"
      rel="edit" type="application/atom+xml;type="entry"" />

```

```

    <atom:category label="XML Document" scheme="x-s-ramp:2013:type"
term="XmlDocument" />
    <atom:category label="XML Document" scheme="x-s-ramp:2013:model"
term="core" />
    <atom:updated>2013-07-22T12:19:21.498-04:00</atom:updated>
    <atom:id>a3f9d4d7-0f95-4219-85f6-84df445ef270</atom:id>
    <atom:published>2013-07-22T12:19:21.376-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:content src="http://localhost:8080/s-ramp/core/XmlDocument/
a3f9d4d7-0f95-4219-85f6-84df445ef270/media"
      type="application/xml" />
  </atom:entry>
</atom:feed>

```

5.2.7.5. API: Batch Processing

/s-ramp

Performs an S-RAMP query and returns an Atom feed containing the matching artifacts.

HTTP Method	Request	Response
POST	multipart/form-data	Atom Feed

This endpoint is used to perform an S-RAMP query and return an Atom Feed of the results. Ordering and paging is supported. The query and other parameters are passed as form data params in the request body. The feed contains Atom summary Entries - one for each artifact in the feed.

Example Request

```
POST XX_TBD_XX HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```
XX_TBD_XX
```

5.2.8. Stored Queries

S-RAMP queries can be utilized through the "stored query" concept. The query is persisted within the S-RAMP repository and can be repeatedly executed by name.

5.2.8.1. API: Create Stored Query

/s-ramp/query

Creates a new stored query in the repository. The body of the request must be the stored query, wrapped as an Atom Entry. The response is also an Atom Entry containing additional, server-generated meta-data.

HTTP Method	Request	Response
POST	Atom Entry	Atom Entry

Example Request

```
POST /s-ramp/query HTTP/1.1

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:entry xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:atom="http://
www.w3.org/2005/Atom">
  <s-ramp:storedQueryData>
    <s-ramp:queryName>FooQuery</s-ramp:queryName>
    <s-ramp:queryString>/s-ramp/ext/FooType</s-ramp:queryString>
    <s-ramp:propertyName>importantProperty1</s-ramp:propertyName>
    <s-ramp:propertyName>importantProperty2</s-ramp:propertyName>
  </s-ramp:storedQueryData>
</atom:entry>
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:entry xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:atom="http://
www.w3.org/2005/Atom">
  <atom:title>Stored Query: FooQuery</atom:title>
  <atom:link href="http://localhost:9093/s-ramp-server/s-ramp/query/
FooQuery"
    rel="self" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:9093/s-ramp-server/s-ramp/query/
FooQuery"
    rel="edit" type="application/atom+xml;type="entry"" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery/results"
    rel="urn:x-s-ramp:2013:query:results" type="application/atom
+xml;type="feed"" />
  <atom:category label="Stored Query Entry" scheme="urn:x-s-ramp:2013:type"
```

```
term="query" />
<atom:id>urn:uuid:FooQuery</atom:id>
<atom:content>Stored Query Entry</atom:content>
<s-ramp:storedQueryData>
  <s-ramp:queryName>FooQuery</s-ramp:queryName>
  <s-ramp:queryString>/s-ramp/ext/FooType</s-ramp:queryString>
  <s-ramp:propertyName>importantProperty1</s-ramp:propertyName>
  <s-ramp:propertyName>importantProperty2</s-ramp:propertyName>
</s-ramp:storedQueryData>
</atom:entry>
```

5.2.8.2. API: Update Stored Query

```
/s-ramp/query/{queryName}
```

Updates the given stored query in the repository. The body of the request is the same Atom Entry as in [Create Stored Query](#).

HTTP Method	Request	Response
PUT	Atom Entry	N/A

5.2.8.3. API: List Stored Queries

```
/s-ramp/query
```

Retrieves all stored queries from the repository.

HTTP Method	Request	Response
GET	N/A	Atom Feed

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:feed xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:atom="http://
www.w3.org/2005/Atom">
  <atom:title>S-RAMP stored queries feed</atom:title>
  <atom:updated>2014-09-25T16:45:10.133-04:00</atom:updated>
  <atom:entry>
    <atom:title>Stored Query: FooQuery</atom:title>
    <atom:link
      href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery"
      rel="self" type="application/atom+xml;type="entry" />
```

```

<atom:link
  href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery"
  rel="edit" type="application/atom+xml;type="entry";" />
<atom:link
  href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery/
results"
  rel="urn:x-s-ramp:2013:query:results" type="application/atom
+xml;type="feed";" />
  <atom:category label="Stored Query Entry" scheme="urn:x-s-
ramp:2013:type"
    term="query" />
  <atom:id>urn:uuid:FooQuery</atom:id>
  <atom:content>Stored Query Entry</atom:content>
  <s-ramp:storedQueryData>
    <s-ramp:queryName>FooQuery</s-ramp:queryName>
    <s-ramp:queryString>/s-ramp/ext/FooType</s-ramp:queryString>
    <s-ramp:propertyName>importantProperty1</s-ramp:propertyName>
    <s-ramp:propertyName>importantProperty2</s-ramp:propertyName>
  </s-ramp:storedQueryData>
</atom:entry>
<atom:entry>
  <atom:title>Stored Query: FooQuery2</atom:title>
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery2"
    rel="self" type="application/atom+xml;type="entry";" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery2"
    rel="edit" type="application/atom+xml;type="entry";" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery2/
results"
    rel="urn:x-s-ramp:2013:query:results" type="application/atom
+xml;type="feed";" />
    <atom:category label="Stored Query Entry" scheme="urn:x-s-
ramp:2013:type"
      term="query" />
    <atom:id>urn:uuid:FooQuery2</atom:id>
    <atom:content>Stored Query Entry</atom:content>
    <s-ramp:storedQueryData>
      <s-ramp:queryName>FooQuery2</s-ramp:queryName>
      <s-ramp:queryString>/s-ramp/ext/FooType</s-ramp:queryString>
    </s-ramp:storedQueryData>
  </atom:entry>
</atom:feed>

```

5.2.8.4. API: Get Stored Query

```
/s-ramp/query/{queryName}
```

Retrieves the given stored query from the repository.

HTTP Method	Request	Response
GET	N/A	Atom Entry

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:entry xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:atom="http://
www.w3.org/2005/Atom">
  <atom:title>Stored Query: FooQuery</atom:title>
  <atom:link href="http://localhost:9093/s-ramp-server/s-ramp/query/
FooQuery"
    rel="self" type="application/atom+xml;type="entry"" />
  <atom:link href="http://localhost:9093/s-ramp-server/s-ramp/query/
FooQuery"
    rel="edit" type="application/atom+xml;type="entry"" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/query/FooQuery/results"
    rel="urn:x-s-ramp:2013:query:results" type="application/atom
+xml;type="feed"" />
  <atom:category label="Stored Query Entry" scheme="urn:x-s-ramp:2013:type"
    term="query" />
  <atom:id>urn:uuid:FooQuery</atom:id>
  <atom:content>Stored Query Entry</atom:content>
  <s-ramp:storedQueryData>
    <s-ramp:queryName>FooQuery</s-ramp:queryName>
    <s-ramp:queryString>/s-ramp/ext/FooType</s-ramp:queryString>
    <s-ramp:propertyName>importantProperty1</s-ramp:propertyName>
    <s-ramp:propertyName>importantProperty2</s-ramp:propertyName>
  </s-ramp:storedQueryData>
</atom:entry>
```

5.2.8.5. API: Execute Stored Query

```
/s-ramp/query/{queryName}/results
```

Similar to a normal, ad-hoc [Query](#), this returns an Atom Feed of artifact entries.

HTTP Method	Request	Response
GET	N/A	Atom Feed

Example Request

```
GET /s-ramp-server/s-ramp/query/FooQuery/results?
startIndex=0&count=20&orderBy=name&ascending=true HTTP/1.1
```

Note that the paging and ordering parameters are optional and have reasonable defaults (defaults are shown values).

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<atom:feed xmlns:s-ramp="http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  xmlns:xlink="http://www.w3.org/1999/xlink" xmlns:atom="http://
www.w3.org/2005/Atom"
  s-ramp:provider="JBoss Overlord" s-ramp:itemsPerPage="20"
  s-ramp:startIndex="0" s-ramp:totalResults="2">
  <atom:title>S-RAMP Feed</atom:title>
  <atom:subtitle>Ad Hoc query feed</atom:subtitle>
  <atom:updated>2014-09-25T17:03:32.504-04:00</atom:updated>
  <atom:id>b4746dcd-82b9-433a-9d61-e54a384ae4e6</atom:id>
  <atom:author>
    <atom:name>anonymous</atom:name>
  </atom:author>
  <atom:entry s-ramp:derived="false" s-ramp:extendedType="FooType">
    <atom:title>FooArtifact</atom:title>
    <atom:link
      href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/
f57c30d3-9a9a-4df9-b362-8f0b0816af99"
      rel="self" type="application/atom+xml;type="entry"" />
    <atom:link
      href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/
f57c30d3-9a9a-4df9-b362-8f0b0816af99/media"
      rel="edit-media" type="application/atom+xml;type="entry"" />
    <atom:link
      href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/
f57c30d3-9a9a-4df9-b362-8f0b0816af99"
      rel="edit" type="application/atom+xml;type="entry"" />
    <atom:category label="Extended Artifact Type" scheme="x-s-
ramp:2013:type"
      term="FooType" />
    <atom:category label="Extended Artifact Type" scheme="x-s-
ramp:2013:model"
      term="ext" />
    <atom:updated>2014-09-25T17:03:27.392-04:00</atom:updated>
    <atom:id>f57c30d3-9a9a-4df9-b362-8f0b0816af99</atom:id>
    <atom:published>2014-09-25T17:03:27.392-04:00</atom:published>
    <atom:author>
```

```

    <atom:name>asdf</atom:name>
  </atom:author>
  <s-ramp:artifact>
    <s-ramp:ExtendedArtifactType />
  </s-ramp:artifact>
</atom:entry>
<atom:entry s-ramp:derived="false" s-ramp:extendedType="FooType">
  <atom:title>FooArtifact2</atom:title>
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/e8b6aaf2-
d787-45d0-a534-b9205d6e8815"
    rel="self" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/e8b6aaf2-
d787-45d0-a534-b9205d6e8815/media"
    rel="edit-media" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:link
    href="http://localhost:9093/s-ramp-server/s-ramp/ext/FooType/e8b6aaf2-
d787-45d0-a534-b9205d6e8815"
    rel="edit" type="application/atom+xml;type=&quot;entry&quot;" />
  <atom:category label="Extended Artifact Type" scheme="x-s-
ramp:2013:type"
    term="FooType" />
  <atom:category label="Extended Artifact Type" scheme="x-s-
ramp:2013:model"
    term="ext" />
  <atom:updated>2014-09-25T17:03:29.580-04:00</atom:updated>
  <atom:id>e8b6aaf2-d787-45d0-a534-b9205d6e8815</atom:id>
  <atom:published>2014-09-25T17:03:29.580-04:00</atom:published>
  <atom:author>
    <atom:name>asdf</atom:name>
  </atom:author>
  <s-ramp:artifact>
    <s-ramp:ExtendedArtifactType />
  </s-ramp:artifact>
</atom:entry>
</atom:feed>
```

5.2.8.6. API: Delete Stored Query

```

/s-ramp/query/{queryName}
```

Deletes the given stored query from the repository.

HTTP Method	Request	Response
DELETE	N/A	N/A

5.3. Ontologies

5.3.1. API: Add Ontology

`/s-ramp/ontology`

Adds a new ontology (*.owl file) to the repository. This allows artifacts to be classified using the classes defined in the ontology.

HTTP Method	Request	Response
POST	application/rdf+xml	Atom Entry

This endpoint is used to add an ontology to the repository. The body of the request must be the OWL Lite formatted ontology (see the S-RAMP specification for more details). The response is an Atom Entry containing meta-data about the ontology, most importantly the UUID of the ontology (which can be later used to update or delete it).

Example Request

```
POST /s-ramp/ontology HTTP/1.1

<?xml version="1.0" encoding="UTF-8"?>
<rdf:RDF xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:owl="http://www.w3.org/2002/07/owl#"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xml:base="http://www.example.org/sample-ontology-1.owl">

  <owl:Ontology rdf:ID="SampleOntology1">
    <rdfs:label>Sample Ontology 1</rdfs:label>
    <rdfs:comment>A sample ontology.</rdfs:comment>
  </owl:Ontology>

  <owl:Class rdf:ID="All">
    <rdfs:label>All</rdfs:label>
  </owl:Class>

  <owl:Class rdf:ID="King">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-ontology-1.owl#All" />
    <rdfs:label>King</rdfs:label>
    <rdfs:comment>Feudal ruler.</rdfs:comment>
  </owl:Class>

  <owl:Class rdf:ID="Imperator">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-ontology-1.owl#All" />
```

```
<rdfs:label>Imperator</rdfs:label>
<rdfs:comment>Roman ruler.</rdfs:comment>
</owl:Class>

<owl:Class rdf:ID="Baron">
  <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#King" />
  <rdfs:label>Baron</rdfs:label>
</owl:Class>
<owl:Class rdf:ID="Rex">
  <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Imperator" />
  <rdfs:label>Imperator</rdfs:label>
</owl:Class>

<owl:Class rdf:ID="Knight">
  <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Baron" />
  <rdfs:label>Knight</rdfs:label>
</owl:Class>
<owl:Class rdf:ID="Dux">
  <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Rex" />
  <rdfs:label>Dux</rdfs:label>
</owl:Class>

</rdf:RDF>
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:entry xmlns="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:atom="http://www.w3.org/2005/Atom"
  xmlns:ns2="http://www.w3.org/1999/02/22-rdf-syntax-ns#" xmlns:ns3="http://
www.w3.org/2002/07/owl#">
  <atom:title>Sample Ontology 1</atom:title>
  <atom:id>e8fe74f3-c9c3-4678-ba76-d71158141ddd</atom:id>
  <atom:author />
  <atom:summary>A sample ontology.</atom:summary>
  <ns2:RDF xml:base="http://www.example.org/sample-ontology-1.owl">
    <ns3:Ontology ns2:ID="SampleOntology1">
      <label>Sample Ontology 1</label>
      <comment>A sample ontology.</comment>
    </ns3:Ontology>
    <ns3:Class ns2:ID="All">
      <label>All</label>
    </ns3:Class>
```

```

<ns3:Class ns2:ID="King">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#All" />
  <label>King</label>
  <comment>Feudal ruler.</comment>
</ns3:Class>
<ns3:Class ns2:ID="Imperator">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#All" />
  <label>Imperator</label>
  <comment>Roman ruler.</comment>
</ns3:Class>
<ns3:Class ns2:ID="Baron">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#King" />
  <label>Baron</label>
</ns3:Class>
<ns3:Class ns2:ID="Knight">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#Baron" />
  <label>Knight</label>
</ns3:Class>
<ns3:Class ns2:ID="Rex">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#Imperator" />
  <label>Imperator</label>
</ns3:Class>
<ns3:Class ns2:ID="Dux">
  <subClassOf ns2:resource="http://www.example.org/sample-
ontology-1.owl#Rex" />
  <label>Dux</label>
</ns3:Class>
</ns2:RDF>
</atom:entry>

```

5.3.2. API: List Ontologies

```
/s-ramp/ontology
```

Retrieves, as an Atom feed, all ontologies currently known to the repository.

HTTP Method	Request	Response
GET	N/A	Atom Feed

This endpoint is used to retrieve all ontologies known to the repository as an Atom Feed of Entries, with one Entry for each ontology. Full information about the ontology can subsequently be retrieved by calling the Get Ontology endpoint.

Example Request

```
GET /s-ramp/ontology HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom">
  <atom:title>S-RAMP ontology feed</atom:title>
  <atom:updated>2013-07-23T10:58:40.356-04:00</atom:updated>
  <atom:entry>
    <atom:title>Sample Ontology 1</atom:title>
    <atom:updated>2013-07-23T10:56:50.410-04:00</atom:updated>
    <atom:id>e8fe74f3-c9c3-4678-ba76-d71158141ddd</atom:id>
    <atom:published>2013-07-23T10:56:50.410-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:source xml:base="http://www.example.org/sample-ontology-1.owl">
      <atom:id>SampleOntology1</atom:id>
    </atom:source>
    <atom:summary>A sample ontology.</atom:summary>
  </atom:entry>
  <atom:entry>
    <atom:title>Animal Kingdom</atom:title>
    <atom:updated>2013-07-23T10:58:37.737-04:00</atom:updated>
    <atom:id>fd0e5210-2567-409f-8df0-f851e1ce630d</atom:id>
    <atom:published>2013-07-23T10:58:37.737-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:source xml:base="http://www.example.org/sample-ontology-2.owl">
      <atom:id>AnimalKingdom</atom:id>
    </atom:source>
    <atom:summary>Animal Kingdom Ontology</atom:summary>
  </atom:entry>
</atom:feed>
```

5.3.3. API: Update Ontology

```
/s-ramp/ontology/{uuid}
```

Updates an existing ontology by its UUID.

HTTP Method	Request	Response
PUT	application/rdf+xml	N/A

This endpoint is used to update a single ontology in the repository. The request body must be a new version of the ontology in OWL Lite RDF format. Note that this might fail if the ontology changes in an incompatible way (e.g. a class is removed that is currently in use).

Example Request

```
PUT /s-ramp/ontology/fd0e5210-2567-409f-8df0-f851e1ce630d HTTP/1.1

<?xml version="1.0" encoding="UTF-8"?>
<rdf:RDF xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:owl="http://www.w3.org/2002/07/owl#"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xml:base="http://www.example.org/sample-ontology-1.owl">

  <owl:Ontology rdf:ID="SampleOntology1">
    <rdfs:label>Sample Ontology 1</rdfs:label>
    <rdfs:comment>A sample ontology.</rdfs:comment>
  </owl:Ontology>

  <owl:Class rdf:ID="All">
    <rdfs:label>All</rdfs:label>
  </owl:Class>

  <owl:Class rdf:ID="King">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-ontology-1.owl#All" />
    <rdfs:label>King</rdfs:label>
    <rdfs:comment>Feudal ruler.</rdfs:comment>
  </owl:Class>

  <owl:Class rdf:ID="Imperator">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-ontology-1.owl#All" />
    <rdfs:label>Imperator</rdfs:label>
    <rdfs:comment>Roman ruler.</rdfs:comment>
  </owl:Class>

  <owl:Class rdf:ID="Baron">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-ontology-1.owl#King" />
    <rdfs:label>Baron</rdfs:label>
  </owl:Class>

  <owl:Class rdf:ID="Rex">
```

```

    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Imperator" />
    <rdfs:label>Imperator</rdfs:label>
  </owl:Class>

  <owl:Class rdf:ID="Knight">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Baron" />
    <rdfs:label>Knight</rdfs:label>
  </owl:Class>
  <owl:Class rdf:ID="Dux">
    <rdfs:subClassOf rdf:resource="http://www.example.org/sample-
ontology-1.owl#Rex" />
    <rdfs:label>Dux</rdfs:label>
  </owl:Class>

</rdf:RDF>

```

Example Response

```
HTTP/1.1 200 OK
```

5.3.4. API: Get Ontology

```
/s-ramp/ontology/{uuid}
```

Returns the OWL representation of an ontology (wrapped in an Atom Entry).

HTTP Method	Request	Response
GET	N/A	Atom Entry

This endpoint is used to get the full ontology (by its UUID) in OWL Lite (RDF) format, wrapped in an Atom Entry. The response body is an Atom Entry with a single extension element that is the ontology RDF. This will fail if no ontology exists with the given UUID.

Example Request

```
GET /s-ramp/ontology/fd0e5210-2567-409f-8df0-f851e1ce630d HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:entry xmlns="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:atom="http://www.w3.org/2005/Atom"

```



```

xmlns:ns2="http://www.w3.org/1999/02/22-rdf-syntax-ns#" xmlns:ns3="http://
www.w3.org/2002/07/owl#">
<atom:title>Animal Kingdom</atom:title>
<atom:updated>2013-07-23T10:58:37.737-04:00</atom:updated>
<atom:id>fd0e5210-2567-409f-8df0-f851e1ce630d</atom:id>
<atom:published>2013-07-23T10:58:37.737-04:00</atom:published>
<atom:author>
  <atom:name>eric</atom:name>
</atom:author>
<atom:summary>Animal Kingdom Ontology</atom:summary>
<ns2:RDF xml:base="http://www.example.org/sample-ontology-2.owl">
  <ns3:Ontology ns2:ID="AnimalKingdom">
    <label>Animal Kingdom</label>
    <comment>Animal Kingdom Ontology</comment>
  </ns3:Ontology>
  <ns3:Class ns2:ID="Animal">
    <label>Animal</label>
    <comment>All animals.</comment>
  </ns3:Class>
  <ns3:Class ns2:ID="UnicellularAnimal">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#Animal" />
    <label>Unicellular Animal</label>
    <comment>Single-celled animal.</comment>
  </ns3:Class>
  <ns3:Class ns2:ID="MulticellularAnimal">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#Animal" />
    <label>Multicellular Animal</label>
    <comment>Multi-celled animal.</comment>
  </ns3:Class>
  <ns3:Class ns2:ID="Protozoa">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#UnicellularAnimal" />
    <label>Protozoa</label>
  </ns3:Class>
  <ns3:Class ns2:ID="Metazoa">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#MulticellularAnimal" />
    <label>Metazoa</label>
  </ns3:Class>
  <ns3:Class ns2:ID="Invertebrate">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#Metazoa" />
    <label>Invertebrate</label>
  </ns3:Class>
  <ns3:Class ns2:ID="Vertebrate">
    <subClassOf ns2:resource="http://www.example.org/sample-
ontology-2.owl#Metazoa" />

```

```
<label>Vertebrate</label>
</ns3:Class>
</ns2:RDF>
</atom:entry>
```

5.3.5. API: Delete Ontology

```
/s-ramp/ontology/{uuid}
```

Deletes an ontology from the repository.

<i>HTTP Method</i>	<i>Request</i>	<i>Response</i>
DELETE	N/A	N/A

This endpoint is used to delete a single ontology from the repository. This might fail if the ontology is currently in-use (at least one artifact is classified by at least one class defined by the ontology).

Example Request

```
DELETE /s-ramp/ontology/fd0e5210-2567-409f-8df0-f851e1ce630d HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

5.4. Auditing

5.4.1. API: Get Artifact Audit History

```
/s-ramp/audit/artifact/{artifactUuid}
```

Retrieves an Atom feed containing all of the audit entries for a single artifact.

<i>HTTP Method</i>	<i>Request</i>	<i>Response</i>
GET	N/A	Atom Feed

This endpoint is used to get a feed of the audit history of a single artifact. The request URL can include standard paging parameters. The response is an Atom Feed where each Entry in the feed represents a single audit event in the history of the artifact. A followup call must be made to the Get Artifact Audit Entry endpoint in order to retrieve full detail information about the audit event. This call might fail if no artifact exists with the given UUID.

Example Request

```
GET /s-ramp/audit/artifact/b086c558-58d6-4837-bb38-6c3da760ae80 HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK
```

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="2">
  <atom:title>S-RAMP Audit Feed</atom:title>
  <atom:subtitle>All Audit Entries for Artifact</atom:subtitle>
  <atom:updated>2013-07-23T11:14:07.189-04:00</atom:updated>
  <atom:id>bff03dd5-e55c-4528-b1aa-eeleb471b899</atom:id>
  <atom:entry>
    <atom:title>artifact:update</atom:title>
    <atom:updated>2013-07-23T11:14:03.225-04:00</atom:updated>
    <atom:id>2947f90e-0f5a-4099-b3dc-29124c96c7d0</atom:id>
    <atom:published>2013-07-23T11:14:03.225-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:summary />
  </atom:entry>
  <atom:entry>
    <atom:title>artifact:add</atom:title>
    <atom:updated>2013-07-23T11:13:28.513-04:00</atom:updated>
    <atom:id>e41404b3-9ec6-43f5-a6d8-aa6089bc6704</atom:id>
    <atom:published>2013-07-23T11:13:28.513-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:summary />
  </atom:entry>
</atom:feed>
```

5.4.2. API: Get User Audit History

```
/s-ramp/audit/user/{username}
```

Retrieves an Atom feed containing all of the audit entries for a specific user.

HTTP Method	Request	Response
GET	N/A	Atom Feed

This endpoint is used to get a feed of the audit history for a single user. The request URL can include standard paging parameters. The response is an Atom Feed where each Entry in the feed represents a single audit event in the history of the artifact. A followup call must be made to the Get Artifact Audit Entry endpoint in order to retrieve full detail information about the audit event. This call might fail if no user exists with the given username.

Example Request

```
GET /s-ramp/audit/user/eric HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<atom:feed xmlns:atom="http://www.w3.org/2005/Atom" xmlns:s-ramp="http://
docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0"
  s-ramp:itemsPerPage="100" s-ramp:provider="JBoss Overlord" s-
ramp:startIndex="0" s-ramp:totalResults="2">
  <atom:title>S-RAMP Audit Feed</atom:title>
  <atom:subtitle>All Audit Entries for Artifact</atom:subtitle>
  <atom:updated>2013-07-23T11:16:00.545-04:00</atom:updated>
  <atom:id>d49057a2-2f84-48aa-9c79-078b1e86680a</atom:id>
  <atom:entry>
    <atom:title>artifact:update</atom:title>
    <atom:updated>2013-07-23T11:14:03.225-04:00</atom:updated>
    <atom:id>2947f90e-0f5a-4099-b3dc-29124c96c7d0</atom:id>
    <atom:published>2013-07-23T11:14:03.225-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:summary />
  </atom:entry>
  <atom:entry>
    <atom:title>artifact:add</atom:title>
    <atom:updated>2013-07-23T11:13:28.513-04:00</atom:updated>
    <atom:id>e41404b3-9ec6-43f5-a6d8-aa6089bc6704</atom:id>
    <atom:published>2013-07-23T11:13:28.513-04:00</atom:published>
    <atom:author>
      <atom:name>eric</atom:name>
    </atom:author>
    <atom:summary />
  </atom:entry>
</atom:feed>
```

5.4.3. API: Add Artifact Audit Entry

```
/s-ramp/audit/artifact/{artifactUuid}
```

Adds a user-defined (custom) audit entry to an artifact.

HTTP Method	Request	Response
POST	application/ auditEntry +xml	Atom Entry

This endpoint is used to add a custom audit entry to a particular artifact. The request must be a POST of an XML document conforming to the audit schema type *auditEntry*. This call may fail if no artifact exists with the given UUID.

Example Request

```
POST /s-ramp/audit/artifact/b086c558-58d6-4837-bb38-6c3da760ae80 HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK

<auditEntry type="custom:foo" uuid="" when="" who="">
  <auditItem type="custom:item-type-1">
    <property name="my-property-1" value="some-value" />
    <property name="my-property-2" value="other-value" />
  </auditItem>
  <auditItem type="custom:item-type-2" />
</auditEntry>
```

5.4.4. API: Get Artifact Audit Entry

```
/s-ramp/audit/artifact/{artifactUuid}/{auditEntryUuid}
```

Retrieves full detailed information about a single audit entry.

HTTP Method	Request	Response
GET	N/A	Atom Entry

This endpoint is used to get the full details for a single audit event for a particular artifact. The particulars of the detailed information are specific to the type of audit entry, so *artifact create* detail information might be different from *artifact update* detail information. In addition, there is the possibility that the detail information might be from a custom audit entry added by an end user. This call might fail if the artifact does not exist or the audit entry does not exist.

Example Request

```
GET /s-ramp/audit/artifact/b086c558-58d6-4837-  
bb38-6c3da760ae80/2947f90e-0f5a-4099-b3dc-29124c96c7d0 HTTP/1.1
```

Example Response

```
HTTP/1.1 200 OK  
  
<?xml version="1.0" encoding="UTF-8" standalone="no"?>  
<atom:entry xmlns="http://downloads.jboss.org/overlord/sramp/2013/  
auditing.xsd" xmlns:atom="http://www.w3.org/2005/Atom">  
  <atom:title>artifact:update</atom:title>  
  <atom:updated>2013-07-23T11:14:03.225-04:00</atom:updated>  
  <atom:id>2947f90e-0f5a-4099-b3dc-29124c96c7d0</atom:id>  
  <atom:published>2013-07-23T11:14:03.225-04:00</atom:published>  
  <atom:author>  
    <atom:name>eric</atom:name>  
  </atom:author>  
  <atom:summary />  
  <auditEntry type="artifact:update" uuid="2947f90e-0f5a-4099-  
b3dc-29124c96c7d0" when="2013-07-23T11:14:03.225-04:00"  
    who="eric">  
    <auditItem type="property:added">  
      <property name="sramp-properties:foo" value="bar" />  
      <property name="sramp-properties:hello" value="world" />  
    </auditItem>  
    <auditItem type="property:changed" />  
    <auditItem type="property:removed" />  
  </auditEntry>  
</atom:entry>
```

Chapter 6. Clients

6.1. Java Client

The Overlord S-RAMP implementation provides a full-featured Java client library that can be used to integrate with S-RAMP compliant servers. This section of the guide describes how to use this library.

6.1.1. Basic Usage

The S-RAMP client is a simple Java based client library and can be included in a Maven project by including the following pom.xml dependency:

```
<dependency>
  <groupId>org.overlord.sramp</groupId>
  <artifactId>s-ramp-client</artifactId>
  <version>${sramp.client.version}</version>
</dependency>
```

Once the library is included in your project, you can use the client by instantiating the **SrampAtomApiClient** class. Note that the client class supports pluggable authentication mechanisms, although BASIC auth is a simple matter of including the username and password upon construction of the client.

Please refer to the javadoc of that class for details, but here are some usage examples to help you get started (code simplified for readability):

Upload an XSD document to S-RAMP.

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);
String artifactFileName = getXSDArtifactName();
InputStream is = getXSDArtifactContentStream();
ArtifactType type = ArtifactType.XsdDocument();
BaseArtifactType artifact =
    client.uploadArtifact(ArtifactType.XsdDocument(), is, artifactFileName);
```

Create a custom artifact in S-RAMP (meta-data only, no file content).

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);
ExtendedArtifactType artifact = new ExtendedArtifactType();
artifact.setArtifactType(BaseArtifactEnum.EXTENDED_ARTIFACT_TYPE);
artifact.setExtendedType("MyArtifactType");
artifact.setName("My Test Artifact #1");
artifact.setDescription("Description of my test artifact.");
BaseArtifactType createdArtifact = client.createArtifact(artifact);
```

Retrieve full meta-data for an XSD artifact by its UUID.

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);
String uuid = getArtifactUUID();
BaseArtifactType metaData =
    client.getArtifactMetaData(ArtifactType.XsdDocument(), uuid);
```

Retrieve artifact content.

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);
String uuid = getArtifactUUID();
InputStream content = client.getArtifactContent(ArtifactType.XsdDocument(),
    uuid);
```

Query the S-RAMP repository (by artifact name).

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);
String artifactName = getArtifactName();
QueryResultSet rset = client.buildQuery("/s-ramp/xsd/XsdDocument[@name
    = ?]")
    .parameter(artifactName)
    .count(10)
    .query();
```

Query the S-RAMP repository using a stored query.

```
SrampAtomApiClient client = new SrampAtomApiClient(urlToSramp);

StoredQuery storedQuery = new StoredQuery();
storedQuery.setQueryName("FooQuery");
storedQuery.setQueryExpression("/s-ramp/ext/FooType");
storedQuery.getPropertyName().add("importantProperty1");
storedQuery.getPropertyName().add("importantProperty2");
client.createStoredQuery(storedQuery);

QueryResultSet rset =
    client.queryWithStoredQuery(storedQuery.getQueryName());
```

6.1.2. Extended Feature: Ontologies

Although the S-RAMP specification is silent on how the API should support the management of ontologies, the Overlord S-RAMP implementation provides an extension to the Atom based REST API to support this. Using any of the client's ontology related methods will work when communicating with the Overlord implementation of S-RAMP, but will likely fail when communicating with any other S-RAMP server.

The client supports adding, updating, and getting (both individual and a full list) ontologies from the S-RAMP repository.

6.1.3. Extended Feature: Auditing

The Overlord S-RAMP implementation also offers an extension to the Atom based REST API to get and set auditing information for artifacts in the repository.

6.1.4. Extending: Custom Expander

A special feature of the client is the ability to automatically expand archive style artifacts (artifacts that are JARs, WARs, ZIPs, etc). This feature is similar to how the server creates Derived content. The result is that certain files from the archive being uploaded as an S-RAMP artifact are extracted from the archive and also uploaded to the server. When this happens these "expanded" artifacts are added with an S-RAMP relationship (`expandedFromDocument`) that points to the archive artifact they were expanded from.

The Overlord S-RAMP implementation comes with a few built-in expanders (e.g. java archive, SwitchYard archive, etc). Additionally, custom expanders can be created and provided by implementing **ZipToSrampArchiveProvider**. In order to tell the client about the custom provider, put it in a JAR along with a file named:

META-INF/services/

org.overlord.sramp.atom.archive.expand.registry.ZipToSrampArchiveProvider

The contents of the file should be a single line with the fully qualified Java classname of the provider implementation.

6.1.5. Important Notes

6.1.5.1. Wildfly and EAP

When using the Java client from within a webapp running on Wildfly or EAP, the *s-ramp-client* Maven dependency carries transitive dependencies that conflict with modules on the app server. At this time, the worst known offender is *jaxb-impl* (causes a `PropertyException` related to RESTEasy's use of *NamespacePrefixMapper*). It's vital to do the following in your webapp's POM.

Exclude *jaxb-impl* from the *s-ramp-client* dependency:

```
<dependency>
  <groupId>org.overlord.sramp</groupId>
  <artifactId>s-ramp-client</artifactId>
  <version>[version]</version>

  <exclusions>
    <exclusion>
      <groupId>com.sun.xml.bind</groupId>
      <artifactId>jaxb-impl</artifactId>
    </exclusion>
  </exclusions>
</dependency>
```

Include the *com.sun.xml.bind* module in your *maven-war-plugin* *manifestEntries*:

```
<plugin>
  <artifactId>maven-war-plugin</artifactId>
  <version>2.3</version>
  <configuration>
    <archive>
      <manifestEntries>
        <Dependencies>com.sun.xml.bind, ...</Dependencies>
      </manifestEntries>
    </archive>
  </configuration>
</plugin>
```

6.2. EJB Client

The logic and actions that back all of the REST services are available for direct use through EJB, for both local server and remote client use. This should be the top choice for client interactivity where performance is a major consideration, as it removes the typical REST bottlenecks.

To use it, you'll need to add the following dependencies:

```
<dependency>
  <groupId>org.overlord.sramp</groupId>
  <artifactId>s-ramp-server-api</artifactId>
  <version>[S-RAMP VERSION]</version>
</dependency>
<dependency>
  <groupId>org.wildfly</groupId>
  <artifactId>wildfly-ejb-client-bom</artifactId>
  <version>8.2.0.Final</version>
  <type>pom</type>
  <scope>runtime</scope>
</dependency>
```

There are a couple of things to note with the dependencies. 1.) We're "cheating" and using the *wildfly-ejb-client-bom* to pull in quite a bit. With out it, you'll need the EJB API, JTA API, etc. 2.) *xercesImpl* is currently required during runtime, mostly due to *XMLGregorianCalendarImpl* use during (un)marshalling.

Then, interacting with S-RAMP is as simple as:

```
ExtendedArtifactType artifact = new ExtendedArtifactType();
artifact.setArtifactType(BaseArtifactEnum.EXTENDED_ARTIFACT_TYPE);
artifact.setExtendedType("FooArtifactType");
artifact.setName("Foo");
artifact.setDescription("I'm a Foo");
```

```

try {
    Properties jndiProps = new Properties();
    jndiProps.put(Context.INITIAL_CONTEXT_FACTORY,
        "org.jboss.naming.remote.client.InitialContextFactory");
    jndiProps.put(Context.PROVIDER_URL, "http-remoting://localhost:8080");
    jndiProps.put("jboss.naming.client.ejb.context", true);
    Context context = new InitialContext(jndiProps);

    final ArtifactService artifactService = (ArtifactService)
context.lookup(
    "s-ramp-server/ArtifactService!" +
ArtifactService.class.getName());
    artifactService.login("artificer", "artificer1!");
    artifactService.create(artifact);

    final QueryService queryService = (QueryService) context.lookup(
        "s-ramp-server/QueryService!" + QueryService.class.getName());
    queryService.login("artificer", "artificer1!");
    ArtifactSet artifactSet = queryService.query("/s-ramp/ext/
FooArtifactType");
    Iterator<BaseArtifactType> iterator = artifactSet.iterator();
    while (iterator.hasNext()) {
        BaseArtifactType artifactResult = iterator.next();
        System.out.println(artifactResult.getName());
    }
} catch (Exception e) {
    e.printStackTrace();
}

```

The complete list of services include the following. Have a look at their javadocs—the capabilities are fairly extensive. * org.overlord.sramp.server.core.api.ArtifactService *
 org.overlord.sramp.server.core.api.AuditService *
 org.overlord.sramp.server.core.api.OntologyService *
 org.overlord.sramp.server.core.api.QueryService

Note that you must call #login for each service, using the EJB/JMS username and password that you provided during installation!

6.3. JMS Client

Overlord S-RAMP publishes JMS messages to both topics and queues for several types of events. The type of event is designated by the JMSType header field. All events carry the relevant object marshalled into a JSON payload.

6.3.1. Installation and Setup

The *sramp.properties* configuration file contains multiple properties relevant to the JMS setup:

```
# S-RAMP will automatically attempt to discover a JMS ConnectionFactory
# through the literal JNDI name
# "ConnectionFactory". However, that name can be overridden here.
sramp.config.events.jms.connectionfactory = ConnectionFactory
# By default, S-RAMP publishes events through the "sramp/events/topic" JMS
# topic name (JNDI). But, it will also publish
# to any other names listed here (comma-delimited).
sramp.config.events.jms.topics = sramp/events/topic
# In addition to the above topics, S-RAMP will also publish non-expiring
# events to any JMS queue names (JNDI)
# listed here (comma-delimited).
sramp.config.events.jms.queues =
# If S-RAMP is running on a non-JavaEE server, or a server where JMS/JNDI is
# not properly configured, it will start
# an embedded ActiveMQ broker over TCP. The property controls that port.
sramp.config.events.jms.embedded-activemq-port = 61616
```

S-RAMP supports three JMS environments:

- When S-RAMP is installed in Wildfly/EAP by using our installation script, JMS is configured automatically. The existing HornetQ configuration is modified to add the default topic, described above, and all necessary credentials. Users can add additional topics/queues to their framework, then add them to *sramp.properties* (see above). IMPORTANT: In order for HornetQ to work properly, the standalone-full profile must be used (*bin/standalone.sh -c standalone-full.xml*)! Without it, errors are guaranteed to occur during startup!
- For other EE platforms, S-RAMP will always attempt to discover a JMS *ConnectionFactory* and all configured topics/queues through JNDI. If found, it will simply use that existing framework and setup. Users can add additional topics/queues to their framework, then add them to *sramp.properties* (see above).
- If the no existing JMS setup is discovered, S-RAMP kicks off an embedded ActiveMQ broker over TCP. Then, all configured topics and queues are created automatically. External clients can connect to this broker in one of two ways:
 - The ActiveMQ broker provides a lightweight JNDI implementation and automatically exposes the *ConnectionFactory* (literally named "ConnectionFactory"). To expose the topics/queues, the **client app** needs to include a *jndi.properties* file (and ActiveMQ jars) on the classpath. The contents of that file should contain something like *topic.[jndi name] = [activemq topic name]*. *[jndi name]* is then available to the client. Other than that properties file, the client is able to use generic JNDI and JMS without any ActiveMQ APIs.
 - Simply use the ActiveMQ libraries and API

6.3.2. Authorization

During installation, you were prompted for a password. This set up a standard Wildfly/EAP **admin** user (including the **artificer** role used by the HornetQ configuration in `standalone*.xml`). These credentials must be used when connecting to the JMS topics/queues as a subscriber!

6.3.3. Artifact JMS Events

Event	JMSType Header	Payload
Artifact Created	sramp:artifactCreated	Artifact JSON
Artifact Updated	sramp:artifactUpdated	Artifact JSON
Artifact Deleted	sramp:artifactDeleted	Artifact JSON

These events carry the artifacts, marshalled into JSON, as payloads. Note that these can be easily unmarshalled back into the s-ramp-api module's Java bindings. Here's a brief example using Jackson:

```
// The TextMessage is received through a typical JMS MessageListener.
TextMessage textMessage = ...;
ObjectMapper mapper = new ObjectMapper();
ExtendedArtifactType eventArtifact = mapper.readValue(textMessage.getText(),
    ExtendedArtifactType.class);
```

Example Artifact Created JSON

```
{
  "classifiedBy":[
  ],
  "relationship":[
  ],
  "property":[
  ],
  "artifactType":"EXTENDED_ARTIFACT_TYPE",
  "name":"Foo",
  "description":"created",
  "createdBy":"admin",
  "version":null,
  "uuid":"cd0d16c6-cee0-41fa-ad53-47d4e48947fb",
```

```
"createdTimestamp":1411744515668,
"lastModifiedTimestamp":1411744515668,
"lastModifiedBy":"admin",
"otherAttributes":{
  "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0}derived":"false",
  "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-
v1.0}contentType":"application/xml"
},
"extendedType":"FooArtifactType"
}
```

artifactUpdated takes the payload a step further and includes both the original and the revised artifacts.

Example Artifact Updated JSON

```
{
  "updatedArtifact":{
    "@class":"org.oasis_open.docs.s_ramp.ns.s_ramp_v1.ExtendedArtifactType",
    "classifiedBy":[

    ],
    "relationship":[

    ],
    "property":[

    ],
    "artifactType":"EXTENDED_ARTIFACT_TYPE",
    "name":"Foo",
    "description":"updated",
    "createdBy":"admin",
    "version":null,
    "uuid":"cd0d16c6-cee0-41fa-ad53-47d4e48947fb",
    "createdTimestamp":1411744515668,
    "lastModifiedTimestamp":1411744516142,
    "lastModifiedBy":"admin",
    "otherAttributes":{
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0}derived":"false",
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-
v1.0}contentType":"application/xml"
    },
    "extendedType":"FooArtifactType"
  },
  "oldArtifact":{
    "@class":"org.oasis_open.docs.s_ramp.ns.s_ramp_v1.ExtendedArtifactType",
    "classifiedBy":[

    ],
    "relationship":[

    ],
    "property":[

    ],
    "artifactType":"EXTENDED_ARTIFACT_TYPE",
    "name":"Foo",
    "description":"original",
    "createdBy":"admin",
    "version":null,
    "uuid":"cd0d16c6-cee0-41fa-ad53-47d4e48947fb",
    "createdTimestamp":1411744515668,
    "lastModifiedTimestamp":1411744515668,
    "lastModifiedBy":"admin",
    "otherAttributes":{
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0}derived":"false",
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-
v1.0}contentType":"application/xml"
    },
    "extendedType":"FooArtifactType"
  }
}
```

```

    "relationship":[

    ],
    "property":[

    ],
    "artifactType":"EXTENDED_ARTIFACT_TYPE",
    "name":"Foo",
    "description":"created",
    "createdBy":"admin",
    "version":null,
    "uuid":"cd0d16c6-cee0-41fa-ad53-47d4e48947fb",
    "createdTimestamp":1411744515668,
    "lastModifiedTimestamp":1411744515668,
    "lastModifiedBy":"admin",
    "otherAttributes":{
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0}derived":"false",
      "{http://docs.oasis-open.org/s-ramp/ns/s-ramp-v1.0}contentType":"application/xml"
    },
    "extendedType":"FooArtifactType"
  }
}

```

6.3.4. Ontology JMS Events

Event	JMSType Header	Payload
Ontology Created	s-ramp:ontologyCreated	Ontology JSON
Ontology Updated	s-ramp:ontologyUpdated	Ontologies JSON
Ontology Deleted	s-ramp:ontologyDeleted	Ontology JSON

These events work similarly to Artifacts, but carry the ontology payload using the s-ramp-api module's binding: RDF.

Example Ontology Created JSON

```

{
  "ontology":{
    "label":"Color",
    "comment":null,
    "id":"Color"
  },

```

```
"clazz":[
  {
    "subClassOf":null,
    "label":"Red",
    "comment":null,
    "id":"Red"
  },
  {
    "subClassOf":null,
    "label":"Blue",
    "comment":null,
    "id":"Blue"
  }
],
"otherAttributes":{
  "{http://www.w3.org/XML/1998/namespace}base":"foo"
}
}
```

Example Ontology Updated JSON

```
{
  "updatedOntology":{
    "ontology":{
      "label":"ColorUpdated",
      "comment":null,
      "id":"Color"
    },
    "clazz":[
      {
        "subClassOf":null,
        "label":"Red",
        "comment":null,
        "id":"Red"
      },
      {
        "subClassOf":null,
        "label":"Blue",
        "comment":null,
        "id":"Blue"
      }
    ],
    "otherAttributes":{
      "{http://www.w3.org/XML/1998/namespace}base":"foo"
    }
  },
  "oldOntology":{
    "ontology":{
      "label":"Color",

```



```
    "comment":null,
    "id":"Color"
  },
  "clazz":[
    {
      "subClassOf":null,
      "label":"Red",
      "comment":null,
      "id":"Red"
    },
    {
      "subClassOf":null,
      "label":"Blue",
      "comment":null,
      "id":"Blue"
    }
  ],
  "otherAttributes":{
    "{http://www.w3.org/XML/1998/namespace}base":"foo"
  }
}
```


Chapter 7. Overlord S-RAMP

Command Line

Using the S-RAMP cmdline tool `s-ramp.sh`

In the `bin` directory of the distribution you can find the `s-ramp.sh`. Run this command to fire up the shell

```
./s-ramp.sh
*****
      _____
     /  _  |      |  _  \  _  \  \  |  _  \
    \  --.  _  |  |  /  /  \  \  .  .  |  |  /
     \  --. \  _  |  /  _  |  \  |  |  _  /
    /  \  /  /      |  \  \  |  |  |  |  |
    \  \  /      \  |  \  \  |  |  |  |  |
     \  \  /      \  |  \  \  |  |  |  |  |

JBoss S-RAMP Kurt Stam and Eric Wittmann, Licensed under the
Apache License, V2.0, Copyright 2012
*****
s-ramp>
```

The shell supports auto-completion and keeps a command history for duration of the session.

7.1. Connecting to S-RAMP server

To connect the shell to the server type `connect` and hit the tab key. It should auto-complete to say `s-ramp:connect http://localhost:8080/s-ramp-server` and when hitting the return key you will be prompted for user credentials. If everything is successful, the cursor should go from red to green. Of course you will need to update the server and port information if your S-RAMP repository runs elsewhere.

7.2. Browsing the S-RAMP repository

To browse the artifacts in the repository run the following query:

```
s-ramp> s-ramp:query /s-ramp
Querying the S-RAMP repository:
/s-ramp
Atom Feed (9 entries)
Idx          Type Name
---          -
1            ImageDocument user-properties.png
2            Document overlord.demo.CheckDeployment-taskform.flt
```

```
3      BrmsPkgDocument SRAMPPackage.pkg
4      ImageDocument  overlord.demo.SimpleReleaseProcess-image.png
5      ImageDocument  run-build-install.png
6      Document       overlord.demo.SimpleReleaseProcess-
taskform.flt
7      ImageDocument  audio-input-microphone-3.png
8      BpmnDocument   overlord.demo.SimpleReleaseProcess.bpmn
9      TextDocument   HttpClientWorkDefinitions.wid
```

To obtain the `metaData` of `overlord.demo.SimpleReleaseProcess.bpmn`, which is number 8 in the list, issue

```
s-ramp> s-ramp:getMetaData feed:8
Meta Data for: 31b3acbc-cda8-4856-9e34-d3e645283035
-----
-- Core S-RAMP Info --
Type: BpmnDocument
Model: ext
UUID: 31b3acbc-cda8-4856-9e34-d3e645283035
Name: overlord.demo.SimpleReleaseProcess.bpmn
Derived: false
Created By: <anonymous>
Created On: 2013-03-08T14:00:37.036-05:00
Modified By: <anonymous>
Modified On: 2013-03-18T14:58:46.328-04:00
s-ramp>
```

7.3. Updating artifact MetaData

7.3.1. Properties

To update a property on the artifact use `s-ramp:property set` and hit the `tab` key

```
s-ramp> s-ramp:property set
description      name      version
```

this shows a list of properties that can be updated. To add a description to this artifact use

```
s-ramp> s-ramp:property set description "BPMN2 artifact representing the
SimpleReleaseProcess"
Successfully set property description.
s-ramp> s-ramp:updateMetaData
Successfully updated artifact overlord.demo.SimpleReleaseProcess.bpmn.
```

To verify issue

```
s-ramp> s-ramp:getMetaData feed:8
```

```

Meta Data for: 31b3acbc-cda8-4856-9e34-d3e645283035
-----
-- Core S-RAMP Info --
Type: BpmnDocument
Model: ext
UUID: 31b3acbc-cda8-4856-9e34-d3e645283035
Name: overlord.demo.SimpleReleaseProcess.bpmn
Derived: false
Created By: <anonymous>
Created On: 2013-03-08T14:00:37.036-05:00
Modified By: <anonymous>
Modified On: 2013-03-18T16:09:56.879-04:00
-- Description --
BPMN2 artifact representing the SimpleReleaseProcess

```

and you can see the added description at the bottom of the printout.

7.3.2. Custom Properties

To add a custom property called `kurt` with value `stam` you can run

```

s-ramp> s-ramp:property set kurt stam
Successfully set property kurt.
s-ramp> s-ramp:updateMetaData
Successfully updated artifact overlord.demo.SimpleReleaseProcess.bpmn.

```

and to verify that the custom property was added issue

```

s-ramp> s-ramp:getMetaData feed:8
Meta Data for: 31b3acbc-cda8-4856-9e34-d3e645283035
-----
-- Core S-RAMP Info --
Type: BpmnDocument
Model: ext
UUID: 31b3acbc-cda8-4856-9e34-d3e645283035
Name: overlord.demo.SimpleReleaseProcess.bpmn
Derived: false
Created By: <anonymous>
Created On: 2013-03-08T14:00:37.036-05:00
Modified By: <anonymous>
Modified On: 2013-03-18T16:21:16.119-04:00
-- Description --
BPMN2 artifact representing the SimpleReleaseProcess
-- Custom Properties --
kurt: stam
s-ramp>

```

When hitting the `tab` key on `s-ramp:property set` results in

```
s-ramp> s-ramp:property set
description      kurt              name              version
```

which now had the added custom property kurt.

7.3.3. Classifications

To add a classification of deployment-status to your artifact use

```
s-ramp> s-ramp:classification add "http://www.jboss.org/overlord/deployment-
status.owl#Dev"
Successfully added classification 'http://www.jboss.org/overlord/deployment-
status.owl#Dev'.
s-ramp> s-ramp:updateMetaData
Successfully updated artifact overlord.demo.SimpleReleaseProcess.bpmn.
```

and to verify that it was added

```
s-ramp> s-ramp:getMetaData feed:8
Meta Data for: 31b3acbc-cda8-4856-9e34-d3e645283035
-----
-- Core S-RAMP Info --
Type: BpmnDocument
Model: ext
UUID: 31b3acbc-cda8-4856-9e34-d3e645283035
Name: overlord.demo.SimpleReleaseProcess.bpmn
Derived: false
Created By: <anonymous>
Created On: 2013-03-08T14:00:37.036-05:00
Modified By: <anonymous>
Modified On: 2013-03-18T16:30:42.641-04:00
-- Description --
BPMN2 artifact representing the SimpleReleaseProcess
-- Classifications --
Classified By: http://www.jboss.org/overlord/deployment-status.owl#Dev
-- Custom Properties --
kurt: stam
s-ramp>
```

7.4. Querying the S-RAMP Repository using XPath2 Syntax

S-RAMP supports an XPath2 Syntax for querying. For example to obtain all WSDL models in the repository use

```
s-ramp> s-ramp:query /s-ramp/wsd1/Wsd1Document
```

```

Querying the S-RAMP repository:
  /s-ramp/wsdl/WsdlDocument
Atom Feed (1 entries)
  Idx          Type Name
  ---          ----
  1            WsdlDocument OrderService.wsdl
s-ramp>

```

When this WSDL file was uploaded derived information was extracted from it and stored a WSDL model. TO see the various data structures it derived simply hit the tab on `s-ramp:query /s-ramp/wsdl`

```

s-ramp> s-ramp:query /s-ramp/wsdl/
Binding          BindingOperation      BindingOperationFault
  BindingOperationInput      BindingOperationOutput
Fault            Message              Operation
  OperationInput      OperationOutput
Part              Port                PortType
  WsdlDocument      WsdlExtension
WsdlService
s-ramp>

```

Note that derived data is read only, and cannot be updated by the user.

To obtain all Operations in this WSDL use

```

s-ramp:query /s-ramp/wsdl/Operation
Querying the S-RAMP repository:
  /s-ramp/wsdl/Operation
Atom Feed (1 entries)
  Idx          Type Name
  ---          ----
  1            Operation submitOrder
s-ramp>

```

You can narrow this query down even more by adding that the name needs to start with `submit`

```

s-ramp:query "/s-ramp/wsdl/Operation[xp2:matches(@name, 'submit.*')]"
Querying the S-RAMP repository:
  /s-ramp/wsdl/Operation[xp2:matches(@name, 'submit.*')]
Atom Feed (1 entries)
  Idx          Type Name
  ---          ----
  1            Operation submitOrder
s-ramp>

```

don't forget to use the surrounding quotes, and a `.` after `submit` as required by XPath2.

To obtain all the artifacts that were derived from an artifact you can use

```
/s-ramp[relatedDocument[@uuid = '<uuid>']]
```

In this case we use the uuid of a wsdl and get all the artifacts derived from the wsdl

```
s-ramp:query "/s-ramp[relatedDocument[@uuid = '15a94308-a088-4a03-ad83-e60239af74e4']]"
```

Querying the S-RAMP repository:

```
/s-ramp[relatedDocument[@uuid = '15a94308-a088-4a03-ad83-e60239af74e4']]
```

Atom Feed (16 entries)

Idx	Type	Name
---	----	----
1	OperationInput	submitOrder
2	WsdService	OrderService
3	SoapAddress	soap:address
4	BindingOperationInput	wsdl:input
5	SoapBinding	soap:binding
6	Part	parameters
7	Binding	OrderServiceBinding
8	BindingOperationOutput	wsdl:output
9	Message	submitOrderResponse
10	OperationOutput	submitOrderResponse
11	BindingOperation	submitOrder
12	Message	submitOrder
13	Operation	submitOrder
14	Port	OrderServicePort
15	Part	parameters
16	PortType	OrderService

To get a list of all artifacts that were extracted from another archive use

```
s-ramp:query "/s-ramp[expandedFromDocument[@uuid = '<uuid>']]"
```

let's say we uploaded a jar file containing switchyard artifacts, with uddi *67c6f2d3-0f10-4f0d-ada6-d85f92f02a33*:

```
s-ramp:query "/s-ramp[expandedFromDocument[@uuid = '67c6f2d3-0f10-4f0d-ada6-d85f92f02a33']]"
```

Querying the S-RAMP repository:

```
/s-ramp[expandedFromDocument[@uuid = '67c6f2d3-0f10-4f0d-ada6-d85f92f02a33']]
```

Atom Feed (3 entries)

Idx	Type	Name
---	----	----
1	XmlDocument	switchyard.xml
2	XmlDocument	beans.xml
3	XmlDocument	faces-config.xml

For more information about querying the repository see the *S-RAMP Query Language* section of this guide.

7.4.1. Stored Queries

The above queries can also be executed using Stored Queries:

```
s-ramp> s-ramp:createStoredQuery FooQuery /s-ramp/ext/FooType
s-ramp> s-ramp:executeStoredQuery FooQuery
Querying the S-RAMP repository:
  /s-ramp/ext/FooType
Atom Feed (1 entries)
  Idx                Type Name
  ---                -
  1                  FooType FooArtifact
```

7.5. Extending the S-RAMP CLI

The S-RAMP CLI has a number of built-in commands that are ready to be used. However, it is also possible to extend the CLI with new custom commands. This section describes how to do it.

New CLI commands are contributed by creating a class that implements the *ShellCommandProvider* interface. The provider will indicate a namespace for its commands along with a Map of commands (command name → command). The provider and command implementations should be packaged up into a JAR along with a file named:

```
META-INF/services/org.overlord.sramp.shell.api.ShellCommandProvider
```

The JAR must be made available to the S-RAMP CLI, either by putting it on the classpath, or else by putting it in the following directory:

```
~/.s-ramp/commands
```

For a working example of a custom S-RAMP CLI command, there is a demo in the S-RAMP distribution called **s-ramp-demos-shell-command**.

7.6. Running Commands in Batch

An interesting thing you can do with the S-RAMP CLI is to use it as a batch processor. To do this, simply create a text file with all of the commands you wish to run in a batch (one per line) and then ask the S-RAMP CLI to execute the batch. For example, a batch of commands may look like this:

```
# Connect to S-RAMP
connect http://localhost:8080/s-ramp-server admin admin123!

# Upload an ontology
```

```
ontology:upload /path/to/data/my-ontology.owl

# Add some artifact content
upload /path/to/artifact-content.ext
property set property-foo Bar
updateMetaData
```

To execute the batch, simply do:

```
sramp.sh -f /path/to/cli-commands.txt
```

7.7. Batch File Property Interpolation

Note that it is possible to use Ant style property replacements within your S-RAMP CLI batch file. The CLI will look for property values as System Properties, or by passing in the path to a Java Properties file to the CLI via a "-propertiesFile" option.

We support simply property replacement as well as property replacement with defaults. For example:

```
# Connect to S-RAMP
connect ${sramp.endpoint:http://localhost:8080/s-ramp-server}
  ${sramp.username:admin} ${sramp.password:admin123!}
upload ${resource.path}
```

The above batch file allows whoever is using it (via the S-RAMP CLI) to set the following properties either via System Properties or via a passed-in properties file:

- resource.path - (required)
- sramp.endpoint - (optional, defaults to <http://localhost:8080/s-ramp-server>)
- sramp.username - (optional, defaults to admin)
- sramp.password - (optional, defaults to admin123!)

7.8. Log-to-File

Rather than creating batch files by hand, the S-RAMP CLI includes a "log-to-file" option. All commands executed during the CLI session will be logged to a file, directly usable as a batch file in the future.

```
sramp.sh -l /path/to/cli-commands.txt
```

Chapter 8. Overlord S-RAMP Maven Integration

8.1. Overview

A key feature of the Overlord S-RAMP project is its integration with Maven. Currently there are two mechanisms provided to integrate with Maven. First, the project provides an HTTP servlet which acts as a facade in front of the S-RAMP repository. This can be used for dependency retrieval and artifact deployments, just as any other Maven repository. Second, there is a "maven" namespace in the S-RAMP Shell (CLI) providing integration between the CLI and Maven.

8.2. Deploying to S-RAMP

The S-RAMP URL can be directly used in the distributionManagement section. For example:

```
<distributionManagement>
  <repository>
    <id>local-sramp-repo</id>
    <name>S-RAMP Releases Repository</name>
    <url>http://localhost:8080/s-ramp-server/maven/repository</url>
  </repository>
  <snapshotRepository>
    <id>local-sramp-repo-snapshots</id>
    <name>S-RAMP Snapshots Repository</name>
    <url>http://localhost:8080/s-ramp-server/maven/repository</url>
  </snapshotRepository>
</distributionManagement>
```

With these settings, maven deployments will be sent directly to the S-RAMP repository using the S-RAMP API. Note that artifacts will be added to the S-RAMP repository with an artifact type based on the maven type of the project. This behavior can be overridden by adding a query parameter to the repository URL in the pom.xml. For example:

```
<distributionManagement>
  <repository>
    <id>local-sramp-repo</id>
    <name>S-RAMP Releases Repository</name>
    <url>http://localhost:8080/s-ramp-server/maven/repository?
artifactType=SwitchYardApplication</url>
  </repository>
</distributionManagement>
```

The above example will cause the maven artifact to be uploaded with an S-RAMP artifact type of "SwitchYardApplication" whenever a maven deployment or release build is performed.

For example, the following maven command could be run to deploy the maven artifact directly into s-ramp:

```
mvn clean deploy
```

8.3. Adding S-RAMP Artifacts as Dependencies

Additionally, artifacts from the S-RAMP repository can be used as dependencies in your maven project.

First, the S-RAMP repository must be configured in the maven project as a maven repository. This can be done with the following markup in the pom.xml.

```
<repositories>
  <repository>
    <id>local-sramp-repo</id>
    <name>Local S-RAMP Repository</name>
    <url>http://localhost:8080/s-ramp-server/maven/repository</url>
    <layout>default</layout>
  </repository>
</repositories>
```

Once the repository is configured, an S-RAMP artifact can be referenced as a dependency in two ways. First, if the artifact was added to S-RAMP using the maven integration to deploy it, then the artifact in S-RAMP will contain maven specific properties, allowing it to be referenced as a dependency using those maven specific properties. In this case, simply add the dependency as you normally would in a maven project. For example:

```
<dependency>
  <groupId>org.overlord.sramp.wiki</groupId>
  <artifactId>s-ramp-wiki-example</artifactId>
  <version>1.0</version>
</dependency>
```

However, even if an artifact was added to the S-RAMP repository in some other way (and therefore does not have any maven specific properties) it can be used as a dependency. In this case, you can reference the dependency by using its S-RAMP artifact model, type, and UUID. The model and type are used to make up a maven groupId, while the UUID becomes the maven artifactId. The version information is not used (but still required in the pom.xml). For example, if a JAR is added to the S-RAMP repository and you wish to use it as a dependency, your pom.xml might contain the following dependency.

```
<dependency>
  <groupId>ext.JavaArchive</groupId>
  <artifactId>8744-437487-4734525-382345-923424</artifactId>
  <version>1.0</version>
```

```
</dependency>
```

Authentication ~~~~~ Whenever the S-RAMP Maven integration features are used, you will need to provide valid authentication credentials in the [Maven settings.xml](http://maven.apache.org/settings.html) [http://maven.apache.org/settings.html] file. However, the typical "username" and "password" values are not sufficient, since they are ignored during artifact retrieval (ie, GET calls to the repo). Instead, you must explicitly define the BASIC authentication header value. Unfortunately, this also means you have to manually Base64 encode the value. For example, "Basic admin:artificer1!" becomes "Basic YWRtaW46YXJ0aWZpY2VyMSE=".

It's a pain, but at least as of Maven 3.0.5, it's the best option we could find (PLEASE correct us if we're wrong!).

An example of providing credentials in the settings.xml file:

```
<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0
    http://maven.apache.org/xsd/settings-1.0.0.xsd">
  <servers>
    <server>
      <id>local-sramp-repo</id>
      <configuration>
        <httpHeaders>
          <property>
            <name>Authorization</name>
            <value>Basic YWRtaW46YXJ0aWZpY2VyMSE=</value>
          </property>
        </httpHeaders>
      </configuration>
    </server>
    <server>
      <id>local-sramp-repo-snapshots</id>
      <configuration>
        <httpHeaders>
          <property>
            <name>Authorization</name>
            <value>Basic YWRtaW46YXJ0aWZpY2VyMSE=</value>
          </property>
        </httpHeaders>
      </configuration>
    </server>
  </servers>
</settings>
```

8.4. Maven Integration in the CLI

Note: For more general information about the S-RAMP Shell please see the S-RAMP CLI chapter in this guide.

Another available mechanism for integrating with maven is the S-RAMP CLI's "maven" command namespace. For help on the maven commands in the CLI, run the S-RAMP shell (sramp.sh) and type the following from the resulting prompt:

```
help maven
```

Using the maven CLI commands is often a good choice if you wish to incorporate maven related S-RAMP operations into a script of some kind.

Chapter 9. The S-RAMP Browser (UI)

9.1. Overview

The Overlord S-RAMP project comes with a user interface that allows end users (or more likely business admins) to browse all of the artifacts in the S-RAMP repository. This UI is capable of viewing and manipulating all S-RAMP artifacts in a very generic way, supporting all aspects of the S-RAMP specification (properties, classifiers, relationships, etc).

The browser is a web based application built using GWT and Errai, and is compatible with all modern web browsers. Additionally, it is capable of scaling the interface down to a size that is useful on a smart phone.

Unresolved directive in Guide.asciidoc - include::GuideUserManagement.asciidoc[]

Chapter 10. Overlord S-RAMP

Extension Points

Overlord S-RAMP includes multiple "extension point" contracts that allow users to provide additional, custom functionality. The contracts currently include the following:

10.1. ArtifactBuilder

As mentioned earlier in this guide, part of the S-RAMP specification is the concept of derived content. This happens when an artifact of a certain type is added to the S-RAMP repository. The server is responsible for creating relevant and interesting derived artifacts from it. For example, when an XML Schema (XSD) document is added to the repository, the server is responsible for automatically creating an artifact for every top level Element, Complex Type, Simple Type, and Attribute declaration found in the XSD.

The ArtifactBuilder contract allows integrations to define custom properties on the primary artifact, generate derived artifacts, and resolve relationships between the whole set. The Overlord S-RAMP implementation includes ArtifactBuilders for all of the logical models defined by the S-RAMP specification (e.g. WSDL, XSD, Policy). However, it also provides a mechanism that allows users to provide ArtifactBuilders for their own artifact types. This is done by performing the following steps:

1. Write a custom ArtifactBuilder Java class - it must implement **ArtifactBuilder**
2. Create an ArtifactBuilderProvider (a class that implements **ArtifactBuilderProvider**) - used to map artifact types to implementations of ArtifactBuilder
3. Provide a text file named **org.overlord.sramp.integration.artifactbuilder.ArtifactBuilderProvider** in the following location: **META-INF/services**. The content of that file should simply be one line containing the fully qualified classname of the class defined in #2
4. Package everything up into a JAR and make it available either on the classpath or in an external directory configured by setting property **sramp.extension.customDir**.

The Overlord S-RAMP distribution comes with an example of how to write and package a custom builder - the demo is named **s-ramp-demos-custom-artifact-builder**. Also, see the Javadocs for the relevant classes.

10.2. ArtifactTypeDetector

When an artifact is deployed **without** an explicit model and type, we must attempt to automatically detect them. The ArtifactTypeDetector contract allows integrations to automatically detect an artifact's type, given various contextual-clues. The clues include the path/filename, the artifact's

context within an archive, and the artifact's full content. That last bit is the most powerful part, allowing integrations to, for example, parse files and introduce complex business logic.

As with ArtifactBuilder, Overlord S-RAMP provides several built-in detectors. However, it also provides a mechanism that allows users to provide their own `ArtifactTypeDetectors`. This is done by performing the following steps:

1. Write a custom `ArtifactTypeDetector` Java class - it must implement **`ArtifactTypeDetector`**
2. Provide a text file named **`org.overlord.sramp.integration.artifacttypedetector.ArtifactTypeDetector`** in the following location: **`META-INF/services`**. The content of that file should simply be one line containing the fully qualified classname of the class defined in #1
3. Package everything up into a JAR and make it available either on the classpath or in an external directory configured by setting property **`sramp.extension.customDir`**.

The implementations form a prioritized chain, most-specialized at the top and most-generic at the bottom (the contract includes a `#getPriority` method). It's important to note that execution is **exclusive** and ends processing for the rest of the chain. So, custom implementations **extending** built-in detectors isn't really necessary — simply return null and they'll be executed eventually.

Chapter 11. Overlord S-RAMP Implementation

11.1. Overview

The Overlord S-RAMP implementation strives to be a fully compliant reference implementation of the S-RAMP specification. This chapter describes the overall architecture of the implementation and also provides some information about how to configure it.

11.2. Server

11.2.1. Description

The server implementation is a conventional Java web application (WAR). The following technologies are used to provide the various components that make up the server implementation:

1. JCR (ModeShape) - used as the persistence engine, where all S-RAMP data is stored. Artifacts and ontologies are both stored as nodes in a JCR tree. All S-RAMP queries are mapped to JCRSQL2 queries for processing by the JCR API. The ModeShape JCR implementation is used by default. However, the persistence layer is pluggable allowing alternative providers to be implemented in the future.
2. JAX-RS (RESTEasy) - used to provide the S-RAMP Atom based REST API. The S-RAMP specification documents an Atom based REST API that implementations should make available. The Overlord S-RAMP implementation uses JAX-RS (specifically RESTEasy) to expose all of the REST endpoints defined by the specification.
3. JAXB - used to expose a Java data model based on the S-RAMP data structures defined by the specification (S-RAMP XSD schemas).

11.2.2. Configuration

The UI is configured with numerous properties in the Wildfly/EAP **standalone/configuration/standalone-full.xml** file under the **urn:jboss:domain:overlord-configuration:1.0** subsystem. For example:

```
<subsystem xmlns="urn:jboss:domain:overlord-configuration:1.0">
  <configurations>
    <configuration name="sramp-ui">
      <properties>
        <!-- The location of the S-RAMP server's Atom API -->
        <property name="s-ramp-ui.atom-api.endpoint" value="http://
localhost:8080/s-ramp-server" />
      </properties>
    </configuration>
  </configurations>
</subsystem>
```

```
<!-- Whether or not to validate the S-RAMP server endpoint when
connecting to it -->
<property name="s-ramp-ui.atom-api.validating" value="true" />
<!-- The authentication provider to use when connecting -->
<property name="s-ramp-ui.atom-api.authentication.provider"
value="org.overlord.sramp.ui.server.api.KeycloakBearerTokenAuthenticationProvider" /
>
    </properties>
</configuration>
</configurations>
</subsystem>
```

11.2.3. Security

The S-RAMP Browser is protected using web application security mechanisms configured in the WARs' web.xml.

By default, the UI uses single-sign-on (SSO) as the actual authentication mechanism. The SSO is provided via integration with the Keycloak framework. The actual web.xml configuration uses a standard basic security-context, but SSO is provided under-the-hood.

The security domain is configured to accept either a username and password (standard BASIC authentication) or a bearer token. If invoking the Atom API directly, then typically BASIC authentication would be used. When invoking the Atom API from an application that has already authenticated the user in some way, then it is appropriate to use the bearer token as a request header ("Authorization", "Bearer " + bearerToken). For example, the S-RAMP CLI application uses BASIC authentication when invoking the S-RAMP Atom API. The S-RAMP Browser (a web application) requires the user be authenticated into it, and thus is able to use the bearer tokens rather than propagate user credentials.

The app uses a Keycloak realm named **artificer**, which you'll see used in **standalone-full.xml**'s Keycloak subsystem resources. See **Getting Started** for more info.

Chapter 12. S-RAMP Samples

Chapter 13. Overlord S-RAMP

Server Configuration

Out-of-the-box, Overlord S-RAMP provides a useful, default server configuration. However, if you'd like to mold it into an existing setup, here are a few areas that can be modified.

13.1. Datasource

By default, S-RAMP uses a simple file-based H2 datasource. However, any existing datasource can be used. Swap-out the datasource's JNDI name in the following location:

Standalone modes: `JBOSS_HOME/standalone/configuration/standalone*.xml`

```
...
<cache-container name="modeshape">
  <local-cache name="sramp">
    <locking isolation="NONE"/>
    <transaction mode="NON_XA"/>
    <string-keyed-jdbc-store purge="false" passivation="false"
datasource="[DATASOURCE JNDI NAME]">
      <string-keyed-table prefix="ispn_bucket">
        <id-column type="VARCHAR(500)" name="id"/>
        <data-column type="VARBINARY" name="datum"/>
        <timestamp-column type="BIGINT" name="version"/>
      </string-keyed-table>
    </string-keyed-jdbc-store>
  </local-cache>
</cache-container>
...
```

13.2. WARNINGS

- Between runs, the ModeShape repository name cannot be changed. The name is used on multiple paths used for binary storage, search indexes, etc. Attempting to do so, without changing all necessary paths, will result in ModeShape failures during startup.
- Similarly, between runs, the Infinispan "local-cache" name (and accompanying "cacheName" in the ModeShape config) cannot be changed. ModeShape includes a hash of the cache name within its node IDs, so changing the name is guaranteed to break your repository.

Bibliography

Books

[walsh-muellner] Norman Walsh & Leonard Muellner. *DocBook - The Definitive Guide*. O'Reilly & Associates. 1999. ISBN 1-56592-580-7.

