

# **Mobicents JAIN SLEE Diameter Gq Resource Adaptor User Guide**

by Alexandre Mendonça

---

---

---

Preface .....	v
1. Document Conventions .....	v
1.1. Typographic Conventions .....	v
1.2. Pull-quote Conventions .....	vii
1.3. Notes and Warnings .....	vii
2. Provide feedback to the authors! .....	viii
<b>1. Introduction to Mobicents JAIN SLEE Diameter Gq Resource Adaptor .....</b>	<b>1</b>
<b>2. Resource Adaptor Type .....</b>	<b>3</b>
2.1. Activities .....	3
2.2. Events .....	5
2.3. Activity Context Interface Factory .....	6
2.4. Resource Adaptor Interface .....	7
2.5. Restrictions .....	9
2.6. Sbb Code Examples .....	9
<b>3. Resource Adaptor Implementation .....</b>	<b>11</b>
3.1. Configuration .....	11
3.2. Default Resource Adaptor Entities .....	11
3.3. Traces and Alarms .....	12
3.3.1. Tracers .....	12
3.3.2. Alarms .....	12
<b>4. Setup .....</b>	<b>13</b>
4.1. Pre-Install Requirements and Prerequisites .....	13
4.1.1. Hardware Requirements .....	13
4.1.2. Software Prerequisites .....	13
4.2. Mobicents JAIN SLEE Diameter Gq Resource Adaptor Source Code .....	13
4.2.1. Release Source Code Building .....	13
4.2.2. Development Trunk Source Building .....	14
4.3. Installing Mobicents JAIN SLEE Diameter Gq Resource Adaptor .....	14
4.4. Uninstalling Mobicents JAIN SLEE Diameter Gq Resource Adaptor .....	14
<b>5. Clustering .....</b>	<b>17</b>
5.1. Failover .....	17
5.2. Load Balancing .....	17
A. Revision History .....	19
Index .....	21

---

---

## Preface

# 1. Document Conventions

This manual uses several conventions to highlight certain words and phrases and draw attention to specific pieces of information.

In PDF and paper editions, this manual uses typefaces drawn from the [Liberation Fonts](https://fedorahosted.org/liberation-fonts/) [https://fedorahosted.org/liberation-fonts/] set. The Liberation Fonts set is also used in HTML editions if the set is installed on your system. If not, alternative but equivalent typefaces are displayed. Note: Red Hat Enterprise Linux 5 and later includes the Liberation Fonts set by default.

## 1.1. Typographic Conventions

Four typographic conventions are used to call attention to specific words and phrases. These conventions, and the circumstances they apply to, are as follows.

**Mono-spaced Bold**

Used to highlight system input, including shell commands, file names and paths. Also used to highlight key caps and key-combinations. For example:

To see the contents of the file `my_next_bestselling_novel` in your current working directory, enter the `cat my_next_bestselling_novel` command at the shell prompt and press **Enter** to execute the command.

The above includes a file name, a shell command and a key cap, all presented in Mono-spaced Bold and all distinguishable thanks to context.

Key-combinations can be distinguished from key caps by the hyphen connecting each part of a key-combination. For example:

Press **Enter** to execute the command.

Press **Ctrl+Alt+F1** to switch to the first virtual terminal. Press **Ctrl+Alt+F7** to return to your X-Windows session.

The first sentence highlights the particular key cap to press. The second highlights two sets of three key caps, each set pressed simultaneously.

If source code is discussed, class names, methods, functions, variable names and returned values mentioned within a paragraph will be presented as above, in **Mono-spaced Bold**. For example:

File-related classes include `filesystem` for file systems, `file` for files, and `dir` for directories. Each class has its own associated set of permissions.

### Proportional Bold

This denotes words or phrases encountered on a system, including application names; dialogue box text; labelled buttons; check-box and radio button labels; menu titles and sub-menu titles. For example:

Choose **System > Preferences > Mouse** from the main menu bar to launch **Mouse Preferences**. In the **Buttons** tab, click the **Left-handed mouse** check box and click **Close** to switch the primary mouse button from the left to the right (making the mouse suitable for use in the left hand).

To insert a special character into a **gedit** file, choose **Applications > Accessories > Character Map** from the main menu bar. Next, choose **Search > Find** from the **Character Map** menu bar, type the name of the character in the **Search** field and click **Next**. The character you sought will be highlighted in the **Character Table**. Double-click this highlighted character to place it in the **Text to copy** field and then click the **Copy** button. Now switch back to your document and choose **Edit > Paste** from the **gedit** menu bar.

The above text includes application names; system-wide menu names and items; application-specific menu names; and buttons and text found within a GUI interface, all presented in Proportional Bold and all distinguishable by context.

Note the **>** shorthand used to indicate traversal through a menu and its sub-menus. This is to avoid the difficult-to-follow 'Select **Mouse** from the **Preferences** sub-menu in the **System** menu of the main menu bar' approach.

*Mono-spaced Bold Italic Of Proportional Bold Italic*

Whether Mono-spaced Bold or Proportional Bold, the addition of Italics indicates replaceable or variable text. Italics denotes text you do not input literally or displayed text that changes depending on circumstance. For example:

To connect to a remote machine using ssh, type `ssh username@domain.name` at a shell prompt. If the remote machine is `example.com` and your username on that machine is john, type `ssh john@example.com`.

The `mount -o remount file-system` command remounts the named file system. For example, to remount the `/home` file system, the command is `mount -o remount /home`.

To see the version of a currently installed package, use the `rpm -q package` command. It will return a result as follows: `package-version-release`.

Note the words in bold italics above `username`, `domain.name`, `file-system`, `package`, `version` and `release`. Each word is a placeholder, either for text you enter when issuing a command or for text displayed by the system.

Aside from standard usage for presenting the title of a work, italics denotes the first use of a new and important term. For example:

When the Apache HTTP Server accepts requests, it dispatches child processes or threads to handle them. This group of child processes or threads is known as

a *server-pool*. Under Apache HTTP Server 2.0, the responsibility for creating and maintaining these server-pools has been abstracted to a group of modules called *Multi-Processing Modules (MPMs)*. Unlike other modules, only one module from the MPM group can be loaded by the Apache HTTP Server.

## 1.2. Pull-quote Conventions

Two, commonly multi-line, data types are set off visually from the surrounding text.

Output sent to a terminal is set in `Mono-spaced Roman` and presented thus:

```
books      Desktop  documentation  drafts  mss    photos  stuff  svn
books_tests Desktop1  downloads      images  notes  scripts svgs
```

Source-code listings are also set in `Mono-spaced Roman` but are presented and highlighted as follows:

```
package org.jboss.book.jca.ex1;

import javax.naming.InitialContext;

public class ExClient
{
    public static void main(String args[])
        throws Exception
    {
        InitialContext iniCtx = new InitialContext();
        Object      ref  = iniCtx.lookup("EchoBean");
        EchoHome    home = (EchoHome) ref;
        Echo        echo = home.create();

        System.out.println("Created Echo");

        System.out.println("Echo.echo('Hello') = " + echo.echo("Hello"));
    }
}
```

## 1.3. Notes and Warnings

Finally, we use three visual styles to draw attention to information that might otherwise be overlooked.



### Note

A note is a tip or shortcut or alternative approach to the task at hand. Ignoring a note should have no negative consequences, but you might miss out on a trick that makes your life easier.



### Important

Important boxes detail things that are easily missed: configuration changes that only apply to the current session, or services that need restarting before an update will apply. Ignoring Important boxes won't cause data loss but may cause irritation and frustration.



### Warning

A Warning should not be ignored. Ignoring warnings will most likely cause data loss.

## 2. Provide feedback to the authors!

If you find a typographical error in this manual, or if you have thought of a way to make this manual better, we would love to hear from you! Please submit a report in the the [Issue Tracker](http://code.google.com/p/mobicents/issues/list) [http://code.google.com/p/mobicents/issues/list], against the product **Mobicents JAIN SLEE Diameter Gq Resource Adaptor**, or contact the authors.

When submitting a bug report, be sure to mention the manual's identifier: JAIN\_SLEE\_DIAMETER\_GQ\_RA\_User\_Guide

If you have a suggestion for improving the documentation, try to be as specific as possible when describing it. If you have found an error, please include the section number and some of the surrounding text so we can find it easily.



# Introduction to Mobicents JAIN SLEE Diameter Gq Resource Adaptor

This resource adaptor provides a Diameter API for JAIN SLEE applications, according to Gq' interface based on Diameter protocol.

The Gq' reference point is used for the service-based policy set-up information exchange between the Service-based Policy Decision Function (SPDF) and the Application Function (AF), e.g. the P-CSCF.

Events represent Diameter Gq' messages received by the Diameter stack. Different events types are specified for each Diameter request or answer. Events are fired either on client or server activities.

The Activities are defined by RA Type to ease use of RA. Activities represent Diameter session between two peers. SLEE applications use activities to create, send and receive messages.



# Resource Adaptor Type

Diameter Gq Resource Adaptor Type is defined by Mobicents team as part of effort to standardize RA Types.

## 2.1. Activities

Diameter Gq Type 1.1.0-SNAPSHOT defines the following Activities:

`net.java.slee.resource.diameter.gq.GqClientSessionActivity`

This type of activity represents client side of Gq' session. Abort-Session-Request (ASR) and Re-Auth-Request (RAR) messages are received in this Activity and respective Answers are sent from it. AA-Request (AAR) and Session-Termination-Request (STR) messages can be created and sent in this Activity, receiving the respective Answer (or timeout) later on this Activity.

This activity type can be created with call to the proper `createGqClientSessionActivity` method of `net.java.slee.resource.diameter.gq.GqProvider`. It ends once underlying Gq' session ends.

State machine for client Authorization sessions can be found at [Section 8.1](http://tools.ietf.org/html/rfc3588#section-8.1) [<http://tools.ietf.org/html/rfc3588#section-8.1>] of Diameter Base Protocol RFC.

`net.java.slee.resource.diameter.gq.GqServerSessionActivity`

This type of activity represents server side of Gq' session. AA-Request (AAR) and Session-Termination-Request (STR) messages are received in this Activity and respective Answers are sent from it. Abort-Session-Request (ASR) and Re-Auth-Request (RAR) messages can be created and sent in this Activity, receiving the respective Answer (or timeout) later on this Activity.

This activity type is implicitly created by the Resource Adaptor upon reception of the AA-Request message. It ends once underlying Gq' session ends.

State machine for server Authorization sessions can be found at [Section 8.1](http://tools.ietf.org/html/rfc3588#section-8.1) [<http://tools.ietf.org/html/rfc3588#section-8.1>] of Diameter Base Protocol RFC.

All activities define methods required to properly function and expose necessary information to JAIN SLEE services. Gq' Server Activity is defined as follows:

```
public GqAAAnswer createGqAAAnswer(GqAAResponse aar);

public void sendGqAAAnswer(GqAAAnswer aaa) throws IOException;

public GqSessionTerminationAnswer createGqSessionTerminationAnswer(
    GqSessionTerminationRequest str);
```

```
public void sendGqSessionTerminationAnswer(GqSessionTerminationAnswer sta)
    throws IOException;

public void sendReAuthRequest(GqReAuthRequest rar) throws IOException;

public void sendAbortSessionRequest(GqAbortSessionRequest asr) throws IOException;
```

`public GqAAAnswer createGqAAAnswer(GqAARequest aar);`  
This method creates a Gq'-specific AA-Answer message pre-populated with the AVPs appropriate for this session and/or taken from the provided request.

`public void sendGqAAAnswer(GqAAAnswer aaa) throws IOException;`  
This method sends a AA-Answer message to the peer.

`public GqSessionTerminationAnswer createGqSessionTerminationAnswer(GqSessionTerminationRequest str);`  
This method creates a Gq'-specific Session-Termination-Answer message pre-populated with the AVPs appropriate for this session and/or taken from the provided request.

`public void sendGqSessionTerminationAnswer(GqSessionTerminationAnswer sta) throws IOException;`  
This method sends a Session-Termination-Answer message to the peer.

`public void sendReAuthRequest(GqReAuthRequest rar) throws java.io.IOException;`  
This method sends a Gq'-specific Re-Auth-Request message to the peer.

`public void sendAbortSessionRequest(GqAbortSessionRequest asr) throws java.io.IOException;`  
This method sends a Gq'-specific Abort-Session-Request message to the peer.

Gq' Client Activity is defined as follows:

```
public void sendGqAARequest(GqAARequest aar) throws IOException;

public GqReAuthAnswer createGqReAuthAnswer(GqReAuthRequest rar);

public void sendGqReAuthAnswer(GqReAuthAnswer raa) throws IOException;

public GqAbortSessionAnswer createGqAbortSessionAnswer(GqAbortSessionRequest asr);

public void sendGqAbortSessionAnswer(GqAbortSessionAnswer asa) throws IOException;

public void sendGqSessionTerminationRequest(GqSessionTerminationRequest str)
```

**throws** IOException;

```
public void sendGqAARequest(GqAARequest aar) throws IOException;
```

Sends an AA-Request message to the peer.

```
public GqReAuthAnswer createGqReAuthAnswer(GqReAuthRequest rar);
```

Create a Gq'-specific Re-Auth-Answer message pre-populated with the AVPs appropriate for this session and/or taken from the provided request.

```
public void sendGqReAuthAnswer(GqReAuthAnswer raa) throws IOException;
```

Sends a Re-Auth-Answer message to the peer.

```
public GqAbortSessionAnswer createGqAbortSessionAnswer(GqAbortSessionRequest asr);
```

Create a Gq'-specific Abort-Session-Answer message pre-populated with the AVPs appropriate for this session.

```
public void sendGqAbortSessionAnswer(GqAbortSessionAnswer asa) throws IOException;
```

Sends a Abort-Session-Answer message to the peer.

```
public void sendGqSessionTerminationRequest(GqSessionTerminationRequest str) throws IOException;
```

Sends a Gq'-specific Session-Termination-Request message to the peer.



### Note

It is safe to type cast all the mentioned Diameter Activities to it's super interface `net.java.slee.resource.diameter.base.DiameterActivity` defined in Diameter Base Activities section.

## 2.2. Events

Diameter Gq Resource Adaptor Type declares the Diameter Gq' Interface specific events.

The following tables shows which events are fired on each activity.

**Table 2.1. Events received on Gq' Server Activity**

Name	Vendor	Version	Class
net.java.slee.resource.diameter.gq.events.GqAARequest	java.net	0.8	net.java.slee.resource.diameter.gq.events.GqAARequest
net.java.slee.resource.diameter.gq.events.GqAbortSessionAnswer	java.net	0.8	net.java.slee.resource.diameter.gq.events.GqAbortSessionAnswer

Name	Vendor	Version	Class
net.java.slee.resource. diameter.gq.events. GqReAuthAnswer	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqReAuthAnswer
net.java.slee.resource. diameter.gq.events. GqSessionTerminationRequest	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqSessionTerminationRequest

**Table 2.2. Events received on Gq' Client Activity**

Name	Vendor	Version	Class
net.java.slee.resource. diameter.gq.events. GqAAAnswer	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqAAAnswer
net.java.slee.resource. diameter.gq.events. GqAbortSessionRequest	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqAbortSessionRequest
net.java.slee.resource. diameter.gq.events. GqReAuthRequest	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqReAuthRequest
net.java.slee.resource. diameter.gq.events. GqSessionTerminationAnswer	java.net	0.8	net.java.slee.resource. diameter.gq.events. GqSessionTerminationAnswer



### Important

Spaces were introduced in Name and Event Class column values, to correctly render the table. Please remove them when using copy/paste.

## 2.3. Activity Context Interface Factory

The Mobicents Diameter Gq Activity Context Interface Factory is defined as follows:

```
package net.java.slee.resource.diameter.gq;

import javax.slee.ActivityContextInterface;
import javax.slee.UnrecognizedActivityException;

public interface GqActivityContextInterfaceFactory {
```

```

public ActivityContextInterface getActivityContextInterface(GqClientSessionActivity cSession)
    throws UnrecognizedActivityException;

public ActivityContextInterface getActivityContextInterface(GqServerSessionActivity sSession)
    throws UnrecognizedActivityException;
}

```

## 2.4. Resource Adaptor Interface

The Mobicents Diameter Gq Resource Adaptor SBB Interface provides SBBs with access to the Diameter objects required for creating and sending messages. It is defined as follows:

```

package net.java.slee.resource.diameter.gq;

import java.io.IOException;

import net.java.slee.resource.diameter.Validator;
import net.java.slee.resource.diameter.base.CreateActivityException;
import net.java.slee.resource.diameter.base.events.avp.DiameterIdentity;
import net.java.slee.resource.diameter.gq.events.GqAAAnswer;
import net.java.slee.resource.diameter.gq.events.GqAAResponse;
import net.java.slee.resource.diameter.gq.events.GqAbortSessionAnswer;
import net.java.slee.resource.diameter.gq.events.GqAbortSessionRequest;
import net.java.slee.resource.diameter.gq.events.GqReAuthAnswer;
import net.java.slee.resource.diameter.gq.events.GqReAuthRequest;

public interface GqProvider {

    public GqMessageFactory getGqMessageFactory();

    public GqAvpFactory getGqAvpFactory();

    public GqClientSessionActivity getActivityBySessionID(String sessionID);

    public GqClientSessionActivity createGqClientSessionActivity()
        throws CreateActivityException;

    public GqClientSessionActivity createGqClientSessionActivity(
        DiameterIdentity destinationHost,
        DiameterIdentity destinationRealm) throws CreateActivityException;
}

```

```
public GqAAAnswer sendGqAARequest(GqAARequest aar) throws IOException;

public GqAbortSessionAnswer sendGqAbortSessionRequest(
    GqAbortSessionRequest asr) throws IOException;

public GqReAuthAnswer sendGqReAuthRequest(
    GqReAuthRequest rar) throws IOException;

DiameterIdentity[] getConnectedPeers();

int getPeerCount();

Validator getValidator();
}
```

public GqMessageFactory getGqMessageFactory();

This method returns a message factory to be used to create concrete implementations of Gq' messages.

public GqAvpFactory getGqAvpFactory();

This method returns an avp factory to be used to create concrete implementations of Gq' credit control AVPs.

public GqClientSessionActivity getActivityBySessionID(String sessionID);

This method returns an existing Gq' activity by its Session-Id attribute and null if it doesn't exist.

public GqClientSessionActivity createGqClientSessionActivity() throws CreateActivityException;

This method creates a new activity to send and receive Diameter Gq' messages.

public GqClientSessionActivity createGqClientSessionActivity(DiameterIdentity destinationHost, DiameterIdentity destinationRealm) throws CreateActivityException;

This method creates a new activity to send and receive Diameter Gq' messages for the given host and/or realm.

public GqAAAnswer sendGqAARequest(GqAARequest aar) throws IOException;

This method sends an AA-Request message to the appropriate peers, and block until the response is received then return it.

public GqAbortSessionAnswer sendGqAbortSessionRequest(GqAbortSessionRequest asr) throws IOException;

This method sends an Abort-Session-Request message to the appropriate peers, and block until the response is received then return it.



```
public GqReAuthAnswer sendGqReAuthRequest(GqReAuthRequest rar) throws IOException;
```

This method sends an Re-Auth-Request message to the appropriate peers, and block until the response is received then return it.

```
public DiameterIdentity[] getConnectedPeers();
```

This method returns the identities of peers this Diameter resource adaptor is connected to.

```
public int getPeerCount();
```

This method returns the number of peers this Diameter resource adaptor is connected to.

```
public Validator getValidator();
```

This method returns the Diameter Message and AVP validator instance.

## 2.5. Restrictions

Current Resource Adaptor Type has no defined restrictions.

## 2.6. Sbb Code Examples

TODO

```
// TODO: Create Gq' Authorization Client/Server Examples.
```



# Resource Adaptor Implementation

This RA uses the Mobicents Diameter Stack, an improvement over [jDiameter Stack](http://jdiameter.dev.java.net) [http://jdiameter.dev.java.net]. The stack is the result of the work done by Mobicents Diameter and jDiameter development teams, and source code is provided in all releases.

## 3.1. Configuration

The Resource Adaptor supports configuration only at Resource Adaptor Entity creation time, the following table enumerates the configuration properties:

**Table 3.1. Resource Adaptor's Configuration Properties**

Property Name	Description	Property Type	Default Value
authApplicationIds	List of supported Authorization Application Ids in form of {vendor}: {application-id}, separated by comma ','	java.lang.String	10415:16777222



### Important

JAIN SLEE 1.1 Specification requires values set for properties without a default value, which means the configuration for those properties are mandatory, otherwise the Resource Adaptor Entity creation will fail!

## 3.2. Default Resource Adaptor Entities

There is a single Resource Adaptor Entity created when deploying the Resource Adaptor, named `DiameterGq`. The `DiameterGq` entity uses the default Resource Adaptor configuration, specified in [Section 3.1, "Configuration"](#).

The `DiameterGq` entity is also bound to Resource Adaptor Link Name `DiameterGq`, to use it in an Sbb add the following XML to its descriptor:

```
<resource-adaptor-type-binding>
  <resource-adaptor-type-ref>
    <resource-adaptor-type-name>Diameter Gq</resource-adaptor-type-name>
    <resource-adaptor-type-vendor>java.net</resource-adaptor-type-vendor>
```

```
<resource-adaptor-type-version>0.8.1</resource-adaptor-type-version>
</resource-adaptor-type-ref>

<activity-context-interface-factory-name>
  slee/resources/JDiameterGqResourceAdaptor/java.net/0.8.1/acif
</activity-context-interface-factory-name>

<resource-adaptor-entity-binding>
  <resource-adaptor-object-name>
    slee/resources/diameter-gq-ra-interface
  </resource-adaptor-object-name>
  <resource-adaptor-entity-link>DiameterGq</resource-adaptor-entity-link>
</resource-adaptor-entity-binding>
</resource-adaptor-type-binding>
```

## 3.3. Traces and Alarms

### 3.3.1. Tracers

Each Resource Adaptor Entity uses a single JAIN SLEE 1.1 Tracer, named `DiameterGqResourceAdaptor`. The related Log4j Logger category, which can be used to change the Tracer level from Log4j configuration, is `javax.slee.RAEntityNotification[entity=DiameterGq]`.

### 3.3.2. Alarms

No alarms are set by this Resource Adaptor.

# Setup

## 4.1. Pre-Install Requirements and Prerequisites

Ensure that the following requirements have been met before continuing with the install.

### 4.1.1. Hardware Requirements

The Resource Adaptor hardware's main concern is RAM memory and Java Heap size, the more the better. For instance, while the underlying Mobicents JAIN SLEE may run with 1GB of RAM, 8GB is needed to achieve performance higher than 800 new requests per second.

Of course, memory is only needed to store the Resource Adaptor state, the faster the CPU more requests per second are supported, yet no particular CPU is a real requirement to use the RA.

### 4.1.2. Software Prerequisites

The RA requires Mobicents JAIN SLEE properly set and Mobicents Diameter Multiplexer (MUX), which includes the stack, Mobicents Diameter Base RA and Mobicents Diameter CCA RA to be properly installed too.

## 4.2. Mobicents JAIN SLEE Diameter Gq Resource Adaptor Source Code

### 4.2.1. Release Source Code Building

#### 1. Downloading the source code



#### Important

Subversion is used to manage its source code. Instructions for using Subversion, including install, can be found at <http://svnbook.red-bean.com>

Use SVN to checkout a specific release source, the base URL is <http://mobicents.googlecode.com/svn/tags/servers/jain-slee/2.x.y/resources/diameter-gq>, then add the specific release version, lets consider 1.1.0-SNAPSHOT.

```
[usr]$ svn co http://mobicents.googlecode.com/svn/tags/servers/jain-slee/2.x.y/resources/diameter-gq/1.1.0-SNAPSHOT slee-ra-diameter-gq-1.1.0-SNAPSHOT
```

### 2. Building the source code



#### Important

Maven 2.0.9 (or higher) is used to build the release. Instructions for using Maven2, including install, can be found at <http://maven.apache.org>

Use Maven to build the deployable unit binary.

```
[usr]$ cd slee-ra-diameter-gq-1.1.0-SNAPSHOT
[usr]$ mvn install
```

Once the process finishes you should have the `deployable-unit` jar file in the `target` directory, if Mobicents JAIN SLEE is installed and environment variable `JBOSS_HOME` is pointing to its underlying JBoss Application Server directory, then the deployable unit jar will also be deployed in the container.

### 4.2.2. Development Trunk Source Building

Similar process as for [Section 4.2.1, "Release Source Code Building"](#), the only change is the SVN source code URL, which is <http://mobicents.googlecode.com/svn/trunk/servers/jain-slee/resources/diameter-gq>.

## 4.3. Installing Mobicents JAIN SLEE Diameter Gq Resource Adaptor

To install the Resource Adaptor simply execute provided ant script `build.xml` default target:

```
[usr]$ ant
```

The script will copy the RA deployable unit jar to the `default` Mobicents JAIN SLEE server profile deploy directory, to deploy to another server profile use the argument `-Dnode=`.

## 4.4. Uninstalling Mobicents JAIN SLEE Diameter Gq Resource Adaptor

To uninstall the Resource Adaptor simply execute provided ant script `build.xml` `undeploy` target:

```
[usr]$ ant undeploy
```

The script will delete the RA deployable unit jar from the `default` Mobicents JAIN SLEE server profile deploy directory, to undeploy from another server profile use the argument `-Dnode=`.





# Clustering

## 5.1. Failover

The Diameter stack used by the Mobicents JAIN SLEE Diameter Gq Resource Adaptor supports application session failover, with specific session state being replicated, thus only available for Application sessions. Failover of application activities is transparent to SLEE applications. This means that SLEE applications must be in charge of properly adapting its state machine to recover generic session on node failure.

## 5.2. Load Balancing

Currently, the only available balancing mechanism is provided by Diameter stack. It depends on [RFC 3588](http://tools.ietf.org/html/rfc3588) [http://tools.ietf.org/html/rfc3588] algorithm to select one peer from realm serving the desired application.



---

# Appendix A. Revision History

## Revision History

Revision 1.0

Mon Aug 15 2011

AlexandreMendonça

Creation of the Mobicents JAIN SLEE Diameter Gq RA User Guide.



---

# Index

## F

feedback, viii

